


Agilent T-1³/₄ (5 mm) Precision Optical Performance InGaN Blue and Green Lamps Data Sheet



**HLMP-CB15, HLMP-CB16, HLMP-CB30, HLMP-CB31,
HLMP-CM15, HLMP-CM16, HLMP-CM30, HLMP-CM31**

Description

These high intensity blue and green LEDs are based on InGaN material technology. InGaN is the most efficient and cost effective material for LEDs in the blue and green region of the spectrum. The 472 nm typical dominant wavelength for blue and 526 nm typical dominant wavelength for green are well suited to color mixing in full color signs.

These LED lamps are untinted, nondiffused, T-1³/₄ packages incorporating second generation optics producing well defined spatial radiation patterns at specific viewing cone angles.

These lamps are made with an advanced optical grade epoxy, offering superior high temperature and high moisture resistance performance in outdoor signal and sign applications. The high maximum LED junction temperature limit of +130°C enables high temperature operation in bright sunlight conditions. The package epoxy contains both UV-A and UV-B inhibitors to reduce the effects of long term exposure to direct sunlight.

These lamps are available in two viewing angle options to give the designer flexibility with optical design.

Features

- Well defined spatial radiation pattern
- Viewing angles: 15° and 30°
- High luminous output
- Colors: 472 nm Blue, 526 nm Green
- Superior resistance to moisture
- UV resistant epoxy

Benefits

- Superior performance in outdoor environments
- Wavelengths suitable for color mixing in full color (RGB) signs

Applications

- Commercial outdoor signs
- Automotive interior lights
- Front panel indicators
- Front panel backlighting

CAUTION: HLMP-CBxx and HLMP-CMxx LEDs are Class 1 ESD sensitive. Please observe appropriate precautions during handling and processing. Refer to Agilent Application Note AN-1142 for additional details.



LED Indicators


Device Selection Guide

| Part Number | Typical Viewing Angle | Color and Typ. Dominant Wavelength λ_d (nm) | Min. Luminous Intensity, I_v (mcd) at 20 mA | Typical Forward Voltage (V) at 20 mA | Leads with Stand-Offs | Package Drawing |
|-----------------|-----------------------|---|---|--------------------------------------|-----------------------|-----------------|
| HLMP-CB15-P00xx | 15° | Blue 472 | 880 | 3.8 | No | A |
| HLMP-CB15-R00xx | 15° | Blue 472 | 1500 | 3.5 | No | A |
| HLMP-CB15-QT0xx | 15° | Blue 472 | 1150 | 3.8 | No | A |
| HLMP-CB16-P00xx | 15° | Blue 472 | 880 | 3.8 | Yes | B |
| HLMP-CB16-QT0xx | 15° | Blue 472 | 1150 | 3.8 | Yes | B |
| HLMP-CB30-K00xx | 30° | Blue 472 | 310 | 3.8 | No | A |
| HLMP-CB30-KN0xx | 30° | Blue 472 | 310 | 3.8 | No | A |
| HLMP-CB30-M00xx | 30° | Blue 472 | 520 | 3.8 | No | A |
| HLMP-CB30-MQ0xx | 30° | Blue 472 | 520 | 3.8 | No | A |
| HLMP-CB30-NRGxx | 30° | Blue 472 | 680 | 3.8 | No | A |
| HLMP-CB31-M00xx | 30° | Blue 472 | 520 | 3.8 | Yes | B |
| HLMP-CB31-M0Gxx | 30° | Blue 472 | 520 | 3.8 | Yes | B |
| HLMP-CB31-NRGxx | 30° | Blue 472 | 680 | 3.8 | Yes | B |
| HLMP-CM15-S00xx | 15° | Green 526 | 1900 | 3.8 | No | A |
| HLMP-CM15-SV0xx | 15° | Green 526 | 1900 | 3.8 | No | A |
| HLMP-CM15-W00xx | 15° | Green 526 | 5500 | 3.5 | No | A |
| HLMP-CM15-VY0xx | 15° | Green 526 | 4200 | 3.8 | No | A |
| HLMP-CM16-S00xx | 15° | Green 526 | 1900 | 3.8 | Yes | B |
| HLMP-CM16-VY0xx | 15° | Green 526 | 4200 | 3.8 | Yes | B |
| HLMP-CM30-M00xx | 30° | Green 526 | 520 | 3.8 | No | A |
| HLMP-CM30-MQ0xx | 30° | Green 526 | 520 | 3.8 | No | A |
| HLMP-CM30-S00xx | 30° | Green 526 | 1900 | 3.5 | No | A |
| HLMP-CM30-TWAxx | 30° | Green 526 | 2500 | 3.8 | No | A |
| HLMP-CM31-M00xx | 30° | Green 526 | 520 | 3.8 | Yes | B |
| HLMP-CM31-TWAxx | 30° | Green 526 | 2500 | 3.8 | Yes | B |


Tolerance for intensity limit is $\pm 15\%$.

Part Numbering System


HLMP - X X XX - X X X XX



Package Dimensions



HLMP-Cx15 and HLMP-Cx30



HLMP-Cx16 and HLMP-Cx31

| HLMP-Cx16 | HLMP-Cx31 |
|-------------------------------------|-------------------------------------|
| d = 12.60 ± 0.25 (0.496 ± 0.010) | d = 12.22 ± 0.50 (0.481 ± 0.020) |

Notes:

1. Dimensions in mm.
2. Tolerance ±0.1 mm unless otherwise noted.

Absolute Maximum Ratings at T_A = 25°C

| Parameter | Blue and Green |
|---|---------------------|
| DC Forward Current ^[1] | 30 mA |
| Peak Pulsed Forward Current | 100 mA |
| Average Forward Current | 30 mA |
| Reverse Voltage (I _R = 100 μA) | 5 V |
| Power Dissipation | 120 mW |
| LED Junction Temperature | 130°C |
| Operating Temperature Range | -40°C to +80°C |
| Storage Temperature Range | -40°C to +100°C |
| Soldering Temperature | 260°C for 5 seconds |

Note:

1. Derate linearly as shown in Figure 5 for temperatures above 50°C.

Electrical/Optical Characteristics at T_A = 25°C

| Parameter | Symbol | Min. | Typ. | Max. | Units | Test Conditions |
|---------------------------------|---------------------|------|------|------|-------|---|
| Forward Voltage | V _F | | 3.5 | 4.0 | V | I _F = 20 mA |
| Reverse Voltage | V _R | 5 | | | | I _R = 100 μA |
| Peak Wavelength | | | | | | Peak of Wavelength of Spectral Distribution at I _F = 20 mA |
| Blue (λ _d = 472 nm) | λ _{peak} | | 470 | | nm | |
| Green (λ _d = 526 nm) | | | 524 | | | |
| Spectral Halfwidth | | | | | | Wavelength Width at Spectral Power Point at I _F = 20 mA |
| Blue (λ _d = 472 nm) | Δλ _{1/2} | | 35 | | nm | |
| Green (λ _d = 526 nm) | | | 47 | | | |
| Capacitance | C | | 43 | | pF | V _F = 0, F = 1 MHz |
| Luminous Efficacy | | | | | | Emitted Luminous Power/Emitted Radiant Power |
| Blue (λ _d = 472 nm) | η _v | | 75 | | lm/W | |
| Green (λ _d = 526 nm) | | | 520 | | | |
| Thermal Resistance | R _{ΘJ-PIN} | | 240 | | °C/W | LED Junction-to-Cathode Lead |




Figure 1. Relative intensity vs. wavelength.




Figure 2. Forward current vs. forward voltage for devices with 3.5 V typical V_f .




Figure 3. Forward current vs. forward voltage for devices with 3.8 V typical V_f .




Figure 4. Relative luminous intensity vs. forward current.




Figure 5. Maximum forward current vs. ambient temperature.




Figure 6. Spatial radiation pattern - 15° lamps.




Figure 7. Spatial radiation pattern - 30° lamps.




Figure 8. Color vs. forward current.

Color Bin Limits (nm at 20 mA)

| Blue | Color Range (nm) | |
|---------------|-------------------------|-------------|
| Bin ID | Min. | Max. |
| 1 | 460.0 | 464.0 |
| 2 | 464.0 | 468.0 |
| 3 | 468.0 | 472.0 |
| 4 | 472.0 | 476.0 |
| 5 | 476.0 | 480.0 |

Tolerance for each bin limit is ± 0.5 nm.

| Green | Color Range (nm) | |
|---------------|-------------------------|-------------|
| Bin ID | Min. | Max. |
| 1 | 520.0 | 524.0 |
| 2 | 524.0 | 528.0 |
| 3 | 528.0 | 532.0 |
| 4 | 532.0 | 536.0 |
| 5 | 536.0 | 540.0 |

Tolerance for each bin limit is ± 0.5 nm.

Intensity Bin Limits

| Bin Name | Min. | Max. |
|-----------------|-------------|-------------|
| K | 310 | 400 |
| L | 400 | 520 |
| M | 520 | 680 |
| N | 680 | 880 |
| P | 880 | 1150 |
| Q | 1150 | 1500 |
| R | 1500 | 1900 |
| S | 1900 | 2500 |
| T | 2500 | 3200 |
| U | 3200 | 4200 |
| V | 4200 | 5500 |
| W | 5500 | 7200 |
| X | 7200 | 9300 |
| Y | 9300 | 12000 |
| Z | 12000 | 16000 |

Tolerance for each intensity bin limit is $\pm 15\%$.

Note:

1. All bin categories are established for classification of products. Products may not be available in all bin categories. Please contact your Agilent representatives for further information.

www.agilent.com/semiconductors

For product information and a complete list of distributors, please go to our web site.

For technical assistance call:

Americas/Canada: +1 (800) 235-0312 or
(916) 788-6763

Europe: +49 (0) 6441 92460

China: 10800 650 0017

Hong Kong: (+65) 6271 2451

India, Australia, New Zealand: (+65) 6271 2394

Japan: (+81 3) 3335-8152(Domestic/International), or 0120-61-1280(Domestic Only)

Korea: (+65) 6271 2194

Malaysia, Singapore: (+65) 6271 2054

Taiwan: (+65) 6271 2654

Data subject to change.

Copyright © 2003 Agilent Technologies, Inc.

Obsoletes 5988-8658EN

August 1, 2003

5988-9962EN



Agilent Technologies