

General Description

The AAT9460 is a low threshold MOSFET designed for applications in DC-DC Converter, battery, cell phone, and PDA markets. Using AnalogicTech™'s ultra-high density proprietary TrenchDMOS™ technology, this product demonstrates high power handling and small size.


Features

- $V_{DS(MAX)} = 30V$
- $I_{D(MAX)}^1 = 3.4A @ 25^{\circ}C$
- Low $R_{DS(ON)}$:
 - $58 m\Omega @ V_{GS} = 4.5V$
 - $84 m\Omega @ V_{GS} = 2.5V$

Applications

- DC-DC Converters
- Battery Packs
- Cellular & Cordless Telephones
- Battery-powered portable equipment

SC59 Package



Absolute Maximum Ratings ($T_A=25^{\circ}C$ unless otherwise noted)

Symbol	Description	Value	Units
V_{DS}	Drain-Source Voltage	30	V
V_{GS}	Gate-Source Voltage	± 12	
I_D	Continuous Drain Current @ $T_J=150^{\circ}C$ ¹	$T_A = 25^{\circ}C$	A
		$T_A = 70^{\circ}C$	
I_{DM}	Pulsed Drain Current ²	± 8.0	
I_S	Continuous Source Current (Source-Drain Diode) ¹	1.0	W
P_D	Maximum Power Dissipation ¹	$T_A = 25^{\circ}C$	
		$T_A = 70^{\circ}C$	
T_J, T_{STG}	Operating Junction and Storage Temperature Range	-55 to 150	$^{\circ}C$

Thermal Characteristics

Symbol	Description	Value	Units
$R_{\theta JA}$	Typical Junction-to-Ambient steady state ¹	140	$^{\circ}C/W$
$R_{\theta JA2}$	Maximum Junction-to-Ambient $t < 5$ seconds ¹	115	
$R_{\theta JF}$	Typical Junction-to-Foot ¹	45	

Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise noted)

Symbol	Description	Conditions	Min	Typ	Max	Units
DC Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0V, I _D =-250μA	30			V
R _{DS(ON)}	Drain-Source ON-Resistance ²	V _{GS} =-4.5V, I _D =3.4A		46	58	mΩ
		V _{GS} =-2.5V, I _D =2.8A		65	84	
I _{D(ON)}	On-State Drain Current ²	V _{GS} =4.5V, V _{DS} =5V (Pulsed)	8			A
V _{GS(th)}	Gate Threshold Voltage	V _{GS} =V _{DS} , I _D =-250μA	0.6			V
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±12V, V _{DS} =0V			±100	nA
I _{DSS}	Drain Source Leakage Current	V _{GS} =0V, V _{DS} =30V			1	μA
		V _{GS} =0V, V _{DS} =24V, T _J =70°C ³			5	
g _{fs}	Forward Transconductance ²	V _{DS} =-5V, I _D =3.4A		9		S
Dynamic Characteristics ³						
Q _G	Total Gate Charge	V _{DS} =15V, R _D =4.2Ω, V _{GS} =4.5V		5		nC
Q _{GS}	Gate-Source Charge	V _{DS} =15V, R _D =4.2Ω, V _{GS} =4.5V		0.9		
Q _{GD}	Gate-Drain Charge	V _{DS} =15V, R _D =4.2Ω, V _{GS} =4.5V		1		
t _{D(ON)}	Turn-ON Delay	V _{DS} =15V, R _D =4.2Ω, V _{GS} =4.5V, R _G =6Ω		6		ns
t _R	Turn-ON Rise Time	V _{DS} =15V, R _D =4.2Ω, V _{GS} =4.5V, R _G =6Ω		3		
t _{D(OFF)}	Turn-OFF Delay	V _{DS} =15V, R _D =4.2Ω, V _{GS} =4.5V, R _G =6Ω		30		
t _F	Turn-OFF Fall Time	V _{DS} =15V, R _D =4.2Ω, V _{GS} =4.5V, R _G =6Ω		8		
Source-Drain Diode Characteristics						
V _{SD}	Source-Drain Forward Voltage ²	V _{GS} =0, I _S =3.4A			1.3	V
I _S	Continuous Diode Current ¹				1.0	A

Note 1: Based on thermal dissipation from junction to ambient while mounted on a 1" x 1" PCB with optimized layout. A 5 second pulse on a 1" x 1" PCB approximates testing a device mounted on a large multi-layer PCB as in many applications. $R_{\theta JF} + R_{\theta FA} = R_{\theta JA}$ where the foot thermal reference is defined as the normal solder mounting surface of the device's leads. $R_{\theta JF}$ is guaranteed by design; however, $R_{\theta FA}$ is determined by PCB design. Actual maximum continuous current is limited by the application's design.


Note 2: Pulse test: Pulse width = 300 μs .

Note 3: Guaranteed by design. Not subject to production testing.


Typical Characteristics

($T_J = 25^\circ\text{C}$ unless otherwise noted)


Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current




On-Resistance vs. Gate to Source Voltage



On-Resistance vs. Junction Temperature




Threshold Voltage




Typical Characteristics

($T_J = 25^\circ\text{C}$ unless otherwise noted)


Gate Charge



Source-Drain Diode Forward Voltage



Capacitance






Ordering Information

Package	Marking	Part Number (Tape and Reel)
SC59	HA	AAT9460IGY-T1

Package Information

SC59



All dimensions in millimeters.

AnalogicTech cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in an AnalogicTech product. No circuit patent licenses, copyrights, mask work rights, or other intellectual property rights are implied.

AnalogicTech reserves the right to make changes to their products or specifications or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

AnalogicTech warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with AnalogicTech's standard warranty. Testing and other quality control techniques are utilized to the extent AnalogicTech deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed.

Advanced Analogic Technologies, Inc.
830 E. Arques Avenue, Sunnyvale, CA 94085
Phone (408) 737-4600
Fax (408) 737-4611