

HIGH FREQUENCY MAGNETICS

T1/E1 Through Hole Shielded Transformer

TM00124


- Designed for DS1, DS1C, and CEPT applications
- Electrostatic shield provides improved longitudinal signal suppression
- 2741J has an internal connection to terminal 8; do not use
- Operating temperature range: -40° C to +85° C
- Meets IEC 695, 2-2 flammability requirements
- PWB Process Capability: standard printed wiring board assembly techniques, total-immersion cleaning
- Reliability testing: Shock, vibration, temperature cycling, temperature - humidity - bias

ELECTRICAL SPECIFICATIONS AT 25° C

Part Number	Turns Ratio ±2%	Primary Inductance ¹ mH min	DCR Ω max		Leakage Inductance ² μH max	Interwinding Capacitance ⁴ pF max	Minimum Interwinding Breakdown Voltage Vrms
	Pri : Sec		Pri	Sec			
2741J	1 CT ³ : 1.37	0.92 ³	0.8 ³	1.25	2.0 ³	8	850
2741K	1 : 1	1.25	0.7	0.85	2.0	3.5	500

1. measured at 10 kHz, 0.1 Vac
2. measured at 100 kHz, 0.1 Vac
3. connect 2 and 6
4. with pin 1 grounded

SCHEMATIC




HIGH FREQUENCY MAGNETICS

T1/E1 Through Hole Shielded Transformer

MECHANICAL

2741J
2741K



Unless otherwise specified, dimensions are nominal and in inches (millimeters).

©2000 Bel Fuse Inc. Specifications subject to change without notice. 09.00

CORPORATE

Bel Fuse Inc.
198 Van Vorst Street
Jersey City, NJ 07302
Tel 201-432-0463
Fax 201-432-9542
www.belfuse.com

T1-54

FAR EAST

Bel Fuse Ltd.
8F / 8 Luk Hop Street
San Po Kong
Kowloon, Hong Kong
Tel 852-2328-5515
Fax 852-2352-3706
www.belfuse.com

EUROPE

Bel Fuse Europe Ltd.
Preston Technology Management Centre
Marsh Lane, Suite G7, Preston
Lancashire, PR1 8UD, U.K.
Tel 44-1772-556601
Fax 44-1772-888366
www.belfuse.com