

NEC's 7.5 V UHF BAND RF POWER SILICON LD-MOS FET

NE5511279A


FEATURES

- **HIGH OUTPUT POWER:**
 $P_{out} = 40.0 \text{ dBm TYP.}$, $f = 900 \text{ MHz}$, $V_{DS} = 7.5 \text{ V}$,
 $P_{out} = 40.5 \text{ dBm TYP.}$, $f = 460 \text{ MHz}$, $V_{DS} = 7.5 \text{ V}$,
- **HIGH POWER ADDED EFFICIENCY:**
 $\eta_{add} = 48\% \text{ TYP.}$, $f = 900 \text{ MHz}$, $V_{DS} = 7.5 \text{ V}$,
 $\eta_{add} = 50\% \text{ TYP.}$, $f = 460 \text{ MHz}$, $V_{DS} = 7.5 \text{ V}$,
- **HIGH LINEAR GAIN:**
 $G_L = 15.0 \text{ dB TYP.}$, $f = 900 \text{ MHz}$, $V_{DS} = 7.5 \text{ V}$,
 $G_L = 18.5 \text{ dB TYP.}$, $f = 460 \text{ MHz}$, $V_{DS} = 7.5 \text{ V}$,
- **SURFACE MOUNT PACKAGE:**
 $5.7 \times 5.7 \times 1.1 \text{ mm MAX}$
- **SINGLE SUPPLY:**
 $V_{DS} = 2.8 \text{ to } 8.0 \text{ V}$

APPLICATIONS

- UHF RADIO SYSTEMS
- CELLULAR REPEATERS
- TWO-WAY RADIOS
- FRS/GMRS
- FIXED WIRELESS

OUTLINE DIMENSIONS (Units in mm)



DESCRIPTION


NEC's NE5511279A is an N-Channel silicon power laterally diffused MOSFET specially designed as the transmission power amplifier for 7.5 V radio systems. Die are manufactured using NEC's NEWMOS1 technology and housed in a surface mount package. This device can deliver 40.0 dBm output power with 48% power added efficiency at 900 MHz using a 7.5 V supply voltage.

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)

SYMBOL	PARAMETER	MIN	TYP	MAX	UNIT	TEST CONDITIONS
P_{out}	Output Power	38.5	40.0	–	dBm	$f = 900 \text{ MHz}$, $V_{DS} = 7.5 \text{ V}$, $P_{in} = 27 \text{ dBm}$, $I_{DSQ} = 400 \text{ mA (RF OFF)}$
I_D	Drain Current	–	2.5	–	A	
η_{add}	Power Added Efficiency	42	48	–	%	
G_L	Linear Gain	–	15.0	–	dB	$P_{in} = 5 \text{ dBm}$
P_{out}	Output Power	–	40.5	–	dBm	$f = 460 \text{ MHz}$, $V_{DS} = 7.5 \text{ V}$, $P_{in} = 25 \text{ dBm}$, $I_{DSQ} = 400 \text{ mA (RF OFF)}$
I_D	Drain Current	–	2.75	–	A	
η_{add}	Power Added Efficiency	–	50	–	%	
G_L	Linear Gain	–	18.5	–	dB	$P_{in} = 5 \text{ dBm}$
I_{GSS}	Gate to Source Leak Current	–	–	100	nA	$V_{GS} = 6.0 \text{ V}$
I_{DSS}	Drain to Source Leakage Current (Zero Gate Voltage Drain Current)	–	–	100	nA	$V_{DS} = 8.5 \text{ V}$
V_{th}	Gate Threshold Voltage	1.0	1.5	2.0	V	$V_{DS} = 4.8 \text{ V}$, $I_{DS} = 1.5 \text{ mA}$
R_{th}	Thermal Resistance	–	5	–	$^\circ\text{C/W}$	Channel to Case
g_m	Transconductance	–	2.3	–	S	$V_{DS} = 3.5 \text{ V}$, $I_{DS} = 900 \text{ mA}$
BV_{DSS}	Drain to Source Breakdown Voltage	20	24	–	V	$I_{DSS} = 15 \mu\text{A}$

Notes:

DC performance is 100% tested. RF performance is tested on several samples per wafer.
 Wafer rejection criteria for standard devices is 1 reject for several samples.



RECOMMENDED SOLDERING CONDITIONS

This product should be soldered and mounted under the following recommended conditions. For soldering methods and conditions other than those recommended below, contact your nearby sales office.

Soldering Method	Soldering Conditions	Condition Symbol
Infrared Reflow	Peak temperature (package surface temperature) : 260°C or below Time at peak temperature : 10 seconds or less Time at temperature of 220°C or higher : 60 seconds or less Preheating time at 120 to 180°C : 120±30 seconds Maximum number of reflow processes : 3 times Maximum chlorine content of rosin flux (% mass) : 0.2%(Wt.) or below	IR260
VPS	Peak temperature (package surface temperature) : 215°C or below Time at temperature of 200°C or higher : 25 to 40 seconds Preheating time at 120 to 150°C : 30 to 60 seconds Maximum number of reflow processes : 3 times Maximum chlorine content of rosin flux (% mass) : 0.2%(Wt.) or below	VP215
Wave Soldering	Peak temperature (molten solder temperature) : 260°C or below Time at peak temperature : 10 seconds or less Preheating temperature (package surface temperature) : 120°C or below Maximum number of flow processes : 1 time Maximum chlorine content of rosin flux (% mass) : 0.2%(Wt.) or below	WS260
Partial Heating	Peak temperature (pin temperature) : 350°C or below Soldering time (per pin of device) : 3 seconds or less Maximum chlorine content of rosin flux (% mass) : 0.2%(Wt.) or below	HS350-P3

Caution Do not use different soldering methods together (except for partial heating).

Life Support Applications

These NEC products are not intended for use in life support devices, appliances, or systems where the malfunction of these products can reasonably be expected to result in personal injury. The customers of CEL using or selling these products for use in such applications do so at their own risk and agree to fully indemnify CEL for all damages resulting from such improper use or sale.

CEL California Eastern Laboratories, Your source for NEC RF, Microwave, Optoelectronic, and Fiber Optic Semiconductor Devices.
 4590 Patrick Henry Drive • Santa Clara, CA 95054-1817 • (408) 988-3500 • FAX (408) 988-0279 • www.cel.com

DATA SUBJECT TO CHANGE WITHOUT NOTICE

08/26/2003

Subject: Compliance with EU Directives

CEL certifies, to its knowledge, that semiconductor and laser products detailed below are compliant with the requirements of European Union (EU) Directive 2002/95/EC Restriction on Use of Hazardous Substances in electrical and electronic equipment (RoHS) and the requirements of EU Directive 2003/11/EC Restriction on Penta and Octa BDE.

CEL Pb-free products have the same base part number with a suffix added. The suffix –A indicates that the device is Pb-free. The –AZ suffix is used to designate devices containing Pb which are exempted from the requirement of RoHS directive (*). In all cases the devices have Pb-free terminals. All devices with these suffixes meet the requirements of the RoHS directive.

This status is based on CEL's understanding of the EU Directives and knowledge of the materials that go into its products as of the date of disclosure of this information.

Restricted Substance per RoHS	Concentration Limit per RoHS (values are not yet fixed)	Concentration contained in CEL devices	
Lead (Pb)	< 1000 PPM	-A	-AZ
		Not Detected	(*)
Mercury	< 1000 PPM	Not Detected	
Cadmium	< 100 PPM	Not Detected	
Hexavalent Chromium	< 1000 PPM	Not Detected	
PBB	< 1000 PPM	Not Detected	
PBDE	< 1000 PPM	Not Detected	

If you should have any additional questions regarding our devices and compliance to environmental standards, please do not hesitate to contact your local representative.

Important Information and Disclaimer: Information provided by CEL on its website or in other communications concerning the substance content of its products represents knowledge and belief as of the date that it is provided. CEL bases its knowledge and belief on information provided by third parties and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. CEL has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. CEL and CEL suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall CEL's liability arising out of such information exceed the total purchase price of the CEL part(s) at issue sold by CEL to customer on an annual basis.

See CEL Terms and Conditions for additional clarification of warranties and liability.