



PC Board Layout

ORDERING INFORMATION

FJ 260S--P_C-- --
 a b c d

- a: No. of position (8,10)
- b: No. of contact (8,10)
- c: Plating 6u" 15u" 30u" 50u"
- d: Option (K,N)



K:With keyway (8p&10p only)



N:No flangestop

MATERIAL: HOUSING-PBT POLYESTER UL94V-0
 COLOR-BLACK

CONTACTS-0.35mm THICKNESS ALLOY
 C5210 SELECTIVE GOLD PLATING

SHIELD-0.25mm THICKNESS COPPER
 ALLOY WITH TIN/NICKEL PLATED

UL.CUL File NO.: E166003

TOLERANCE .x ±0.3
 .xx ±0.20

XMULTIPLE		CONNECTING THE INFORMATION AGE	
XMULTIPLE ASIA 27, West Hill, Jackson St., Tsim Sha Tsui, Kowloon, H.K.	XMULTIPLE USA 2800 Old Country Road, Fountain Valley, CA 92708	DATE	REV
THIS DRAWING IS A CONTROLLED DOCUMENT.			
TITLE: Top Entry Shielded Modular Jack 180°		DRAWN	BY
PART NO: XRJ-FJ-260S		CHECKED	DATE
		1 of 1	A
		1/1/98	06/18/98