

International  
**IOR** Rectifier

**MBRS130TR**

**SCHOTTKY RECTIFIER**

**1 Amp**

$$I_{F(AV)} = 1.0 \text{ Amp}$$

$$V_R = 30V$$

#### Major Ratings and Characteristics

| Characteristics                   | Value       | Units      |
|-----------------------------------|-------------|------------|
| $I_{F(AV)}$ Rectangular waveform  | 1.0         | A          |
| $V_{RRM}$                         | 30          | V          |
| $I_{FSM}$ @ $t_p = 5 \mu s$ sine  | 230         | A          |
| $V_F$ @ 1.0A, $T_J = 125^\circ C$ | 0.42        | V          |
| $T_J$ range                       | - 55 to 125 | $^\circ C$ |


#### Description/ Features

The MBRS130TR surface-mount Schottky rectifier has been designed for applications requiring low forward drop and small foot prints on PC boards. Typical applications are in disk drives, switching power supplies, converters, free-wheeling diodes, battery charging, and reverse battery protection.

- Small foot print, surface mountable
- Very low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability

#### Case Styles

MBRS130TR



SMB

Cathode  Anode

## Voltage Ratings

| Part number                                     | MBRS130TR |
|---|-----------|
| $V_R$ Max. DC Reverse Voltage (V)               | 30        |
| $V_{RWM}$ Max. Working Peak Reverse Voltage (V) |           |

## Absolute Maximum Ratings

| Parameters   | Value | Units | Conditions  |  |
|--|-------|-------|---|--|
| I <sub>F(AV)</sub> Max. Average Forward Current  | 1.0   | A     | 50% duty cycle @ T <sub>L</sub> = 147 °C, rectangular wave form   |  |
| I <sub>FSM</sub> Max. Peak One Cycle Non-Repetitive Surge Current, T <sub>j</sub> = 25°C | 870   | A     | 5µs Sine or 3µs Rect. pulse   | Following any rated load condition and with rated V <sub>RRM</sub> applied |
|  | 50    |       | 10ms Sine or 6ms Rect. pulse  |  |
| E <sub>AS</sub> Non- Repetitive Avalanche Energy   | 3.0   | mJ    | T <sub>j</sub> = 25 °C, I <sub>AS</sub> = 1A, L = 6mH   |  |
| I <sub>AR</sub> Repetitive Avalanche Current   | 1.0   | A     | Current decaying linearly to zero in 1 µsec<br>Frequency limited by T <sub>j</sub> max. Va = 1.5 x Vr typical |  |

## Electrical Specifications

| Parameters      |  |     | Value | Units | Conditions  |                                       |
|-----------------|--|-----|-------|-------|---|---------------------------------------|
| V <sub>FM</sub> | Max. Forward Voltage Drop                              | (1) | 0.6   | V     | @ 1A  | T <sub>J</sub> = 25 °C                |
|                 |  |     | 0.67  | V     | @ 2A  |                                       |
|                 |  |     | 0.42  | V     | @ 1A  | T <sub>J</sub> = 125 °C               |
|                 |  |     | 0.52  | V     | @ 2A  |                                       |
| I <sub>RM</sub> | Max. Reverse Leakage Current                           | (1) | 0.5   | mA    | T <sub>J</sub> = 25 °C  | V <sub>R</sub> = rated V <sub>R</sub> |
|                 |  |     | 5.0   | mA    | T <sub>J</sub> = 100 °C   |                                       |
|                 |  |     | 15    | mA    | T <sub>J</sub> = 125 °C   |                                       |
| C <sub>T</sub>  | Max. Junction Capacitance                              |     | 200   | pF    | V <sub>R</sub> = 5V <sub>DC</sub> (test signal range 100KHz to 1Mhz) 25°C |                                       |
| L <sub>S</sub>  | Typical Series Inductance                              |     | 2.0   | nH    | Measured lead to lead 5mm from package body                               |                                       |
| dv/dt           | Max. Voltage Rate of Change<br>(Rated V <sub>R</sub> ) |     | 10000 | V/μs  |   |                                       |

(1) Pulse Width < 300 $\mu\text{s}$ , Duty Cycle < 2%

## Thermal-Mechanical Specifications

| Parameters   | Value       | Units              | Conditions          |
|--|-------------|--------------------|---------------------|
| $T_J$ Max. Junction Temperature Range (*)                | -55 to 125  | $^\circ\text{C}$   |                     |
| $T_{stg}$ Max. Storage Temperature Range                 | -55 to 150  | $^\circ\text{C}$   |                     |
| $R_{thJL}$ Max. Thermal Resistance Junction to Lead (**) | 25          | $^\circ\text{C/W}$ | DC operation        |
| $R_{thJA}$ Max. Thermal Resistance Junction to Ambient   | 80          | $^\circ\text{C/W}$ | DC operation        |
| wt Approximate Weight                                    | 0.10(0.003) | g (oz.)            |                     |
| Case Style   | SMB         |                    | Similar to DO-214AA |
| Device Marking   | IR13        |                    |                     |

(\*)  $\frac{dP_{tot}}{dT_J} < \frac{1}{R_{th(j-a)}}$  thermal runaway condition for a diode on its own heatsink

(\*\*) Mounted 1 inch square PCB




Fig. 1 - Maximum Forward Voltage Drop Characteristics




Fig. 2 - Typical Peak Reverse Current Vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage




Fig. 4 - Maximum Average Forward Current  
Vs. Allowable Lead Temperature




Fig. 5 - Maximum Average Forward Dissipation  
Vs. Average Forward Current





Fig. 6 - Maximum Peak Surge Forward Current Vs. Pulse Duration

(2) Formula used:  $T_C = T_J - (P_d + P_{d_{REV}}) \times R_{thJC}$ ;


$P_d$  = Forward Power Loss =  $I_{F(AV)} \times V_{FM} @ (I_{F(AV)} / D)$  (see Fig. 6);

$P_{d_{REV}}$  = Inverse Power Loss =  $V_{R1} \times I_R (1 - D)$ ;  $I_R @ V_{R1} = 80\% \text{ rated } V_R$

Outline Table



Marking & Identification




MBRS130TR

Bulletin PD-20584 rev. E 07/04



Tape & Reel Information



Ordering Information Table

| Device Code |   |   |    |    |   |
|-------------|---|---|----|----|---|
| MBR         | S | 1   | 30 | TR | - |
| 1           | 2 | 3   | 4  | 5  | 6 |
| 1           | - | Schottky MBR Series                               |    |    |   |
| 2           | - | S = SMB   |    |    |   |
| 3           | - | Current Rating (1 = 1 A)                          |    |    |   |
| 4           | - | Voltage Rating (30 = 30V)                         |    |    |   |
| 5           | - | TR = Tape & Reel (3000 pieces)                    |    |    |   |
| 6           | - | • none = Standard Production<br>• PbF = Lead-Free |    |    |   |

Data and specifications subject to change without notice.  
This product has been designed and qualified for Industrial Level.  
Qualification Standards can be found on IR's Web site.



IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
TAC Fax: (310) 252-7309  
Visit us at [www.irf.com](http://www.irf.com) for sales contact information. 07/04