


## UNCONTROLLED DOCUMENT

| PAR1   | NUMBER   |
|--------|----------|
| SSL-L> | <25783GD |

| REV. | E.C.N. NUMBER AND REVISION COMMENTS | DATE    |
|------|-------------------------------------|---------|
| Α    | CHANGED PEAK WAVELENGTH.            | 9.23.92 |
| В    | UPDATED SPECS.                      | 3.6.95  |
| C    | F.C.N. #10702                       | 1 10 01 |







| ELECTRO-OPTICAL CHARACTERISTICS TA=25°C I f= 20mA |           |          |     |          |                       |
|---|-----------|----------|-----|----------|-----------------------|
| PARAMETER   | MIN       | TYP      | MAX | UNITS    | TEST COND             |
| PEAK WAVELENGTH                                   |           | 565      |     | nm       |                       |
| FORWARD VOLTAGE                                   |           | 2.0      | 2.8 | $V_{f}$  |                       |
| REVERSE VOLTAGE                                   | 5.0       |          |     | $V_r$    | I <sub>r</sub> =100µA |
| AXIAL INTENSITY                                   |           | 9        |     | mcd      | $I_f = 20 \text{mA}$  |
| VIEWING ANGLE                                     |           | 110      |     | 2x theta |                       |
| EMITTED COLOR:                                    | GREEN     |          |     |          |                       |
| EPOXY LENS FINISH                                 | : GREEN [ | DIFFUSED |     |          |                       |

| LIMITS | OF | SAFE | OPERATION | ΑT | 25°C | PER DIE |  |
|--------|----|------|-----------|----|------|---------|--|
|        |    |      |           |    |      |         |  |

| PARAMETER                | MAX          | UNITS      |
|--------------------------|--------------|------------|
| PEAK FORWARD CURRENT*    | 150          | mA         |
| STEADY CURRENT           | 25           | mA         |
| POWER DISSIPATION        | 105          | mW         |
| DERATE FROM 25°C         | - 1.2        | mW/°C      |
| OPERATING, STORAGE TEMP. | -40  TO  +85 | •C         |
| SOLDERING TEMP.          | + 260        | •C         |
| 2.0mm FROM BODY          |              | 3 SEC. MAX |

\* t<10µS

\*UNCONTROLLED DOCUMENT\*

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN=  $\frac{+0.00}{-0.000}$  MAX. =  $\frac{+0.00}{-0.000}$  MAX.

REV.

PART NUMBER SSL-LX25783GD

2.3mm x 8mm RECTANGULAR LED, GREEN DIFFUSED.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC.. THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw

DRAWN BY:

CHECKED BY: APPROVED BY: DATE:

4.26.90 PAGE: 1 OF 1

CT

SCALE: N/A