


DESCRIPTION

A red and green lamp made of GaAlAs, GaP offering a changing color characteristic dependent on the direction the lamp is biased. These two light emitting diodes are mounted in a $\phi 4.8$ mm dual color, clear transparent lens.



ABSOLUTE MAXIMUM RATINGS

Power Dissipation @ $T_a=25^\circ\text{C}$

Forward Current, DC (IF)

Reverse Voltage

Operating & Storage Temperature Range

Lead Temperature

RED	GREEN
100mW	100mW
40mA	30mA
5V	5V
-55 to +100°C	
260°C	

ELECTRO-OPTICAL CHARACTERISTICS

($T_a=25^\circ\text{C}$)

PARAMETER	SYMBOL	RED	GREEN	UNIT	CONDITIONS
Forward Voltage	MAX VF	2.4	3.0	V	IF=20mA
Reverse Breakdown Voltage	MIN BVR	5	5	V	IR=100 μ A
Luminous Intensity	MIN IV	180	100	mcd	IF=20mA
	TYP	300	200	mcd	
Peak Wavelength	TYP λ_p	660	570	nm	IF=20mA
Spectral Line Half Width	TYP $\Delta\lambda$	20	30	nm	IF=20mA



MICRO ELECTRONICS LTD. 美科有限公司

38, Hung To Road, Microtron Building, Kwun Tong, Kowloon, Hong Kong.

Kwun Tong P.O. Box 69477 Hong Kong. Fax No. 2341 0321 Telex: 43510 Micro Hx. Tel: 2343 0181-5