

High IP3

Low Noise Amplifier

50Ω 950 to 2150 MHz

NEW!

ZRL-2150

Maximum Ratings

Operating Temperature	-40°C to 80°C case
	-40°C to 60°C ambient
Storage Temperature	-55°C to 100°C
DC Voltage	+17V max.

Features

- high IP3, +33 dBm typ.
- low noise figure, 1.5 dB typ.
- broadband flat gain response
- excellent return loss, 20 dB typ.
- internal voltage regulated
- over voltage and transient protected

Applications

- PCS, UMTS
- mobil satellite service
- baseband amp, fiber optic driver
- defense and aeronautical




BLUE CELL™

CASE STYLE: FJ893

PRICE: \$119.95 ea. QTY (1-9)

Outline Drawing







Electrical Specifications (T_{AMB} = 25°C)

FREQ. RANGE (MHz)	GAIN (dB)		Flatness		NOISE FIGURE (dB)		MAXIMUM POWER (dBm)		INTER- CEPT POINT IP3 dBm Typ.*	VSWR (:1) Typ.		DIRECTIVITY (dB) Typ.	DC POWER	
f _L - f _U	Typ.	Min.	Typ.	Max.	Typ.	Max.	Output (1 dB Comp.) Typ. Min.	Input (no damage) Typ. Min.		In	Out		Volt ¹ Typ.	Max. Current (mA)
950-2150	25	22.5	±1.1	±1.8	15	22	22	17.5	33	1.3	1.2	26	12	280
1500-2000	25	23	±0.9	±1.5	13	2.0	24	22	34	1.3	1.2	21	12	280

¹ Other voltages available in the 6.5 to 17V range, please contact factory.

Outline Dimensions (inch)

A	B	C	D	E	F	G	H	J
2.00	3.75	.80	3.00	.19	3.374	1.624	.156	.44
50.80	95.25	20.32	76.20	4.83	85.70	41.25	3.96	11.18
K	L	M	N	P	Q	R	S	wt.
.26	1.00	.51	.22	.26	—	.19	.10	grams
6.60	25.40	12.95	5.59	6.60	—	4.83	2.54	135



Mini-Circuits®

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

ISO 9001 CERTIFIED

INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

REV. A
M92817
ZRL-2150
EDB021202
BLUE/RS/CP
0406