

1/4 DUTY LCD DRIVER


GENERAL DESCRIPTION

The NJU6437 is a 1/4 duty LCD driver for segment type LCD panel.

The LCD driver consists of 4-common and 32-segment drives up to 128 segments.

The rectangle outline is useful the COG applications.

PACKAGE OUTLINE




FEATURES


NJU6437C

- 32 Segment Drivers
- Duty and Bias Ratio : 1/4Duty, 1/3Bias(up to 128 segments)
- Serial Data Transmission (Shift Clock 2MHz max.)
- Oscillation Circuit On-chip
- Display Off Function (INH Terminal)
- Operating Voltage --- 2.4~3.6V
- LCD Driving Voltage --- 6.0V Max.
- Package Outline --- Chip / Bumped Chip
- C-MOS Technology

BLOCK DIAGRAM



PAD LOCATION



■ : 4th Mark is the Alignment Mark.
The Alignment Mark is useful the COG Assembly.

■ PAD COORDINATES

Chip Size 4.0x1.5mm(Chip Center X=0 μ m, Y=0 μ m)

No	PAD NAME	X=(μ m)	Y=(μ m)	No	PAD NAME	X=(μ m)	Y=(μ m)
1	INH	-1716.5	-575.0	26	SEG ₁₆	253.5	579.0
2	CE	-1406.5	-575.0	27	SEG ₁₇	153.5	579.0
3	SCL	-1076.5	-575.0	28	SEG ₁₈	53.5	579.0
4	DN	-766.5	-575.0	29	SEG ₁₉	-46.5	579.0
5	TEST	-485.0	-575.0	30	SEG ₂₀	-146.5	579.0
6	V ₁	100.0	-575.0	31	SEG ₂₁	-246.5	579.0
7	V ₂	458.5	-575.0	32	SEG ₂₂	-346.5	579.0
8	V _{LCD}	858.5	-575.0	33	SEG ₂₃	-446.5	579.0
9	V _{DD}	1258.5	-575.0	34	SEG ₂₄	-546.5	579.0
10	V _{SS}	1658.5	-575.0	35	SEG ₂₅	-646.5	579.0
11	SEG ₁	1753.5	579.0	36	SEG ₂₆	-746.5	579.0
12	SEG ₂	1653.5	579.0	37	SEG ₂₇	-846.5	579.0
13	SEG ₃	1553.5	579.0	38	SEG ₂₈	-946.5	579.0
14	SEG ₄	1453.5	579.0	39	SEG ₂₉	-1046.5	579.0
15	SEG ₅	1353.5	579.0	40	SEG ₃₀	-1146.5	579.0
16	SEG ₆	1253.5	579.0	41	SEG ₃₁	-1246.5	579.0
17	SEG ₇	1153.5	579.0	42	SEG ₃₂	-1346.5	579.0
18	SEG ₈	1053.5	579.0	43	COM ₁	-1446.5	579.0
19	SEG ₉	953.5	579.0	44	COM ₂	-1546.5	579.0
20	SEG ₁₀	853.5	579.0	45	COM ₃	-1646.5	579.0
21	SEG ₁₁	753.5	579.0	46	COM ₄	-1746.5	579.0
22	SEG ₁₂	653.5	579.0	ALIGNMENT	ALI_A1	-1848.0	579.0
23	SEG ₁₃	553.5	579.0	ALIGNMENT	ALI_A2	1855.0	579.0
24	SEG ₁₄	453.5	579.0	ALIGNMENT	ALI_B1	-1848.0	-579.0
25	SEG ₁₅	353.5	579.0	ALIGNMENT	ALI_B2	1848.0	-579.0

■ TERMINAL DESCRIPTION

NO.	SYMBOL	F U N C T I O N
1	INH	Display-Off Control Terminal : When display goes to off, the before display Off data in the shift-register is retained. "H" : Display-Off "L" : Display-On
2	CE	Chip Enable Signal Input Terminal : "H" : LCD display data "L" : Disable
3	SCL	Serial Data Transmission Clock Input Terminal : LCD display data are input synchronized SCL clock signal rise edge.
4	DN	Serial Data Input Terminal Data input timing : SCL clock rise edge
6	V ₁	LCD Driving Voltage Adjust Terminal
7	V ₂	LCD Driving Voltage Adjust Terminal
8	V _{LCD}	Power Supply for LCD Driving
9	V _{DD}	Power Supply (+3V)
10	V _{SS}	Power Supply (0V)
11~42	SEG ₁ ~ SEG ₃₂	LCD Segment Output Terminals
43~46	COM ₁ ~ COM ₄	LCD Common Output Terminals

■ FUNCTIONAL DESCRIPTION

(1) Operation of each block

(1-1) Oscillation Circuit :

This circuits supply the basical clock signal to other circuits like as common driver and segment driver.

(1-2) Shift-Register

When the CE terminal is "H" (Enable mode), the display data is transferred to the shift-register synchronized by the shift clock on the SCL terminal.

(1-3) Common Divider Circuit


This circuit divides the oscillating signal to generate the common timing.

(1-4) Segment Divider Circuit

This circuit divides the oscillating signal to generate the segment timing.

(1-5) The LCD Driving Voltage Adjust circuit

The incorporated Bleeder Resistance sets 1/3 bias, and LCD Driver ability can be increased by connecting external resistance.



NJU6437

(2) Display Data input timing, correspond to segment and common terminal

When the CE terminal is "H" (Enable mode), the display data is transferred to the shift-register synchronized by the shift clock on the SCL terminal.

When the power is turned on, whole data in the shift-register are "L".

- ※ Whole 128bits data transfer to the shift register. When the input data is less than 128 bits, parts which bit data is inputted corresponded to display, and segment which correspond to the rest part in "off".


In case of over then 128bits, front 128bits from fall edge of "CE" signal is valid.

• Input data correspond to Segment Status

The "H" input data correspond to segment "ON" and "L" correspond to "OFF".

Data (D1...D128)	Segment Status
"H"	ON
"L"	OFF

• Display Data Correspond to Segment Status



(2-3) Display Data Correspond to Segment and Common Terminals

Segment	Data	COM ₁	COM ₂	COM ₃	COM ₄
SEG ₁	D ₁ D ₂ D ₃ D ₄	○	○	○	○
SEG ₂	D ₅ D ₆ D ₇ D ₈	○	○	○	○
⋮	⋮	⋮	⋮	⋮	⋮
SEG ₃₁	D ₁₂₁ D ₁₂₂ D ₁₂₃ D ₁₂₄	○	○	○	○
SEG ₃₂	D ₁₂₅ D ₁₂₆ D ₁₂₇ D ₁₂₈	○	○	○	○

ABSOLUTE MAXIMUM RATINGS

(Ta=25°C)

PARAMETER	SYMBOL	RATING	UNIT
Operating Voltage (1)	V _{DD}	-0.3 ~ +7.0	V
Operating Voltage (2)	V _{LCD}	-0.3 ~ +7.0	V
Operating Voltage (3)	V ₁ , V ₂	-0.3 ~ +7.0	V
Input Voltage	V _{IN}	-0.3 ~ V _{DD}	V
Operating Temperature	T _{opr}	-20 ~ +75	°C
Storage Temperature	T _{stg}	-55 ~ +125	°C

Note 1) If the LSI are used on condition above the absolute maximum ratings, the LSI may be destroyed. Using the LSI within electrical characteristics is strongly recommended for normal operation. Use beyond the electric characteristics conditions will cause malfunction and poor reliability.

Note 2) All voltage values are specified as V_{SS} = 0 V

Note 3) The relation: V_{LCD} ≥ V₂ ≥ V₁ ≥ V_{SS} must be maintained.

Note 4) Decoupling capacitor should be connected between V_{DD} and V_{SS} due to the stabilized operation.

ELECTRICAL CHARACTERISTICS

DC Characteristics

(Ta=25°C, V_{DD}=3.0~5.0V, V_{SS}=0V, V_{LCD}=6.0V)

PARAMETER		SYMBOL	C O N D I T I O N S		MIN	TYP	MAX	UNIT	NOTE
Operating	Recommend	V _{DD}	V _{DD} Terminal		2.4	3.0	3.6	V	
Voltage(1)	Available	V _{DD}	V _{DD} Terminal		2.4	3.0	5.5	V	
Operating Voltage (2)		V _{LCD}	V _{LCD} Terminal		2.0		6.0	V	
Operating Voltage (3)		V ₂	V ₂ Terminal		2.0	2/3V _{LCD}	V _{LCD}	V	
Operating Voltage (4)		V ₁	V ₁ Terminal		0.7	1/3V _{LCD}	V ₂	V	
"H" Input Voltage		V _{IH}	CE, SCL, DN, INH Terminals		0.7V _{DD}		V _{DD}	V	
"L" Input Voltage		V _{IL}	CE, SCL, DN, INH Terminals		V _{SS}		0.3V _{DD}	V	
"H" Input Current		I _{IH}	CE, SCL, DN, INH Term. , V _{IN} =V _{DD}				5	μA	
"L" Input Current		I _{IL}	CE, SCL, DN, INH Term. , V _{IN} =V _{SS}				5	μA	
"H" Output Voltage(1)		V _{OH} (1)	SEG ₁ ~SEG ₃₂ Term. , I _O = -1μA		V _{LCD} -0.6			V	5
"L" Output Voltage(1)		V _{OL} (1)	SEG ₁ ~SEG ₃₂ Term. , I _O = 1μA				V _{DD} +0.6	V	5
Middle Level Voltage 1/3 (1)		V _{MS1/3}	SEG ₁ ~SEG ₃₂ Term. , I _O = ±1μA		1/3V _{LCD} -0.6	1/3V _{LCD}	1/3V _{LCD} +0.6	V	5
Middle Level Voltage 2/3 (1)		V _{MS2/3}	SEG ₁ ~SEG ₃₂ Term. , I _O = ±1μA		2/3V _{LCD} -0.6	2/3V _{LCD}	2/3V _{LCD} +0.6	V	5
"H" Output Voltage(2)		V _{OH} (2)	COM ₁ ~COM ₄ Term. , I _O = -30μA		V _{LCD} -0.6			V	6
"L" Output Voltage(2)		V _{OL} (2)	COM ₁ ~COM ₄ Term. , I _O = 30μA				V _{SS} +0.6	V	6
Middle Level Voltage 1/3 (2)		V _{MC1/3}	COM ₁ ~COM ₄ Term. , I _O = ±1μA		1/3V _{LCD} -0.6	1/3V _{LCD}	1/3V _{LCD} +0.6	V	6
Middle Level Voltage 2/3 (2)		V _{MC2/3}	COM ₁ ~COM ₄ Term. , I _O = ±1μA		2/3V _{LCD} -0.6	2/3V _{LCD}	2/3V _{LCD} +0.6	V	6
Operating Current (1)		I _{SS}	V _{DD}	V _{DD} =5.0V V _{LCD} OPEN		16	30	μA	
			Terminal	V _{DD} =3.0V V _{LCD} OPEN		7.5	10		
Operating Current (2)		I _{LCD}	V _{LCD} Terminal V _{DD} =3.0V V _{LCD} =6.0V				12	μA	
Hysteresis Voltage		V _H	CE, SCL, DN, INH Terminal		V _{DD} =5.0V	0.3	0.6	V	
					V _{DD} =3.0V	0.3	1.0		

(Note 5) Segment terminals are open.


(Note 6) Common terminals are open.

AC Characteristics


(Ta=25°C, V_{DD}=3.0V, V_{SS}=0V, V_{LCD}=6.0V)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNIT
"L" Clock Pulse Width	t _{WCLL}	SCL	0.25	—	—	μs
"H" Clock Pulse Width	t _{WCLH}	SCL	0.25	—	—	μs
SCL Rise time, Fall time	t _r , t _f	SCL	—	—	50	ns
Data Set-up Time	t _{DS}	DN, SCL	0.25	—	—	μs
Data Hold Time	t _{DH}	SCL	0.25	—	—	μs
CE Set-up Time	t _{SCE}	CE, DN	1.25	—	—	μs
CE Hold Time	t _{HOLE}	SCL, CE	1.00	—	—	μs
"L" CE Pulse Width	t _{WCEL}	CE	4.00	—	—	μs
Frame Frequency	f _O	COM ₁ ~ COM ₄ , SEG ₁ ~ SEG ₃₂	V _{DD} =5.0V	45	75	Hz
			V _{DD} =3.0V	45	70	

Input Timing Characteristics



LCD Driving Waveform(1/4DUTY - 1/3BIAS)



• • •



To avoid the meaningless display, please keep the INH terminal at "H" until proper display data has been transferred.

be displayed should be transferred.

MEMO

[CAUTION]

The specifications on this databook are only given for information, without any guarantee as regards either mistakes or omissions. The application circuits in this databook are described only to show representative usages of the product and not intended for the guarantee or permission of any right including the industrial rights.