



April 1991

LM78MG/LM79MG

4-Terminal Adjustable Voltage Regulators

General Description


The LM78MG and LM79MG are 4-terminal adjustable voltage regulators. They are designed to deliver continuous load currents of up to 500 mA with a maximum input voltage of +40V for the positive regulator LM78MG and -40V for the negative regulator LM79MG. Output current capability can be increased to greater than 10A through use of one or more external transistors. The output voltage range of the LM78MG positive voltage regulator is 5.0V to 30V and the output voltage range of the negative LM79MG is -30V to -2.6V. For systems requiring both a positive and negative, the LM78MG and LM79MG are excellent for use as a dual tracking regulator.

Features

- Output current in excess of 0.5A
- LM78MG positive output voltage +5.0V to +30V
- LM79MG negative output voltage -30V to -2.6V
- Internal thermal overload protection
- Internal short circuit current protection
- Output transistor safe-area protection

Connection Diagrams

LM78MG




TL/H/10058-1

Top View

Heat sink tabs connected to Input through device substrate. Not recommended for direct electrical connection.

LM79MG



TL/H/10058-2

Top View

Heat sink tabs connected to Input through device substrate. Not recommended for direct electrical connection.

Ordering Information

Device Type	Device Code	Package Code	Package Description
Positive Adjustable Regulator	LM78MGCP	P04A	Molded 4-Lead TO-202
Negative Adjustable Regulator	LM79MGCP	P04A	Molded 4-Lead TO-202

Absolute Maximum Ratings

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

Storage Temperature Range	-65°C to +150°C	Input Voltage LM78MGC LM79MGC	+40V -40V
Operating Junction Temperature Range	0°C to +150°C	Control Lead Voltage LM78MGC LM79MGC	0V ≤ V+ ≤ VO VO- ≤ V- ≤ 0V
Lead Temperature (Soldering, 10 sec.)	265°C		
Internal Power Dissipation	Internally Limited		


LM78MGC

Electrical Characteristics 0°C ≤ TA ≤ 125°C for LM78MGC, VI = 10V, IO = 350 mA, CI = 0.33 μF, CO = 0.1 μF, Test Circuit 1, unless otherwise specified

Symbol	Parameter	Conditions (Notes 1, 3)	Min	Typ	Max	Units	
VI _R	Input Voltage Range	T _J = 25°C	7.5	40	40	V	
VO _R	Output Voltage Range	VI = VO + 5.0V	5.0	30	30	V	
VO	Output Voltage Tolerance	(VO + 3.0V) ≤ VI ≤ (VO + 15V), 5.0 mA ≤ IO ≤ 350 mA, PD ≤ 5.0W, VI _{MAX} = 38V			4.0	% (VO)	
VO LINE	Line Regulation	T _J = 25°C, IO = 200 mA, VO ≤ 10V, (VO + 2.5V) ≤ VI ≤ (VO + 20V), T _J = 25°C, IO = 200 mA, VO ≥ 10V			1.0	% (VO)	
VO LOAD	Load Regulation	T _J = 25°C, 5.0 mA ≤ IO ≤ 500 mA, VI = VO + 7.0V			1.0	% (VO)	
I _C	Control Lead Current	T _J = 25°C		1.0	6.0	μA	
					7.0		
I _Q	Quiescent Current	T _J = 25°C		2.8	5.0	mA	
					6.0		
RR	Ripple Rejection	IO = 125 mA, 8.0V ≤ VI ≤ 18V, VO = 5.0V, f = 2400 Hz	62	80		dB	
NO	Output Noise Voltage	10 Hz ≤ f ≤ 100 kHz, VO = 5.0V		8	40	μV/ VO	
V _{DO}	Dropout Voltage (Note 2)			2	2.5	V	
IO _S	Short Circuit Current	VI = 35V, T _J = 25°C			600	mA	
I _{PK}	Peak Output Current	T _J = 25°C	0.4	0.8	1.4	A	
ΔVO/ΔT	Average Temperature Coefficient of Output Voltage	VO = 5.0V, IO = 5.0 mA	T _A = -55°C to +25°C		0.4	mV/°C/ VO	
			T _A = 25°C to 125°C		0.3		
V _C	Control Lead Voltage (Reference)	T _J = 25°C		4.8	5.0	5.2	V
				4.75		5.25	

LM78MG Test Circuit 1

$VO = \left(\frac{R1 + R2}{R2} \right) V_{CONT}$
 V_{CONT} Nominally = 5V
 Recommended R2 current ≈ 1 mA
 R2 = 5 kΩ



TL/H/10058-20

LM79MGC

Electrical Characteristics $0^\circ\text{C} \leq T_J \leq 125^\circ\text{C}$ for LM79MGC, $V_I = -14\text{V}$, $I_O = 350\text{ mA}$, $C_I = 2.0\text{ }\mu\text{F}$, $C_O = 1.0\text{ }\mu\text{F}$, Test Circuit 2, unless otherwise specified

Symbol	Parameter	Conditions (Notes 1, 3 & 4)	Min	Typ	Max	Units
V_{IR}	Input Voltage Range	$T_J = 25^\circ\text{C}$	-40		-7.0	V
V_{OR}	Output Voltage Range	$V_I = V_O - 5.0\text{V}$	-30		-2.55	V
V_O	Output Voltage Tolerance	$(V_O - 15\text{V}) \leq V_I \leq (V_O - 3.0\text{V})$, $5.0\text{ mA} \leq I_O \leq 350\text{ mA}$, $P_D \leq 5.0\text{W}$, $V_{I\text{ Max}} = -38\text{V}$	$T_J = 25^\circ\text{C}$		4.0	% (V_O)
					5.0	
V_O LINE	Line Regulation	$T_J = 25^\circ\text{C}$, $I_O = 200\text{ mA}$, $V_O \leq -10\text{V}$, $(V_O - 20\text{V}) \leq V_I \leq (V_O - 2.5\text{V})$, $T_J = 25^\circ\text{C}$, $I_O = 200\text{ mA}$, $V_O \leq -10\text{V}$			1.0	% (V_O)
V_O LOAD	Load Regulation	$V_I = V_O - 7.0\text{V}$, $5.0\text{ mA} \leq I_O \leq 500\text{ mA}$, $T_J = 25^\circ\text{C}$			1.0	% (V_O)
I_C	Control Lead Current	$T_J = 25^\circ\text{C}$			2.0	μA
					3.0	
I_Q	Quiescent Current	$T_J = 25^\circ\text{C}$		2.1	7.0	mA
					8.0	
RR	Ripple Rejection	$T_J = 25^\circ\text{C}$, $I_O = 125\text{ mA}$, $V_I = -13\text{V}$, $V_O = -5.0\text{V}$, $f = 2400\text{ Hz}$	50			dB
No	Noise	$10\text{ Hz} \leq f \leq 100\text{ kHz}$, $V_O = -8.0\text{V}$, $I_L = 50\text{ mA}$		25	80	$\mu\text{V}/V_O$
V_{DO}	Dropout Voltage (Note 2)			-1.1	-2.3	V
I_{OS}	Short Circuit Current	$V_I = 35\text{V}$, $T_J = 25^\circ\text{C}$			600	mA
I_{pk}	Peak Output Current		0.4	0.65	1.4	A
$\Delta V_O/\Delta T$	Average Temperature Coefficient of Output Voltage	$V_O = -5.0\text{V}$, $I_O = -5.0\text{ mA}$	$T_A = -55^\circ\text{C}$ to $+25^\circ\text{C}$		0.3	$\text{mV}/^\circ\text{C}/V_O$
			$T_A = 25^\circ\text{C}$ to 125°C		0.3	
V_C	Control Lead Voltage (Reference)	$T_J = 25^\circ\text{C}$	-2.65	-2.55	-2.45	V
				-2.68	-2.43	


Note 1: V_O is defined for the LM78MGC as $V_O = \frac{R_1 + R_2}{R_2}(5.0)$; the LM79MGC as $V_O = \frac{R_1 + R_2}{R_2}(-2.55)$.

Note 2: Dropout voltage is defined as that input/output voltage differential which causes the output voltage to decrease by 5% of its initial value.

Note 3: All characteristics except noise voltage and ripple rejection ratio are measured using pulse techniques ($t_W \leq 10\text{ ms}$, duty cycle $\leq 5\%$). Output voltage changes due to changes in internal temperature must be taken into account separately.


Note 4: The convention for negative regulators is the Algebraic value, thus -15V is less than -10V .

LM79MG Test Circuit 2




TLH/10058-22

LM78MG Equivalent Circuit



TL/H/10058-3

LM79MG Equivalent Circuit (Note 1)



Design Considerations

The LM78MG and LM79MG variable voltage regulators have an output voltage which varies from V_{CONT} to typically

$$V_I - 2.0V \text{ by } V_O = V_{CONT} \frac{(R_1 + R_2)}{R_2}$$

The nominal reference in the LM78MG is 5.0V and LM79MG is -2.55V. If we allow 1.0 mA to flow in the control swing to eliminate bias current effects, we can make $R_2 = 5 \text{ k}\Omega$ in the LM78MG. The output voltage is then: $V_O = (R_1 + R_2) \text{ Volts}$, where R_1 and R_2 are in k Ω s.

Example: If $R_2 = 5.0 \text{ k}\Omega$ and $R_1 = 10 \text{ k}\Omega$ then

$$V_O = 15V \text{ nominal, for the LM78MG;}$$

$$R_2 = 2.6 \text{ k}\Omega \text{ and } R_1 = 13 \text{ k}\Omega \text{ then}$$

$$V_O = -15.3V \text{ nominal, for the LM79MG.}$$

By proper wiring of the feedback resistors, load regulation of the devices can be improved significantly.

Both LM78MG and LM79MG regulators have thermal overload protection from excessive power, internal short circuit protection which limits each circuit's maximum current, and output transistor safe-area protection for reducing the output current as the voltage across each pass transistor is increased.

Although the internal power dissipation is limited, the junction temperature must be kept below the maximum specified temperature in order to meet data sheet specifications. To calculate the maximum junction temperature or heat sink required, the following thermal resistance values should be used:

Package	Typ θ_{JC}	Max θ_{JC}	Typ θ_{JA}	Max θ_{JA}
Power Watt	8.0	12.0	70	75

$$P_D \text{ Max} = \frac{T_J \text{ Max} - T_A}{\theta_{JC} + \theta_{CA}} \text{ or}$$

$$\frac{T_J \text{ Max} - T_A}{\theta_{JA}} \text{ (without a heat sink)}$$

$$\theta_{CA} = \theta_{CS} + \theta_{SA}$$

Solving for T_J :

$$T_J = T_A + P_D(\theta_{JC} + \theta_{CA}) \text{ or}$$

$$T_A + P_D \theta_{JA} \text{ (without heat sink)}$$

Where

T_J = Junction Temperature

T_A = Ambient Temperature

P_D = Power Dissipation

θ_{JC} = Junction-to-Case Thermal Resistance

θ_{CA} = Case-to-Ambient Thermal Resistance

θ_{CS} = Case-to-Heat Sink Thermal Resistance

θ_{SA} = Heat Sink-to-Ambient Thermal Resistance

θ_{JA} = Junction-to-Ambient Thermal Resistance


Typical Applications for LM78MG (Note 1)

Bypass capacitors are recommended for stable operation of the LM78MG over the input voltage and output current ranges. Output bypass capacitors will improve the transient response of the regulator.

The bypass capacitors, (0.33 μ F on the input, 0.1 μ F on the output) should be ceramic or solid tantalum which have good high frequency characteristics. The bypass capacitors should be mounted with the shortest leads, and if possible, directly across the regulator terminals.

Note 1: All resistor values in ohms.


Basic Positive Regulator



TL/H/10058-8


$$V_O = V_{CONT} \left(\frac{R_1 + R_2}{R_2} \right)$$

Positive 5.0V to 30V Adjustable Regulator



TL/H/10058-9

Positive 5.0V to 30V Adjustable Regulator $I_O > 1.5A$




TL/H/10058-10

$$R_1 = \frac{\beta V_{BE}(Q1)}{I_R \text{ Max}(\beta) - I_0}$$

Typical Applications for LM78MG (Note 1) (Continued)


$\pm 10V, 500 \text{ mA}$ Dual Tracking Regulator



TL/H/10058-11

Note: External series pass device is not short circuit protected.

Positive High Current Short Circuit Protected Regulator




TL/H/10058-14


$$R1 = \frac{\beta V_{BE}(Q1)}{V_R \text{ Max}(\beta + 1) - I_O \text{ Max}}$$

If load is not ground referenced, connect reverse biased diodes from outputs to ground.

Positive High-Current Voltage Regulator




TL/H/10058-12



TL/H/10058-13


External Series Pass (a)



TL/H/10058-15

Short-Circuit Limit (b)

Output Waveform



TL/H/10058-16


Note 1: All resistor values in ohms.

Typical Applications for LM79MG (Note 1)

Bypass capacitors are recommended for stable operation of the LM79MG over the input voltage and output current ranges. Output bypass capacitors will improve the transient response of the regulator.

The bypass capacitors, (2.0 μ F on the input, 1.0 μ F on the output) should be ceramic or solid tantalum which have good high frequency characteristics. If aluminum electrolytics are used, their values should be 10 μ F or larger. The bypass capacitors should be mounted with the shortest leads, and if possible, directly across the regulator terminals.


Basic Negative Regulator



TL/H/10058-19

$$V_O = -V_{CONT} \left(\frac{R_1 + R_2}{R_2} \right)$$


-30V to -2.6V Adjustable Regulator



TL/H/10058-21

Note 1: All resistor values in ohms.


Negative High Current Short Circuit Protected Regulator



TL/H/10058-17


$$R_1 = \frac{\beta V_{BE}(Q1)}{I_{R\ Max}(\beta) - I_{O\ Max}}$$

Negative High Current Voltage Regulator













TL/H/10058-18

Typical Performance Characteristics for LM78MG and LM79MG



TL/H/10058-7


Typical Performance Characteristics for LM78MG




TL/H/10058-5

Typical Performance Characteristics for LM79MG


**Peak Output Current
vs Input/Output
Differential Voltage**




**Quiescent Current
vs Input Voltage**




**Control Current
vs Temperature**




**Differential Control Voltage
vs Input Voltage**




**Differential Control Voltage
vs Output Current**




**Ripple Rejection
vs Output Voltage**




**Dropout Voltage
vs Junction Temperature**




Load Transient Response



**Ripple Rejection
vs Frequency**




Line Transient Response



TLH/10058-6

LML78MG/LM79MG 4-Terminal Adjustable Voltage Regulators

Physical Dimensions inches (millimeters)



LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



National Semiconductor
Corporation
2800 Semiconductor Drive
P.O. Box 58080
Santa Clara, CA 95052-8080
Tel: (800) 272-9950
TWX: (910) 339-9240

National Semiconductor
GmbH
Industriestrasse 10
D-8080 Furstenfeldbruck
West Germany
Tel: (081-41) 103-0
Telex: 527-649
Fax: (08141) 103654

National Semiconductor
Japan LM.
Semicondo Bldg. 5F
4-16 Nishi Sanjub
Shinjuku-Ku,
Tokyo 160, Japan
Tel: 3-399-7001
FAX: 3-299-7000

National Semiconductor
Hong Kong Ltd.
Suite 513, 5th Floor
Chinachem Golden Plaza,
77 Mody Road, Tsimshatsui East,
Kowloon, Hong Kong
Tel: 3-7231290
Telex: 52985 NSSEA HK
Fax: 3-3112536

National Semiconductors
Do Brasil Ltda.
Av. Brig. Faria Lima, 1383
6.0 Andar-Conj. 62
77 Mody Road, Tsimshatsui East,
Kowloon, Hong Kong
Tel: (55/11) 212-5056
Telex: 52985 NSSEA HK
Fax: (55/11) 211-1181 NSBR BR

National Semiconductor
(Australia) PTY, Ltd.
1st Floor, 441 St Kilda Rd.
Melbourne, 3004
Victory, Australia
Tel: (03) 257-6000
Fax: 61-3-2677456