

AlGaAs laser diode

RLD78PZW2

The RLD78PZW2 is infrared laser diode high power output type (pulse 180mW). This is the best for optical disk drive use, such as CD-R/RW.


●Applications

Max. X32 speed CD-R/RW drives.

●Features

- 1) Absolute maximum optical power output : pulse 180mW
- 2) Wave length : Typ. 784nm
- 3) $\phi 5.6$ mm small packages

●External dimensions (Units : mm)



●Absolute maximum ratings (Tc=25°C)

Parameter		Symbol	Limits	Unit
Output		P _O	Pulsed 180	mW
Reverse voltage	Raser	V _R	2	V
	PIN photodiode	V _{R(PIN)}	—	—
Operating temperature		T _{opr}	−10 to +70	°C
Storage temperature		T _{stg}	−40 to +85	°C

Laser Diodes

●Electrical and optical characteristics (T_c=25°C, CW)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Threshold current	I _{th}	—	30	50	mA	—
Operating current	I _{op}	—	120	150	mA	P _o =80mW
Operating voltage	V _{op}	—	2.0	2.5	V	
Differential efficiency	η	0.7	0.9	1.4	mW/mA	
Parallel divergence angle	θ *	8	9	10	deg	
Perpendicular divergence angle	θ _⊥ *	15	17	19	deg	
Parallel deviation angle	Δφ	-2	0	+2	deg	
Perpendicular deviation angle	Δφ _⊥	-3	0	+3	deg	—
Emission point accuracy	ΔX ΔY ΔZ	-80	0	+80	μm	
Peak emission wavelength	λ	779	784	789	nm	P _o =80mW
Astigmatism	Δℓ	—	—	6	μm	NA=0.15, P _o =80mW

* θ_{||} and θ_⊥ are defined as the angle within which the intensity is 50% of the peak value.

●Electrical and optical characteristics curves




Fig.1 Optical output
vs. operating current




Fig.2 Far field pattern




Fig.3 Dependence of wavelength
on temperature