


A8180SLU/SLT Series

A8184SLT, A8187SLT are product of Allegro Microsystems, INC.

Surface-Mount, Low Quiescent Current, Low Dropout Voltage Dropper Type

■Features

- Compact surface-mount package (equivalent to SOT-89)
- Output current: 0.15A
- Low circuit current
 $I_{q} \leq 60\mu A$ (Output ON: $V_{IN}=6V$, $I_o=0$ to 0.1A)
 $I_{q(off)} \leq 5\mu A$ (Output OFF: A8183SLU, A8186SLU)
- Low dropout voltage: $V_{DIF} \leq 150mV$ ($I_o=60mA$)
- Output ON/OFF control terminal is compatible with LS-TTL.
 (A8183SLU, A8186SLU)
- Built-in thermal protection circuit



■Applications

- Portable phones and PHS telephones
- Battery-driven electronic equipment

■Absolute Maximum Ratings

($T_a=25^\circ C$)

Parameter	Symbol	Ratings	Unit
DC Input Voltage	V_{IN}	10	V
DC Output Current	I_o	0.15	A
Power Dissipation	P_D	0.5($T_c=25^\circ C$)	W
Junction Temperature	T_j	150	$^\circ C$
Ambient Operating Temperature	T_{op}	-30 to +85	$^\circ C$
Storage Temperature	T_{stg}	-40 to +150	$^\circ C$

■Electrical Characteristics


(Ta=25°C unless otherwise specified)

Parameter		Symbol	Ratings											Unit	
			A8183SLU			A8184SLT			A8186SLU			A8187SLT			
			min.	typ.	max.	min.	typ.	max.	min.	typ.	max.	min.	typ.		max.
Input Voltage		V _{IN}			8			8			8			8	V
Output Voltage		V _O	2.9	3.0	3.1	2.9	3.0	3.1	3.2	3.3	3.4	3.2	3.3	3.4	V
		Conditions	V _{IN} =4 to 8V, I _O =0 to 0.1A						V _{IN} =4.5 to 8V, I _O =0 to 0.1A						
Dropout Voltage		V _{DIF}			0.15			0.15			0.15			0.15	V
		Conditions	I _O =60mA												
Line Regulation		ΔV _{OLINE}		7	20		7	20		7	20		7	20	mV
		Conditions	V _{IN} =4.5 to 6V, I _O =0A												
Load Regulation		ΔV _{OLOAD}		30	90		30	90		30	90		30	90	mV
		Conditions	V _{IN} =6V, I _O =0 to 0.1A												
Temperature Coefficient of Output Voltage		ΔV _O /ΔT _a	-1.0		1.0	-1.0		1.0	-1.0		1.0	-1.0		1.0	mV/°C
		Conditions	T _J =-30 to +85°C												
Circuit Current		I _q		45	60		45	60		45	60		45	60	μA
		Conditions	V _{IN} =6V, I _O =0 to 0.1A												
Quiescent Circuit Current		I _{q(off)}			5	—					5	—			μA
		Conditions	V _{IN} =4.5 to 8V, V _C =0.4V					—			V _{IN} =4.5 to 8V, V _C =0.4V			—	
V _C Terminal*	Control Voltage (Output ON)	V _{O(off)}	2.0			—			2.0			—			V
		Conditions	V _{IN} =6V					—			V _{IN} =6V			—	
	Control Voltage (Output OFF)	V _{C.OL}			0.8	—					0.8	—			V
		Conditions	V _{IN} =6V					—			V _{IN} =6V			—	
Input Current		I _C	-1.0		1.0	—			-1.0		1.0	—			μA
		Conditions	V _{IN} =6V					—			V _{IN} =6V			—	


*Output is OFF when output ON/OFF terminal (V_C terminal) is open.

■Outline Drawing


(unit: mm)




■Block Diagram



■Standard External Circuit




■Ta-PD Characteristics





■Typical Characteristics

($T_a=25^\circ\text{C}$)

I_o vs. V_{DIF} Characteristics



Rise Characteristics (A8183SLU/A8184SLT) Circuit Current



Output ON/OFF Control (A8183SLU)

