

SANYO

No.3451

2SK1448

N-Channel MOS Silicon FET

Very High-Speed
Switching Applications**Features**

- Low ON-state resistance.
- Very high-speed switching.



Absolute Maximum Ratings at Ta = 25°C

bsolute Maximum Ratings at Ta= 25°C				unit
Drain to Source Voltage	V _{DSS}		450	V
Gate to Source Voltage	V _{GSS}		± 30	V
Drain Current(DC)	I _D		8	A
Drain Current(Pulse)	I _{DP}	PW≤10μs, duty cycle≤1%	32	A
Allowable Power Dissipation	P _D	Tc= 25°C	100	W
			2.5	W
Channel Temperature	Tch		150	°C
Storage Temperature	Tstg		− 55 to + 150	°C

Electrical Characteristics at Ta = 25°C

			min	typ	max	unit
D-S Breakdown Voltage	$V_{(BR)DSS}$	$I_D = 1mA, V_{GS} = 0$	450			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 450V, V_{GS} = 0$			1.0	mA
Gate to Source Leakage Current	I_{GSS}	$V_{GS} = \pm 30V, V_{DS} = 0$			± 100	nA
Cutoff Voltage	$V_{GS(off)}$	$V_{DS} = 10V, I_D = 1mA$	2.0		3.0	V
Forward Transfer Admittance	$ Y_{fs} $	$V_{DS} = 10V, I_D = 4A$	3.0	6.0		S
Static Drain to Source on State Resistance	$R_{DS(on)}$	$I_D = 4A, V_{GS} = 10V$		0.6	0.8	Ω
Input Capacitance	C_{iss}	$V_{DS} = 20V, f = 1MHz$		1200		pF
Output Capacitance	C_{oss}	$V_{DS} = 20V, f = 1MHz$		180		pF
Reverse Transfer Capacitance	C_{rss}	$V_{DS} = 20V, f = 1MHz$		70		pF
Turn-ON Delay Time	$t_{d(on)}$	$I_D = 4A, V_{GS} = 10V$ $V_{DD} = 200V, R_{GS} = 50\Omega$		20		ns
Rise Time	t_r			40		ns
Turn-OFF Delay Time	$t_{d(off)}$			160		ns
Fall Time	t_f			60		ns
Diode Forward Voltage	V_{SD}	$I_S = 8A, V_{GS} = 0$			1.8	V









(Note) Be careful in handling the 2SK1448 because it has no protection diode between gate and source.





Switching Time Test Circuit**Package Dimensions 2056**
(unit : mm)

SANYO: TO3PB

SANYO Electric Co., Ltd. Semiconductor Business Headquarters
TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110 JAPAN

7151JN (KOTO) X-6827, 8035 No.3451-1/3





■ No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.

■ Anyone purchasing any products described or contained herein for an above-mentioned use shall:

- ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
- ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.

■ Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.