


3/4 STRINGS Xmas LIGHT CONTROL

FEATURES


- *Adjustable flash rate.
- *Programmable 2/3/4 strings of bulbs.
- *UTC 801 sequential mode for about 57 sec. 4 light string flash for about 3 sec. according to normal fosc. then back to sequential again.
- *UTC 802 sequential mode only.

APPLICATION

- *Xmas light controller, any AC control toys.




PIN CONFIGURATIONS



ELECTRICAL CHARACTERISTICS (@VDD=3.6V unless otherwise specified)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP.	MAX	UNIT
Operating Voltage	V _{DD}		-	3.6	5	V
Operating Current	I _{OP}	No load	-	-	-	mA
Quiescent Current	I _{SB}		-	-	-	μA
Driving Current	I _{OH}	@V _{DS} =1.2V	-	0.02	-	mA
Oscillator Frequency	F _{OSC}	External ± 30%, R _{osc} ~ 150kΩ	-	150	-	Hz
Operating Temperature	Temp.		0	25	60	°C

APPLICATION DIAGRAM



Note 1: IC CHIP ~ 1.26 x 1.14 mm², substrate to VDD

Note 2: This specification is subject to be changed without prior notice.