

600 V - 1,000 V Rectifiers
1.5 A Forward Current
150 ns - 3000 ns Recovery Time

X06FG X10FG
X06SG X10SG

AXIAL LEADED
HERMETICALLY SEALED




3

ELECTRICAL CHARACTERISTICS AND MAXIMUM RATINGS

Part Number	Working Reverse Voltage (Vrwm)	Average Rectified Current (Io)		Reverse Current @ Vrwm (Ir)		Forward Voltage (Vf)		1 Cycle Surge Current tp=8.3ms (Ifsm)	Repetitive Surge Current (Ifrm)	Reverse Recovery Time (3) (Trr)	Thermal Impedance θ_{J-L}			Junction Cap. @50VDC @ 1kHz (Cj)
		55°C(1)	100°C(2)	25°C	100°C	25°C					25°C	25°C	25°C	
	Volts	Amps	Amps	µA	µA	Volts	Amps	Amps	Amps	ns	°C/W	°C/W	°C/W	pF
X06FG X10FG	600 1000	1.50 1.50	0.75 0.75	1.0 1.0	20 20	1.5 1.5	1.0 1.0	25 25	5 5	150 150	18 18	38 38	45 45	16 16
X06SG X10SG	600 1000	1.50 1.50	0.75 0.75	1.0 1.0	20 20	1.3 1.3	3.0 3.0	25 25	5 5	3000 3000	18 18	38 38	45 45	16 16

(1)TL=55°C L=0.375" (2)TL=100°C L=0.375" (3)If=0.5A, Ir=1.0A, Irr=0.25A • Op.Temp.= -65°C to +175°C Stg.Temp.= -65°C to +200°C



Dimensions: In. (mm) • All temperatures are ambient unless otherwise noted. • Data subject to change without notice.



VOLTAGE MULTIPLIERS INC.
 8711 W. Roosevelt Ave.
 Visalia, CA 93291

TEL 559-651-1402
 FAX 559-651-0740
www.voltagemultipliers.com

X06FG X10FG X06SG X10SG

