

## R2860C Digital Receiver OC-192/STM-64

---



### Features

- High sensitivity,  $-20$  dBm typical
- Wide dynamic range, 2 dBm overload typical
- High transimpedance,  $2000\ \Omega$  typical
- Hermetically sealed
- Qualified in accordance with *Telcordia Technologies*<sup>TM</sup> TR-NWT-000468 requirements

### Applications

- 10 Gbits/s short, intermediate, and long-haul systems
- SONET/SDH equipment
- Datacom equipment

### Description

The R2860C receiver module incorporates a high-speed planar PIN diode and a GaAs PHEMT preamplifier to provide exceptionally high performance. The unit provides high bandwidth and sensitivity to operate with long, dispersive fibers, plus wide dynamic range for operation over a variety of loss budgets. High transimpedance coupled with a nonquantizing limiting buffer output provides high gain while limiting the maximum output signal swing, thereby simplifying the interface to subsequent stages.

Agere Systems Inc. offers several 1R and 2R high-speed receiver components for 10 Gbits/s and 12.5 Gbits/s applications. APD and PIN receivers are available in a 6-pin hermetic package with coaxial output. In addition, Agere Systems also offers a PIN receiver with coplanar waveguide in a multisource agreement form-factor or a smaller, space-sensitive package. For more information about the complete line of high-speed receiver products, please visit the Agere Systems' website at [www.agere.com/opto](http://www.agere.com/opto).

## Absolute Maximum Ratings

Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. These are absolute stress ratings only. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of the data sheet. Exposure to absolute maximum ratings for extended periods can adversely affect device reliability.

Parameter	Symbol	Min	Max	Unit
Operating Temperature Range	T <sub>OP</sub>	−5	70	°C
Storage Case Temperature Range	T <sub>stg</sub>	−40	85	°C
Preamplifier Supply Voltage	V <sub>CC</sub>	—	12	V
Photodiode Bias Voltage	V <sub>PD</sub>	—	20	V
Optical Input Power	P <sub>IN</sub>	—	4	dBm

## Electrical/Optical Characteristics

**Table 1. Electrical and Optical Characteristics** (25 °C Case Temperature)

Parameter	Symbol	Min	Typ	Max	Unit
Optical Wavelength Range	$\lambda$	1280	—	1580	nm
Sensitivity (10 <sup>−10</sup> BER, PRBS 2 <sup>23</sup> − 1)	—	—	−20	−18	dBm
Overload (10 <sup>−13</sup> BER, PRBS 2 <sup>23</sup> − 1)	—	0	2	—	dBm
Responsivity	R	0.7	0.8	—	A/W
Dark Current	I <sub>D</sub>	—	—	1	nA
High-Frequency Cutoff	—	8.0	9.0	—	GHz
Low-Frequency Cutoff	—	—	—	30	kHz
Transimpedance	Z	1400	2000	—	$\Omega$
Maximum ac Output Voltage Swing	—	—	800	—	mVp-p
RF Output Return Loss* (0.1 GHz—5 GHz)	R <sub>LRF</sub>	—	—	10	dB
Optical Return Loss	O <sub>RL</sub>	27	—	—	dB
Logic Sense	—	—	Noninverting	—	—
Preamplifier Supply Voltage	(V <sub>CC</sub> )	7.6	8.0	8.4	V
Photodiode Supply Voltage	V <sub>PD</sub>	7	8	12	V
Supply Current	I <sub>CC</sub>	—	80	120	mA


\* External blocking capacitor required.

## Pin Information

Table 2. Pin Descriptions


Pin No.	Description
1	NC
2	8 V (VCC)
3	8 V (VPD)
4	NC
5	NC
6	Ground

## Block Diagram



1-1170 (F)

## Characteristic Curve



1-1172 (F)

Figure 1. R2860C Typical Electrical Output Voltage vs. Optical Input Power

Dimensions are in inches and (millimeters).



4

## Ordering Information

Table 3. Ordering Information <sup>1</sup>

Device Code	Description	Connector	Pigtail	Comcode
R2860C023	Digital Receiver, 1400 $\Omega$ min. TIA gain, dc-coupled output	FC/SPC, Standard	SMF-28™ (1 m, min)	108870130
R2860C040	Digital Receiver, 1400 $\Omega$ min. TIA gain, dc-coupled output	SC/UPC	SMF-28 (1 m, min)	108870148
R2860C050	Digital Receiver, 1400 $\Omega$ min. TIA gain, dc-coupled output	LC	SMF-28 (1 m, min)	108870155

1. Other options available. For additional ordering information, please contact an account manager at Opto West, Agere Systems Inc., 1-800-362-3891 (for sales staff, please press option 2).

*Telcordia Technologies* is a trademark of Telcordia Technologies, Inc.  
*K-Connector* is a trademark of Anritsu Company.  
*SMF-28* is a trademark of Corning Incorporated.

---

For additional information, contact your Agere Systems Account Manager or the following:

INTERNET: **<http://www.agere.com>**

E-MAIL: **[docmaster@micro.lucent.com](mailto:docmaster@micro.lucent.com)**

N. AMERICA: Agere Systems Inc., 555 Union Boulevard, Room 30L-15P-BA, Allentown, PA 18109-3286

**1-800-372-2447**, FAX 610-712-4106 (In CANADA: **1-800-553-2448**, FAX 610-712-4106)

ASIA PACIFIC: Agere Systems Singapore Pte. Ltd., 77 Science Park Drive, #03-18 Cintech III, Singapore 118256

**Tel. (65) 778 8833**, FAX (65) 777 7495

CHINA: Agere Systems (Shanghai) Co., Ltd., 33/F Jin Mao Tower, 88 Century Boulevard Pudong, Shanghai 200121 PRC

**Tel. (86) 21 50471212**, FAX (86) 21 50472266

JAPAN: Agere Systems Japan Ltd., 7-18, Higashi-Gotanda 2-chome, Shinagawa-ku, Tokyo 141, Japan

**Tel. (81) 3 5421 1600**, FAX (81) 3 5421 1700

EUROPE: Data Requests: DATALINE: **Tel. (44) 7000 582 368**, FAX (44) 1189 328 148

Technical Inquiries: OPTOELECTRONICS MARKETING: **(44) 1344 865 900** (Ascot UK)

---

Agere Systems Inc. reserves the right to make changes to the product(s) or information contained herein without notice. No liability is assumed as a result of their use or application.