

# Fuse Blocks, Holders and Accessories

Class J POWR-SAFE Holders

**NEW**



Littelfuse POWR-SAFE “Dead Front” fuseholders provide optimum protection to personnel. An integral DIN-Rail adapter system allows fuse holders to be mounted on 35mm DIN-Rail without the use of tools or special parts. Indicating and non-indicating versions are available in 1, 2, or 3 poles for Class J fuses.

## SPECIFICATIONS

**Voltage Rating:** 600 VAC

**Interrupting Rating:** 200 kA

**Ampere Rating:** 30 and 60 amperes

**Terminal Type:** Pressure plate

**Suggested Torque:** 30A – 35 inch-pounds  
60A – 45 inch-pounds

**Wire Range:** #2 – #14CU

**Material:** Thermo-plastic

**Flammability Rating:** 94V0

**Approvals:** UL Listed

CSA Certified

IEC Type IP20 Protection

CE

## FEATURES/BENEFITS

- Meets “Dead Front” requirements and IEC Type IP20 protection.
- Mountable on 35mm DIN-Rail.
- Blown fuse identification (Indicating versions only).
- Easy installation and removal of fuses. No special fuse pullers or tools required.
- UL listed for branch circuit protection.
- Ventilated design for cooler operation.

## ORDERING INFORMATION

Littelfuse Catalog No.	Littelfuse System No.	No. of Poles	Pack Qty.	Voltage Rating	Ampere Rating	Options
LPSJ30-1	LPSJ301.Z	1	6	600V	30A	—
LPSJ30-2	LPSJ302.Z	2	3	600V	30A	—
LPSJ30-3	LPSJ303.Z	3	2	600V	30A	—
LPSJ30-1ID	LPSJ301.ZXID	1	6	600V	30A	Indicating
LPSJ30-2ID	LPSJ302.ZXID	2	3	600V	30A	Indicating
LPSJ30-3ID	LPSJ303.ZXID	3	2	600V	30A	Indicating
LPSJ60-1	LPSJ601.Z	1	6	600V	60A	—
LPSJ60-2	LPSJ602.Z	2	3	600V	60A	—
LPSJ60-3	LPSJ603.Z	3	2	600V	60A	—
LPSJ60-1ID	LPSJ601.ZXID	1	6	600V	60A	Indicating
LPSJ60-2ID	LPSJ602.ZXID	2	3	600V	60A	Indicating
LPSJ60-3ID	LPSJ603.ZXID	3	2	600V	60A	Indicating

Contact Littelfuse for dimensions.