


10 TAP LEADING EDGE CONTROL PRECISE DELAY MODULES

Cat 26-R3



Part Numbers

SMD	Thru-Hole	Total Delay	Delay per Tap	Rise Time
S497-0025-10	A497-0025-10	* 22.5 ns	2.5 ns	3 ns
S497-0030-10	A497-0030-10	* 27 ns	3 ns	3 ns
S497-0040-10	A497-0040-10	* 36 ns	4 ns	3 ns
S497-0050-10	A497-0050-10	50 ns	5 ns	3 ns
S497-0060-10	A497-0060-10	60 ns	6 ns	3 ns
S497-0070-10	A497-0070-10	70 ns	7 ns	3 ns
S497-0080-10	A497-0080-10	80 ns	8 ns	3 ns
S497-0090-10	A497-0090-10	90 ns	9 ns	3 ns
S497-0100-10	A497-0100-10	100 ns	10 ns	3 ns
S497-0125-10	A497-0125-10	125 ns	12.5 ns	3 ns
S497-0150-10	A497-0150-10	150 ns	15 ns	3 ns
S497-0200-10	A497-0200-10	200 ns	20 ns	3 ns
S497-0250-10	A497-0250-10	250 ns	25 ns	3 ns


Tolerances

Input to Taps ± 1 ns or 3 % , Whichever is Greater
 Delays measured @ 1.5 V levels on Leading Edge only
 with no loads on Taps
 Rise and Fall Times measured from 0.75 V to 2.4 V levels
 * Ref. Delay from P13, Delay P1-P13 = 4.5 ns typical

Drive Capabilities

Nh	Logic 1 Fanout	-	20 TTL Loads Max.
Nl	Logic 0 Fanout	-	10 TTL Loads Max.

Recommended Temperature Profile



Test Conditions @ 25°C

Ein	Pulse Voltage	3.2 Volts
Trin	Rise Time	3.0 ns (10%-90%)
PW	Pulse Width	1.2 x Total Delay
PP	Pulse Period	4 x Pulse Width
Iccl	Supply Current	80 ma Typical
Vcc	Supply Voltage	5.0 Volts

Electrical Characteristics

	Min.	Max.	Units
Vcc Supply Voltage	4.75	5.25	V
Vih Logic 1 Input Voltage	2.0		V
Vil Logic 0 Input Voltage		0.8	V
Ioh Logic 1 Output Current		-1	ma
Iol Logic 0 Output Current		20	ma
Voh Logic 1 Output Voltage	2.7		V
Vol Logic 0 Output voltage		0.5	V
Vik Input Clamp Voltage		-1.2	V
Iih Logic 1 Input Current		40	ua
Iil Logic 0 Input Current		-1.2	ma
Ios Short Circuit Output Current	-60	-150	ma
Icch Logic 1 Supply Current		50	ma
Iccl Logic 0 Supply Current		90	ma
Ta Operating Free Air Temperature	0°	70°	C
PW Min. Input Pulse Width of Total Delay	40		%
d Maximum Duty Cycle		50	%
Tc Temp. Coeff. of Total Delay (TD) 100 + (25000/TD) PPM/°C			

Notes

Transfer molded for better reliability
Compatible with TTL & DTL circuits
Terminals: Electro-Tin plate phosphor bronze
Performance warranty is limited to specified parameters listed
SMD - Tape & Reel available:
32mm Wide x 16mm Pitch, 500 pieces per 13" reel

**Other Delays and Tolerances Available
Consult Sales**

Specifications subject to change without notice.

Corporate Office

Bel Fuse Inc.
198 Van Vorst Street, Jersey City, NJ 07302-4496
Tel: 201-432-0463
Fax: 201-432-9542
E-Mail: BelFuse@belfuse.com
Internet: <http://www.belfuse.com>

Far East Office

Bel Fuse Ltd.
8F/8 Luk Hop Street
San Po Kong
Kowloon, Hong Kong
Tel: 852-2328-5515
Fax: 852-2352-3706

European Office

Bel Fuse Europe Ltd.
Preston Technology Management Centre
Marsh Lane, Preston PR1 8UD
Lancashire, U.K.
Tel: 44-1772-556601
Fax: 44-1772-888366