

NON-ISOLATED DC/DC CONVERTERS

2.5 V Input 0.9 V-1.65 V/10 A Output

bel
POWER PRODUCTS

xRAH-10J Series

- Non-Isolated
- Low profile package (7.82 mm)
- Fixed frequency (300 kHz)
- Under-voltage lockout (UVLO)
- Remote On/Off
- Short circuit protection
- Over current protection
- Trim Function



Description

The Bel xRAH-10Jxx0 is part of the low cost non-isolated dc/dc power converter series. The modules use a SMD or SIP package for ease of layout and space savings. The output is closely regulated and the efficiency of 1.5 V output is typically 88% at full load. Typical features include remote on/off, input under voltage lockout, over current protection and short circuit protection.

Part Selection

Output Voltage	Input Voltage	Max. Output Current	Max. Output Power	Typical Efficiency	Part Number Surface Mount	Part Number Vertical Mount
1.5 V	2.5 V	10 A	15 W	88%	SRAH-10J150	VRAH-10J150
1.2 V	2.5 V	10 A	12 W	83%	SRAH-10J120	VRAH-10J120
1.0 V	2.5 V	10 A	10 W	80%	SRAH-10J100	VRAH-10J100

Note: Add "0" suffix at the end of the model number to indicate "Tube Packaging", and "R" for "Reel Packaging", and "G" for "Tray Packaging".

Absolute Maximum Ratings

Parameter	Min	Typ	Max	Notes
Input Voltage (continuous)	-0.3 V	-	6 V	
Output Enable Terminal Voltage	-0.3 V	-	7 V	
Ambient Temperature	-40 °C	-	85 °C	
Storage Temperature	-40 °C	-	125 °C	

Input Specifications

Parameter	Min	Typ	Max	Notes
Input Voltage	2.25 V	2.5 V	2.75 V	
Input Current (no load)	-	75 mA	-	
Input Current (full load)				
Vo=1.5 V	-	6.8 A	-	
Vo=1.2 V	-	5.6 A	-	
Vo=1.0 V	-	4.9 A	-	
Remote Off Input Current	-	4 mA	8 mA	
Input Reflected Ripple Current (pk-pk)	-	80 mA	150 mA	Tested with simulated source impedance of 500 nH, 5 Hz to 20 MHz; with a 270 uF/16 V with ESR=0.018 ohm max, at 100 kHz at 25 °C
Input Reflected Ripple Current (rms)	-	25 mA	50 mA	
I ² t Inrush Current Transient	-	0.04 A ² s	0.10 A ² s	
Turn on Voltage Threshold	2 V	2.1 V	2.15 V	
Turn off Voltage Threshold	1.8 V	2 V	2.15 V	

NON-ISOLATED DC/DC CONVERTERS

2.5 V Input 0.9 V-1.65 V/10 A Output



Output Specifications

Parameter		Min	Typ	Max	Notes
Output Voltage Set Point	V _O =1.5 V	1.470 V	1.5 V	1.530 V	Test conditions: V _{in} =2.5 V, I _o =full load
	V _O =1.2 V	1.176 V	1.2 V	1.224 V	
	V _O =1.0 V	0.980 V	1.0 V	1.020 V	
Line Regulation	V _O =1.5 V	-	2 mV	5 mV	
	V _O =1.2 V	-	2 mV	5 mV	
	V _O =1.0 V	-	2 mV	5 mV	
Load Regulation	V _O =1.5 V	-	5 mV	10 mV	
	V _O =1.2 V	-	5 mV	10 mV	
	V _O =1.0 V	-	5 mV	10 mV	
Regulation Over Temperature (-40 °C to +85 °C)	V _O =1.5 V	-	13 mV	25 mV	
	V _O =1.2 V	-	10 mV	20 mV	
	V _O =1.0 V	-	9 mV	20 mV	
Output Current		0 A	-	10 A	
Current Limit Threshold		13 A	-	25 A	
Short Circuit Surge Transient	V _O =1.5 V	-	0.5 A ² s	1.5 A ² s	
	V _O =1.2 V	-	0.5 A ² s	1.5 A ² s	
	V _O =1.0 V	-	0.5 A ² s	1.5 A ² s	
Ripple and Noise (rms)		-	15 mV	25 mV	Test conditions: 0-20 MHz BW, with a 1 µF ceramic capacitor at the output.
Ripple and Noise (pk-pk)		-	50 mV	100 mV	
Turn on Time		-	1 mS	2 mS	
Overshoot at Turn on		-	0%	3%	
Output Capacitance		220 µF	-	4000 µF	
Transient Response					
50% ~ 100% Max Load	Overshoot	V _O =1.5 V	-	90 mV	Test conditions: di/dt = 0.5 A/µs; V _{in} = 2.5 V; with a 220 µF tantalum capacitor at the output.
	Settling Time		-	30 µs	
100% ~ 50% Max Load	Overshoot		-	90 mV	
	Settling Time		-	30 µs	
50% ~ 100% Max Load	Overshoot	V _O =1.2 V	-	80 mV	
	Settling Time		-	30 µs	
100% ~ 50% Max Load	Overshoot		-	80 mV	
	Settling Time		-	30 µs	
50% ~ 100% Max Load	Overshoot	V _O =1.0 V	-	80 mV	
	Settling Time		-	30 µs	
100% ~ 50% Max Load	Overshoot		-	80 mV	
	Settling Time		-	30 µs	

Note: All specifications are typical at nominal input, full load at 25 °C unless otherwise stated.

NON-ISOLATED DC/DC CONVERTERS

2.5 V Input 0.9 V-1.65 V/10 A Output



General Specifications

Parameter	Min	Typ	Max	Notes
Efficiency				Measured at Vin=2.5 V, full load and Ta=25 °C.
Vo=1.5 V	85%	88%	-	
Vo=1.2 V	83%	86%	-	
Vo=1.0 V	79%	82%	-	
Switching Frequency	250 kHz	300 kHz	350 kHz	
Output Trim Range	90%Vo	-	110%Vo	
MTBF	4,447,157 hours			Calculated Per Bell Core SR-332 (Io = Nominal; Ta = 25 °C)
Dimensions (surface mount)				
Inches (L x W x H)	0.78 x 0.70 x 0.32			
Millimeters (L x W x H)	19.81 x 17.78 x 8.13			
Dimensions (vertical)				
Inches (L x W x H)	0.70 x 0.308 x 0.65			
Millimeters (L x W x H)	17.78 x 7.82 x 16.51			
Weight	-	4.7 g	-	

Control Specifications



Parameter	Min	Typ	Max	Notes
Remote On/Off				
Signal Low (Unit Off)	0 V	-	0.5 V	Remote on/off pin open, the module is on.
Signal High (Unit On)	2 V	-	5.5 V	

Output Trim Equations

Equations for calculating the trim resistor (in kΩ) given the desired adjusted voltage (Vadj) and the nominal output voltage of the converter (Vnom) are shown below. The Trim Down resistor should be connected between the Trim pin and Vout. The Trim Up resistor should be connected between the Trim pin and Ground. Only one of the resistors should be used for any given application.

$$R_{TrimDown} = \frac{A}{V_{nom} - V_{adj}} - B \qquad R_{TrimUp} = \frac{C}{V_{adj} - V_{nom}} - D$$

Vnom	A	B	C	D
1.5 V	49.788	287.900	43.330	226.000
1.2 V	31.241	223.900	43.330	162.000
1.0 V	11.029	92.800	25.550	56.200




NON-ISOLATED DC/DC CONVERTERS


2.5 V Input 0.9 V-1.65 V/10 A Output




Efficiency Data



xRAH-10J150




xRAH-10J120



xRAH-10J100

Thermal Derating Curve




Note: Derating curve is for 1.2 V output and tested at nominal input.

2.5 V Input 0.9 V-1.65 V/10 A Output



Mechanical Outline

SRAH-10Jxx0



Pin Connections

Pin	Function
1	Remote On/Off (option)
2	Vin
3	Ground
4	Vout
5	Trim (option)
6	N/A
7	N/A



NON-ISOLATED DC/DC CONVERTERS

2.5 V Input 0.9 V-1.65 V/10 A Output




Mechanical Outline (continued)

VRAH-10Jxx0



RECOMMENDED PCB PAD LAYOUT



Pin Connections

Pin	Function
1	Remote On/Off (option)
2	Vin
3	Ground
4	Vout
5	Trim (option)

RoHS Compliance

Complies with the European Directive 2002/95/EC, calling for the elimination of lead and other hazardous substances from electronic products. These parts are not however compatible with the higher temperatures associated with lead free solder processes and must be soldered using a reflow profile with a peak temperature of no more than 240 °C.



©2005 Bel Fuse Inc. Specifications subject to change without notice. 112305

CORPORATE

Bel Fuse Inc.
206 Van Vorst Street
Jersey City, NJ 07302
Tel 201-432-0463
Fax 201-432-9542
www.belfuse.com

FAR EAST

Bel Fuse Ltd.
8F/ 8 Luk Hop Street
San Po Kong
Kowloon, Hong Kong
Tel 852-2328-5515
Fax 852-2352-3706
www.belfuse.com

EUROPE

Bel Fuse Europe Ltd.
Preston Technology Management Centre
Marsh Lane, Suite G7, Preston
Lancashire, PR1 8UD, U.K.
Tel 44-1772-556601
Fax 44-1772-888366
www.belfuse.com