

90° LED ASSEMBLIES

T-1 (3mm) Bi-Level Assemblies

- Standard Footprint, Conserves Board Space
- 4mm PC Leads Standard
- Additional Configurations
- Design Your Own LED Assembly (see page 136-137)



H204C Series

T-1 (3mm), Quad Station Bi-Level Array.

LED Assy. No.	Peak Wave Length	Emitted Color	Lens Appearance	Abs. Max. Rating If (mA)	Electro-Optical Data @20mA			Viewing Angle 2 θ 1/2 (deg)	LED P/N
					Vf (V)	Iv (mcd)			
H204CBWD	430	BLUE	DIFFUSED	20	4.0	4.5	20.0	45	3BWD
H204CGD	565	GREEN	DIFFUSED	20	2.2	2.6	30.0	45	3GD
H204CYD	585	YELLOW	DIFFUSED	20	2.1	2.6	20.0	45	3YD
H204CHD	635	HE RED	DIFFUSED	20	2.0	2.6	30.0	45	3HD
H204CRD	655	RED	DIFFUSED	20	1.7	2.0	6.0	45	3RD
H204CSRD	660	SUPER RED	DIFFUSED	20	1.7	2.6	90.0	45	3SRD
Low Current					Data @2mA				
H204CGDL	565	GREEN	DIFFUSED	2	1.9	2.2	6.0	45	3GDL
H204CYDL	585	YELLOW	DIFFUSED	2	1.9	2.2	4.0	45	3YDL
H204CHDL	635	HE RED	DIFFUSED	2	1.8	2.2	6.0	45	3HDL
5 Volt					Data @10mA				
H204CGD5V	565	GREEN	DIFFUSED	10	-	5.0	30.0	45	3GD5V
H204CYD5V	585	YELLOW	DIFFUSED	10	-	5.0	20.0	45	3YD5V
H204CHD5V	635	HE RED	DIFFUSED	10	-	5.0	30.0	45	3HD5V

