

CA1004

FEATURES

- **Very Tight Initial Voltage Tolerance**
 - 1004-1.2..... $\pm 5\text{mV}$
 - 1004-2.5..... $\pm 10\text{mV}$
- **Very Low Operating Current**
 - 1004-1.2..... $10\mu\text{A}$
 - 1004-2.5..... $20\mu\text{A}$
- **Wide Operating Current Range** $10\mu\text{A}$ to 20mA
- **Very Low Dynamic Impedance**..... 0.6 Max.



PRODUCT DESCRIPTION

The CA1004 is a two-terminal, temperature compensated, micropower band-gap voltage reference, which provides a fixed voltage for a wide range of input currents ($10\mu\text{A}$ to 20mA). The high stability of the device is primarily the result of the low temperature coefficient Thin Film Resistor process and the tight output voltage tolerance is obtained by resistor Laser trimming at the wafer level. This gives the benefit of eliminating the need of external voltage adjustment.



ORDERING INFORMATION

Part	Package	Max Tempco (ppm/ $^{\circ}\text{C}$)	Temp Range
CA1004N1 (1.2)	TO-92	100	0°C to $+70^{\circ}\text{C}$
CA1004BY1 (1.2)	SOIC	100	-40°C to $+85^{\circ}\text{C}$
CA1004N2 (2.5)	TO-92	100	0°C to $+70^{\circ}\text{C}$
CA1004BY2 (2.5)	SOIC	100	-40°C to $+85^{\circ}\text{C}$

PIN CONFIGURATIONS



TO-92 (N-SUFFIX)
BOTTOM VIEW



SO PACKAGE
(Y-SUFFIX)
BOTTOM VIEW

ABSOLUTE MAXIMUM RATINGS

Forward Current.	10mA	Storage Temperature Range	
Reverse Current.	30mA	TO-92.	-65°C to +150°C
Operating Temperature Range		SOIC.	-65°C to +150°C
TO-92.	0°C to +70°C	Lead Temperature (10 sec.).	+300°C
SOIC.	40°C to +85°C		

SPECIFICATIONS: At I_{in} = 100µA and T_A = +25°C unless otherwise specified.

PARAMETERS	CA1004			UNITS	CONDITIONS
	MIN	TYP	MAX		
Output Voltage	1.235 2.480	1.25 2.500	1.265 2.520	V	1004-1, 2 1004-2, 5
Min Operating Current			10 20	µA	1004-1, 2 1004-2, 5
Output Voltage Change With Current			2.0 20	mV	10µA ≤ I _{in} ≤ 1mA 1mA ≤ I _{in} ≤ 20mA
Temperature Coefficient			100	ppm/°C	
Dynamic Impedence			1.0	Ω	
Wide Band Noise		60		µV	10Hz f 10KHz
Long Term Stability		20		ppm/KHr	T _A = 25°C ±.1°C