

- 1N941BUR-1, 1N943UR-1B, 1N944BUR-1 AND 1N945BUR-1 AVAILABLE IN JAN, JANTX, JANTXV AND JANS PER MIL-PRF-19500/157
- TEMPERATURE COMPENSATED ZENER REFERENCE DIODES
- LEADLESS PACKAGE FOR SURFACE MOUNT
- 11.7 VOLT NOMINAL ZENER VOLTAGE
- METALLURGICALLY BONDED, DOUBLE PLUG CONSTRUCTION

1N941BUR-1 thru 1N945BUR-1  
and  
CDLL941 thru CDLL945B

## MAXIMUM RATINGS

Operating Temperature: -65°C to +175°C  
Storage Temperature: -65°C to +175°C  
DC Power Dissipation: 500mW @ +50°C  
Power Derating: 4 mW / °C above +50°C

## REVERSE LEAKAGE CURRENT

$I_R = 15 \mu A$  @ 25°C &  $V_R = 8 V_{dc}$

ELECTRICAL CHARACTERISTICS @ 25°C, unless otherwise specified.

CDI TYPE NUMBER	ZENER VOLTAGE $V_Z @ I_{ZT}$	ZENER TEST CURRENT $I_{ZT}$	MAXIMUM ZENER IMPEDANCE $Z_{ZT}$  (Note 1)	VOLTAGE TEMPERATURE STABILITY $V_{ZT}$ MAXIMUM (Note 2)	TEMPERATURE RANGE	EFFECTIVE TEMPERATURE COEFFICIENT
	VOLTS	mA	OHMS	mV	°C	% / °C
CDLL941	11.12 - 12.28	7.5	30	88	0 to + 75	0.01
CDLL941A	11.12 - 12.28	7.5	30	181	-55 to +100	0.01
CDLL941B	11.12 - 12.28	7.5	30	239	-55 to +150	0.01
CDLL942	11.12 - 12.28	7.5	30	44	0 to + 75	0.005
CDLL942A	11.12 - 12.28	7.5	30	90	-55 to +100	0.005
CDLL942B	11.12 - 12.28	7.5	30	120	-55 to +150	0.005
CDLL943	11.12 - 12.28	7.5	30	18	0 to + 75	0.002
CDLL943A	11.12 - 12.28	7.5	30	36	-55 to +100	0.002
CDLL943B	11.12 - 12.28	7.5	30	47	-55 to +150	0.002
CDLL944	11.12 - 12.28	7.5	30	9	0 to + 75	0.001
CDLL944A	11.12 - 12.28	7.5	30	18	-55 to +100	0.001
CDLL944B	11.12 - 12.28	7.5	30	24	-55 to +150	0.001
CDLL945	11.12 - 12.28	7.5	30	4	0 to + 75	0.0005
CDLL945A	11.12 - 12.28	7.5	30	9	-55 to +100	0.0005
CDLL945B	11.12 - 12.28	7.5	30	12	-55 to +150	0.0005

**NOTE 1** Zener impedance is derived by superimposing on  $I_{ZT}$  A 60Hz rms a.c. current equal to 10% of  $I_{ZT}$ .

**NOTE 2** The maximum allowable change observed over the entire temperature range i.e., the diode voltage will not exceed the specified mV at any discrete temperature between the established limits, per JEDEC standard No.5.




FIGURE 1

## DESIGN DATA

**CASE:** DO-213AA, Hermetically sealed glass case. (MELF, SOD-80, LL34)

**LEAD FINISH:** Tin / Lead

**POLARITY:** Diode to be operated with the banded (cathode) end positive.

**MOUNTING POSITION:** Any.


**MOUNTING SURFACE SELECTION:**  
The Axial Coefficient of Expansion (COE) Of this Device is Approximately +6PPM/°C. The COE of the Mounting Surface System Should Be Selected To Provide A Suitable Match With This Device.




**COMPENSATED DEVICES INCORPORATED**

22 COREY STREET, MELROSE, MASSACHUSETTS 02176  
PHONE (781) 665-1071 FAX (781) 665-7379  
WEBSITE: <http://www.cdi-diodes.com> E-mail: [mail@cdi-diodes.com](mailto:mail@cdi-diodes.com)


# CDLL941 thru CDLL945B



**FIGURE 2  
POWER DERATING CURVE**



**FIGURE 3  
TYPICAL CHANGE OF TEMPERATURE COEFFICIENT  
WITH CHANGE IN OPERATING CURRENT**



**FIGURE 4**

**ZENER IMPEDANCE VS. OPERATING CURRENT**