

# Central<sup>TM</sup> Semiconductor Corp.

145 Adams Avenue, Hauppauge, NY 11788 USA  
Tel: (631) 435-1110 • Fax: (631) 435-1824

Manufacturers of World Class Discrete Semiconductors

CQ220-6BS  
CQ220-6DS  
CQ220-6MS  
CQ220-6NS

6.0 AMP TRIAC  
200 THRU 800 VOLTS

JEDEC TO-220AB CASE

## DESCRIPTION

The CENTRAL SEMICONDUCTOR CQ220-6BS series type is an Epoxy Molded Silicon Triac designed for full wave AC control applications featuring gate triggering in all four (4) quadrants.

## MAXIMUM RATINGS (T<sub>C</sub> = 25°C unless otherwise noted)

	SYMBOL	CQ220 -6BS	CQ220 -6DS	CQ220 -6MS	CQ220 -6NS	UNITS
Peak Repetitive Off-State Voltage	V <sub>DRM</sub>	200	400	600	800	V
RMS On-State Current (T <sub>C</sub> = 90°C)	I <sub>T(RMS)</sub>		6.0			A
Peak One Cycle Surge (t = 10ms)	I <sub>TSM</sub>		60			A
I <sup>2</sup> t Value for Fusing (t = 10ms)	I <sup>2</sup> t		18			A <sup>2</sup> s
Peak Gate Power (tp = 10μs)	P <sub>GM</sub>		40			W
Average Gate Power Dissipation	P <sub>G(AV)</sub>		1.0			W
Peak Gate Current (tp = 10μs)	I <sub>GM</sub>		4.0			A
Peak Gate Voltage (tp = 10μs)	V <sub>GM</sub>		16			V
Critical Rate of Rise of On-State Current						
Repetitive (F = 50Hz)	di/dt		10			A/μs
Storage Temperature	T <sub>stg</sub>		-40 to +150			°C
Junction Temperature	T <sub>J</sub>		-40 to +110			°C
Thermal Resistance	θ <sub>J-A</sub>		60			°C/W
Thermal Resistance	θ <sub>J-C</sub>		3.2			°C/W


## ELECTRICAL CHARACTERISTICS (T<sub>C</sub> = 25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
I <sub>DRM</sub>	Rated V <sub>DRM</sub>			0.01	mA
I <sub>DRM</sub>	Rated V <sub>DRM</sub> , T <sub>C</sub> = 110°C			0.75	mA
I <sub>GT</sub>	V <sub>D</sub> = 12V, R <sub>L</sub> = 33Ω, QUAD I,II,III			5.0	mA
I <sub>GT</sub>	V <sub>D</sub> = 12V, R <sub>L</sub> = 33Ω, QUAD IV			10	mA
I <sub>H</sub>	I <sub>T</sub> = 100mA			15	mA
V <sub>GT</sub>	V <sub>D</sub> = 12V, R <sub>L</sub> = 33Ω, QUAD I,II,III,IV			1.50	V
V <sub>TM</sub>	I <sub>TM</sub> = 8.5A, tp = 10ms			1.65	V
dv/dt	V <sub>D</sub> = 2/3 V <sub>DRM</sub> , R <sub>GK</sub> = ∞, T <sub>C</sub> = 110°C		10		V/μs


(OVER)

# CQ220-6BS SERIES RATING AND CHARACTERISTIC CURVES

RMS ON-STATE CURRENT vs. CASE TEMPERATURE



MAXIMUM ON-STATE CHARACTERISTICS



## MECHANICAL DIMENSIONS

All Dimensions in inches (mm).

