

**B08**

## FEMALE HEADER PROFILE : 8.5mm STRAIGHT

**PITCH: 2.54mm**

### SPECIFICATIONS

#### Material

Insulator : PBT, glass reinforced, rated UL 94V-0

Contact : Phosphor Bronze

#### Electrical

Current Rating : 1 Amp DC



Contact Resistance : 30 mΩ max.

Insulation Resistance : 3000 MΩ min.

Dielectric Withstanding Voltage : 500V AC for 1minute

Operating Temperature : -40°C to +105°C

♦ Mating Suggestion : C15, C16, C17 & C18 series.



### HOW TO ORDER:

B08 -  1 -  2 -  3 -  4

| 1.NO. OF CONTACT                                       | 2.CONTACT MATERIAL | 3.CONTACT PLATING   | 4.INSULATOR COLOR |
|--|--------------------|---|-------------------|
| SINGLE ROW<br>1*2 - 1*40<br><br>DUAL ROW<br>2*2 - 2*40 | B: PHOSPHOR BRONZE | T: TIN PLATED<br>S: SELECTIVE<br>G: GOLD FLASH<br>A: 5u" INCH GOLD<br>B: 10u" INCH GOLD<br>C: 15u" INCH GOLD<br>D: 30u" INCH GOLD | 1. BLACK          |