



**DC COMPONENTS CO., LTD.**

RECTIFIER SPECIALISTS

**SK22  
THRU  
SK28**

**TECHNICAL SPECIFICATIONS OF SURFACE MOUNT SCHOTTKY BARRIER RECTIFIER**

**VOLTAGE RANGE - 20 to 80 Volts**

**CURRENT - 2.0 Amperes**

**FEATURES**

- \* Ideal for surface mounted applications
- \* Low leakage current
- \* Glass passivated junction

**MECHANICAL DATA**


- \* Case: Molded plastic
- \* Epoxy: UL 94V-0 rate flame retardant
- \* Terminals: Solder plated, solderable per MIL-STD-750, Method 2026
- \* Polarity: As marked
- \* Mounting position: Any
- \* Weight: 0.093 gram

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25 °C ambient temperature unless otherwise specified.  
Single phase, half wave, 60 Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.



**SMB (DO-214AA)**



Dimensions in inches and (millimeters)

		SYMBOL	SK22	SK23	SK24	SK25	SK26	SK28	UNITS
Maximum Recurrent Peak Reverse Voltage		V <sub>RRM</sub>	20	30	40	50	60	80	Volts
Maximum RMS Voltage		V <sub>RMS</sub>	14	21	28	35	42	56	Volts
Maximum DC Blocking Voltage		V <sub>DC</sub>	20	30	40	50	60	80	Volts
Maximum Average Forward Rectified Current at Derating Lead Temperature		I <sub>O</sub>	2						Amps
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC Method)		I <sub>FSM</sub>	50						Amps
Maximum Instantaneous Forward Voltage at 2.0A DC		V <sub>F</sub>	0.55			0.70		0.85	Volts
Maximum DC Reverse Current	@ T <sub>A</sub> = 25°C	I <sub>R</sub>	1.0						mAmps
at Rated DC Blocking Voltage	@ T <sub>A</sub> = 100°C		20						
Typical Thermal Resistance (Note 2)		R θJA	75						°C/W
Typical Junction Capacitance (Note 1)		C <sub>J</sub>	130						pF
Operating Temperature Range		T <sub>J</sub>	-65 to + 125						°C
Storage Temperature Range		T <sub>STG</sub>	-65 to + 150						°C

NOTES : 1. Thermal Resistance (Junction to Ambient).  
2. Measured at 1 MHz and applied reverse voltage of 4.0 volts.  
3. P.C.B Mounted with 0.2X0.2\*(5.0X5.0mm<sup>2</sup>) copper pad area.

## RATING AND CHARACTERISTIC CURVES ( SK22 THRU SK28 )

FIG. 1 - TYPICAL FORWARD CURRENT DERATING CURVE




FIG. 2 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG. 3A - TYPICAL REVERSE CHARACTERISTICS




FIG. 3B - TYPICAL REVERSE CHARACTERISTICS




FIG. 4 - TYPICAL JUNCTION CAPACITANCE




FIG. 5 - MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT

