



GLASS PASSIVATED RECTIFIER


1N4001G THRU 1N4007G	VOLTAGE RANGE CURRENT	50 to 1000 Volts 1.0 Ampere
----------------------	--------------------------	--------------------------------

FEATURES

- Glass passivated chip junction
- Low forward voltage
- Low reverse leakage
- High forward surge current capacity
- High temperature soldering guaranteed:
260 /10 seconds, 0.375" (9.5mm) lead length

MECHANICAL DATA

- Case: transfer molded plastic
- Epoxy: UL94V – 0 rate flame retardant
- Polarity: Color band denotes cathode end
- Lead: Plated axial lead, solderable per MIL-STD-202E method 208C
- Mounting position: any
- Weight: 0.012 ounce, 0.33 gram



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

	SYMBOLS	1N 4001G	1N 4002G	1N 4003G	1N 4004G	1N 4005G	1N 4006G	1N 4007G	UNIT
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage	V _{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Current, 0.375" (9.5mm) lead length at T _A = 75°C	I _(AV)	1.0							Amps
Peak Forward Surge Current 8.3mS single half sine wave superimposed on rated load (JEDEC method)	I _{FSM}	30							Amps
Maximum Instantaneous Forward Voltage @ 1.0A	V _F	1.1							Volts
Maximum DC Reverse Current at Rated T _A = 25 °C	I _R	5.0							μA
DC Blocking Voltage per element T _A = 125 °C		50							
Maximum Full Load Reverse Current, full cycle Average 0.375" (9.5mm) lead length at T _L = 75 °C	I _{R(AV)}	30							μA
Typical Junction Capacitance (Measured at 1.0MHz and applied reverse voltage of 4.0V)	C _J	15							pF
Typical Thermal Resistance (Note 1)	R _{θJA}	50							°C/W
Operating Junction Temperature Range	T _J	(-65 to +175)							°C
Storage Temperature Range	T _{STG}	(-65 to +175)							°C

Notes:

1. Thermal resistance from junction to ambient with 0.375" (9.5mm) lead length, PCB mounted with 0.2" x 0.2" (5.0mm x 5.0mm) copper pads



RATINGS AND CHARACTERISTIC CURVES 1N4001G THRU 1N4007G

FIG.1-TYPICAL FORWARD CURRENT
DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK
FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS
FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE
CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE

