

FEATURES


- Single 5V power supply
- Propagation delay, 3.5ns typical
- Fully compatible with Motorola MC10H350
- Available in 20-pin PLCC package

DESCRIPTION

The SY10H350 consists of 4 translators with differential inputs and TTL outputs. The 3-state outputs can be disabled by applying a HIGH TTL logic level on the common OE input.


The SY10H350 is designed to be used primarily in systems incorporating both ECL and TTL logic operating off a common power supply. The separate V_{CC} power pins are not connected internally and thus isolate the noisy TTL V_{CC} runs from the relatively quiet ECL V_{CC} runs on the printed circuit board. The differential inputs allow the H350 to be used as an inverting or noninverting translator, or a differential line receiver. The H350 can also drive CMOS with the addition of a pullup resistor.

BLOCK DIAGRAM



V_{CC} (+5 VDC) = Pins 2 and 20; GND = Pin 10

PIN CONFIGURATION



PIN NAMES

Pin	Function
$D_0 - D_3$	True PECL Inputs
$/D_0 - /D_3$	Inverted PECL Inputs
$Q_0 - Q_3$	TTL Outputs
V_{CCE}	PECL V_{CC} (5.0V)
V_{CCT}	TTL V_{CC} (5.0V)
GND	Ground
/OE	Output Enable

ABSOLUTE MAXIMUM RATINGS⁽¹⁾

Symbol	Parameter	Value	Unit
V_{CC}	Power Supply Voltage	-0.5 to +7.0	V
V_I	PECL Input Voltage	0V to $V_{CC}+0.5$	V
V_O	Voltage Applied to Output at HIGH State	-0.5 to +5.5	V
I_O	Current Applied to Output at LOW State	Twice the Rated I_{OL}	mA
T_{store}	Storage Temperature	-65 to +150	°C
T_A	Operating Temperature	0 to +85	°C

TRUTH TABLE

/EN	D	/D	Q
L	L	H	L
L	H	L	H
L	Open	Open	L
H	X	X	Z
Open	X	X	Z

NOTE:

1. Permanent device damage may occur if ABSOLUTE MAXIMUM RATINGS are exceeded. This is a stress rating only and functional operation is not implied at conditions other than those detailed in the operational sections of this data sheet. Exposure to ABSOLUTE MAXIMUM RATING conditions for extended periods may affect device reliability.

DC ELECTRICAL CHARACTERISTICS

$V_{CC} = 4.75V$ to $5.25V$

Symbol	Parameter	$T_A = 0^\circ C$		$T_A = +25^\circ C$			$T_A = +85^\circ C$		Unit	Condition
		Min.	Max.	Min.	Typ.	Max.	Min.	Max.		
I_{CC}	Power Supply Current TTL ECL	—	20 12	—	12 12	20 —	—	20 12	mA	No output loads
V_{OH}	Output HIGH Voltage	2.7	—	2.7	—	—	2.7	—	V	$I_{OH} = -3.0mA$
V_{OL}	Output LOW Voltage	—	0.5	—	—	0.5	—	0.5	V	$I_{OL} = 20mA$
I_{IH}	Input HIGH Current (Pin 12)	—	20	—	—	20	—	20	μA	
I_{INH}	Reverse Current Others	—	50	—	—	50	—	50	μA	
I_{IL}	Input LOW Current (Pin 12)	—	-0.6	—	—	-0.6	—	-0.6	mA	
I_{INL}	Forward Current Others	—	50	—	—	50	—	50	μA	
I_{OS}	Output Short Circuit Current	-60	-150	-60	—	-150	-60	-150	mA	$V_{OUT} = 0V$
I_{OZH}	Output Disable Current HIGH	—	50	—	—	50	—	50	μA	$V_{OUT} = 2.7V$
I_{OZL}	Output Disable Current LOW	-50	+50	-50	—	+50	-50	+50	μA	$V_{OUT} = 0.5$
V_{CMR}	Common Mode Range	2.8	V_{CC}	2.8	—	V_{CC}	2.8	V_{CC}	V	
V_{PP}	Minimum Peak-to-Peak Input ⁽¹⁾	200	—	200	—	—	200	—	mV	
V_{IH}	Input HIGH Voltage (Pin 12)	2.0	—	2.0	—	—	2.0	—	V	
V_{IL}	Input LOW Voltage (Pin 12)	—	0.8	—	—	0.8	—	0.8	V	

NOTES:

1. 200mV input guarantees full logic at output.
2. These values are for $V_{CC} = 5.0V$. Level Specifications will vary 1:1 V_{CC} .

AC ELECTRICAL CHARACTERISTICS

$V_{CC} = 4.75V$ to $5.25V$

Symbol	Parameter	$T_A = 0^\circ C$		$T_A = +25^\circ C$			$T_A = +85^\circ C$		Unit	Condition
		Min.	Max.	Min.	Typ.	Max.	Min.	Max.		
t_{PLH} t_{PHL}	Propagation Delay D to Output Q	1.5	5.0	1.5	3.5	5.0	1.5	5.0	ns	$C_L = 50pF$
t_{pdLZ} t_{pdHZ}	Output Disable Time ⁽¹⁾	2.0	8.0	2.0	—	8.0	2.0	8.0	ns	$C_L = 50pF$
t_{pdZL} t_{pdZH}	Output Enable Time ⁽¹⁾	2.0	8.0	2.0	—	8.0	2.0	8.0	ns	$C_L = 50pF$
t_r t_f	Output Rise/Fall Time (1.0V to 2.0V)	0.3	1.6	0.3	0.8	1.6	0.3	1.6	ns	$C_L = 50pF$

NOTES:

1. Guaranteed, but not tested.

SWITCHING WAVEFORMS




Figure 1. 3-State Output Low Enable and Disable Times





Figure 2. 3-State Output High Enable and Disable Times



Includes jig and probe capacitance

Figure 3. Test Load





Figure 4. Propagation Delay and Transition Times

*Application Note: Pin 12 is an /OE and the 10H350 is disabled when /OE is at V_{IH} or higher.

PRODUCT ORDERING CODE

Ordering Code	Package Type	Operating Range	Vcc Range (V)
SY10H350JC	J20-1	Commercial	+4.75 to +5.25
SY10H350JCTR	J20-1	Commercial	+4.75 to +5.25

20 LEAD PLASTIC LEADED CHIP CARRIER (J20-1)



Rev. 00

MICREL-SYNERGY 3250 SCOTT BOULEVARD SANTA CLARA CA 95054 USA

TEL + 1 (408) 980-9191 FAX + 1 (408) 914-7878 WEB <http://www.micrel.com>

This information is believed to be accurate and reliable, however no responsibility is assumed by Micrel for its use nor for any infringement of patents or other rights of third parties resulting from its use. No license is granted by implication or otherwise under any patent or patent right of Micrel Inc.

© 2000 Micrel Incorporated