



2.5" Clock Display

PART NO. : ELC-2501SR ECN : Page: 1/5

■ Features :

- Industrial standard size.
- Low power consumption.
- Categorized for luminous intensity.

■ Applications:

- Audio equipment
- Instrument panels
- Digital read out display

■ Descriptions :

- The ELC-2501 series is a large 63.5 mm (2.5")high light bar display design for viewing distances up to 7 meters.
- These displays provide excellent reliability in bright ambient light.
- These devices are made with red surface.

PART NO.	Chip	
	Material	Emitted Color
ELC-2501SR	GaAlAs	Super Red

OFFICE : NO. 25,Lane 76,Sec.3, Chung Yang Rd., Tucheng 236, Taipei, Taiwan, R.O.C.
TEL : 886-2-2267-2000,2267-9936
FAX : 886-2-2267-6244,22676189,22676306
<http://www.everlight.com>


2.5" Clock Display

PART NO.: ELC-2501SR

ECN :

Page: 2/5

■ Package Dimensions:



■ Notes:

- 1.All dimensions are in millimeters, tolerance is 0.25mm unless otherwise noted.
2.Above specification may be changed without notice.
Supplier will reserve authority on material change for above specification.



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : CDDC-250-001 REV: 1

2.5" Clock Display

PART NO. : ELC-2501SR ECN : Page: 3/5

■ Absolute maximum ratings at Ta = 25°C :

Parameter	Symbol	Rating	Unit
Reverse Voltage	VR	5	V
Forward Current	IF	40	mA
Operating Temperature	Topr	-40 to +85	°C
Storage Temperature	Tstg	-40 to +100	°C
Soldering Temperature	Tsol	260 ± 5	°C
Power Dissipation	Pd	330	mW
Peak Forward Current(Duty 1/10 @ 1KHZ)	IF(Peak)	180	mA

■ Electronic optical characteristics :

Parameter		Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	Per segment	Iv	4.0	7.65	----	mcd	IF=10mA
	Per decimal point		1.2	2.23	----		
Peak Wavelength		λ p	----	660	----	nm	IF=20mA
Dominant Wavelength		λ d	----	643	----	nm	IF=20mA
Spectrum Radiation Bandwidth		△ λ	----	20	----	nm	IF=20mA
Forward Voltage		VF	1.5	5.1	7.2	V	IF=20mA
Reverse Current		IR	----	----	10	μ A	VR=5V






EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : CDDC-250-001 REV: 1

2.5" Clock Display

PART NO. : ELC-2501SR ECN : Page: 4/5

Typical Electro-Optical Characteristic Curves:





EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : CDDC-250-001 REV: 1

2.5" Clock Display

PART NO. : ELC-2501SR ECN : Page: 5/5

■ Reliability test item and condition:

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	5 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85°C 30min └ 5 min L : -55°C 30min	50 CYCLE	76 PCS	0/1
3	Thermal Shock	H : +100°C 5min └ 10 sec L : -10°C 5min	50 CYCLE	76 PCS	0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -55°C	1000 HRS	76 PCS	0/1
6	DC Operating Life	IF = 10 mA	1000 HRS	76 PCS	0/1
7	High Temperature / High Humidity	85°C/85% RH	1000 HRS	76 PCS	0/1