

SURFACE MOUNT LED LAMP STANDARD BRIGHT 1.8mm (Dome Lens)

QTLP660C-2 HER


QTLP660C-3 Yellow

QTLP660C-4 Green

QTLP660C-7 AlGaAs Red


QTLP660C-B Blue

PACKAGE DIMENSIONS



NOTE:

- Dimensions for all drawings are in inches (mm).
- Cathode for -2, -3, -4 and B. Anode for -7.



APPLICATIONS

- Backlighting
- Status indication for consumer electronics and other equipment

DESCRIPTION

These surface mount chip LEDs are designed with a 1.8 mm dome lens that focuses the light output.

FEATURES

- Small footprint - 3.2(L) X 2.4(W) X 2.6(H) mm
- Narrow viewing angle of 30°
- Water clear
- Moisture-proof packaging
- Available in 0.315" (8mm) width tape on 7" (178mm) diameter reel; 2,000 units per reel

SURFACE MOUNT LED LAMP

STANDARD BRIGHT 1.8mm (Dome Lens)

QTLP660C-2 HER

QTLP660C-3 Yellow

QTLP660C-4 Green

QTLP660C-7 AlGaAs Red

QTLP660C-B Blue

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ Unless otherwise specified)

Parameter	Symbol	QTLP660C					Units
		-2	-3	-4	-7	-B	
Continuous Forward Current	I_F	30	30	30	30	30	mA
Peak Forward Current ($f = 1.0 \text{ KHz}$, Duty Factor = 1/10)	I_{FM}	160	160	160	180	100	mA
Reverse Voltage ($I_R = 10 \mu\text{A}$)	V_R	5	5	5	5	5	V
Power Dissipation	P_D	84	84	84	72	135	mW
Operating Temperature	T_{OPR}	-40 to +85					$^\circ\text{C}$
Storage Temperature	T_{STG}	-40 to +90					$^\circ\text{C}$
Lead Soldering Time	T_{SOL}	260 for 5 sec					$^\circ\text{C}$

ELECTRICAL / OPTICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$)

Part Number	Symbol	QTLP660C					Condition
		-2	-3	-4	-7	-B	
Luminous Intensity (mcd)	I_V						$I_F = 20\text{mA}$
Minimum		20	35	70	110	80	
Typical		40	60	120	190	110	
Forward Voltage (V)	V_F						$I_F = 20\text{mA}$
Maximum		2.8	2.8	2.8	2.4	4.5	
Typical		2.0	2.0	2.1	1.9	3.8	
Wavelength (nm)	λ_P						$I_F = 20\text{mA}$
Peak		635	585	565	660	430	
Dominant	λ_D	630	590	570	645	465	
Spectral Line Half Width (nm)	$\Delta\lambda$	45	35	30	20	65	$I_F = 20\text{mA}$
Viewing Angle ($^\circ$)	$2\Theta_{1/2}$	30	30	30	30	30	$I_F = 20\text{mA}$

QTLP660C-2 HER

QTLP660C-3 Yellow

QTLP660C-4 Green

QTLP660C-7 AlGaAs Red

QTLP660C-B Blue

TYPICAL PERFORMANCE CURVES

Fig. 1 Forward Current vs. Forward Voltage




Fig. 2 Relative Luminous Intensity vs. DC Forward Current




Fig. 3 Relative Intensity vs. Peak Wavelength




Fig.4 Radiation Diagram





Fig.5 Maximum Forward Current vs. Ambient Temperature



SURFACE MOUNT LED LAMP

STANDARD BRIGHT 1.8mm (Dome Lens)

QTLP660C-2 HER


QTLP660C-3 Yellow

QTLP660C-4 Green


QTLP660C-7 AlGaAs Red

QTLP660C-B Blue

RECOMMENDED PRINTED CIRCUIT BOARD PATTERN



RECOMMENDED IR REFLOW SOLDERING PROFILE



SURFACE MOUNT LED LAMP

STANDARD BRIGHT 1.8mm (Dome Lens)

QTLP660C-2 HER



QTL P660C-3 Yellow

QTL P660C-4 Green

QTL P660C-7 AlGaAs Red

QTL P660C-B Blue

TAPE AND REEL DIMENSIONS



for -7

Polarity

Dimensional tolerance is $\pm 0.1\text{mm}$ unless otherwise specified
 Angle: ± 0.5
 Unit: mm
 Polarity marks on the opposite sprocket side.

SURFACE MOUNT LED LAMP STANDARD BRIGHT 1.8mm (Dome Lens)

QTLP660C-2 HER



QTLP660C-3 Yellow

QTLP660C-4 Green

QTLP660C-7 AlGaAs Red

QTLP660C-B Blue

TAPE AND REEL DIMENSIONS



for -2, -3, -4 and -B
Polarity

Dimensional tolerance is ± 0.1 mm unless otherwise specified
 Angle: ± 0.5
 Unit: mm
 Polarity marks on the sprocket side.

SURFACE MOUNT LED LAMP

STANDARD BRIGHT 1.8mm (Dome Lens)

QTLP660C-2 HER

QTLP660C-3 Yellow

QTLP660C-4 Green

QTLP660C-7 AlGaAs Red

QTLP660C-B Blue

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.