



RL201G THRU RL207G

GLASS PASSIVATED JUNCTION RECTIFIER


Reverse Voltage - 50 to 1000 Volts

Forward Current - 2.0 Amperes

Features

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0 utilizing Flame retardant epoxy molding compound
- 2.0 ampere operation at $T_A=75^{\circ}\text{C}$ with no thermal runaway
- Glass passivated junction in DO-15 package

DO-15



Mechanical Data

- **Case:** Molded plastic, DO-15
- **Terminals:** Axial leads, solderable per MIL-STD-202, method 208
- **Polarity:** Color band denotes cathode
- **Mounting Position:** Any
- **Weight:** 0.014 ounce, 0.395 gram

DIMENSIONS					
DIM	inches		mm		Note
	Min.	Max.	Min.	Max.	
A	0.228	0.299	5.8	7.6	
B	0.102	0.142	2.6	3.6	φ
C	0.028	0.034	0.71	0.86	φ
D	1.000	-	25.40	-	

Maximum Ratings and Electrical Characteristics @25°C unless otherwise specified

	Symbols	RL 201G	RL 202G	RL 203G	RL 204G	RL 205G	RL 206G	RL 207G	Units
Maximum repetitive peak reverse voltage	V_{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS voltage	V_{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC blocking voltage	V_{DC}	50	100	200	400	600	800	1000	Volts
Average forward current $T_A=75^{\circ}\text{C}$	$I_{(AV)}$	2.0							Amps
Peak forward surge current 8.3ms half sine-wave	I_{FSM}	60.0							Amps
Maximum instantaneous forward voltage $I_F=2.0\text{A}; T_A=25^{\circ}\text{C}$ (Note 1)	V_F	1.0							Volts
Maximum DC reverse current at rated DC blocking voltage $T_A=25^{\circ}\text{C}$ $T_A=100^{\circ}\text{C}$	I_R	5.0 50.0							μA
Typical junction capacitance Measure at 1.0MHz, $V_R=4.0\text{V}$	C_J	20							pF
Typical thermal resistance	$R_{\theta JA}$	50							$^{\circ}\text{C/W}$
Operating and storage temperature range	T_J, T_{STG}	-65 to +175							$^{\circ}\text{C}$

Note:

(1) Pulse test: Pulse width 300uSec, Duty cycle 1%

RATINGS AND CHARACTERISTIC CURVES

Figure 1
Typical Forward Characteristics




Figure 2
Forward Derating Curve






Figure 3
Junction Capacitance




RATINGS AND CHARACTERISTIC CURVES

Figure 4
Typical Reverse Characteristics



Instantaneous Reverse Current - Amps *versus*
Percent Of Rated Peak Reverse Voltage - Volts

Figure 5
Peak Forward Surge Current



Peak Forward Surge Current - Amperes *versus*
Number Of Cycles At 60Hz - Cycles