

Intel® LXT384

Octal T1/E1/J1 Line Interface Unit

Intel Delivers

Intel introduces a family of T1/E1 3.3V transceivers that are pin-to-pin and software compatible. This LXT product series includes the Intel® LXT380, LXT381, LXT386, and LXT388 (detailed in separate product briefs), and the LXT384 (detailed in this product brief). With Intel's range of transceivers, you have the flexibility to change from E1-only designs to T1/E1 designs and migrate from two to eight ports (or vice versa) with little time and effort.

The Intel® LXT384 is an octal 3.3V short-haul PCM transceiver for use in either 1.544Mbps (T1) or 2.048Mbps (E1) applications. It incorporates eight receivers and eight transmitters in a single 144-pin LQFP or 160 PBGA package.

The LXT384 is the world's first fully integrated octal transceiver incorporating an advanced crystal-less, digital Jitter Attenuator (JA) that meets CTR12/13 and the latest SONET/SDH requirements. You can configure the LXT384 as a seven-channel transceiver with the additional channel configured as a G.772-compliant non-intrusive performance monitor.

Intel Advantage

With the introduction of its LXT38x series, Intel offers a transceiver that supports G.772 non-intrusive performance monitoring. This feature allows one channel to eavesdrop on other channels for remote monitoring and debugging purposes without interrupting service. This powerful tool can help you reduce system downtime and achieve faster time-to-market.


The Intel® LXT384 also offers Intel® Hitless Protection Switching (Intel® HPS), which



incorporates fast tri-stateable drivers and a constant delay JA. Intel® HPS helps you reduce system cost by eliminating costly mechanical relays and opto-isolators in 1+1 protection and redundancy applications. The switch from primary to backup board is less than 1 μ s—more than 1,000 times faster than mechanical relays—and helps eliminate loss of frame synchronization. A maximum of 1 bit error is generated when Intel® HPS is used instead of relays, which can generate more than 6,000 bit errors. Analog and digital JTAG can also help reduce test costs by reducing test times.

Alternate solutions require triple the PCB space or more for an eight-channel 1+1 protection application. The superior digital JA is designed for SONET/SDH applications, meets CTR12/13 specification, and provides the constant delay needed in Intel® HPS applications.

LXT384 Block Diagram



Features

- Intel® Hitless Protection Switching
- Superior crystal-less JA
- Nonintrusive performance monitor
- 3.3V supply with 5V-tolerant inputs
- Analog and digital JTAG
- 15x15mm BGA package

Benefits

- Helps eliminate expensive relays needed for 1+1 redundant applications
- Meets ETSI CTR 12/13, ITU G.736, G.742, G.823, and AT&T Pub62411 specifications
- Optimized for SONET/SDH applications, meets ITU G.783 mapping jitter specifications
- Constant throughput delay jitter attenuator
- Allows eavesdropping on other channels without interrupting service
- Easy integration and lower power consumption
- Helps reduce test costs and increase coverage
- Leads to higher integration, helps reduce PCB real estate, and helps increase ports per card

Support Collateral/Tools

Item	Description	Order Number
Support Products	■ LXT384 Octal T1/E1 Transceiver Data Sheet	248994
	■ LXT384 Design Assistant	248836
	■ LXD384—Evaluation Board for Octal T1/E1 Applications Developer Manual	249214
	■ LXT384/386/388 Frequently Asked Questions (FAQs)	249183
Application Notes	■ Transformer Specification for Intel® Transceiver Applications	249133
	■ LXT380/381/384/386/388 Redundancy Applications	249134
	■ LXT380/384 Octal T1/E1 LIUs—Interfacing with the Transwitch Octal Framer	249136
	■ LXT384/386/388 Twisted Pair Interface—without Component Changes	249138
	■ Intel® Hitless Protection Switching Backup Board not Powered	249143

Applications

- SONET/SDH tributary interfaces
- Digital cross connects
- Public/private switching trunk line interfaces
- Microwave transmission systems
- M13 and E1-E3 multiplexer

Intel® Internet Exchange Architecture

Intel® Internet Exchange Architecture (IXA) is an end-to-end family of high-performance, flexible and scalable hardware and software development building blocks designed to meet the growing performance requirements of today's networks. Based on programmable silicon and software building blocks, Intel® IXA solutions enable faster development, more cost-effective deployment, and future upgradability of network and communications systems. Additional information can be found at www.intel.com/IXA.

Intel Access

Developer Web Site	http://developer.intel.com
Intel® Internet Exchange Architecture Home Page	http://intel.com/IXA
Networking Components Home Page	http://developer.intel.com/design/network
Intel Literature Center	http://developer.intel.com/design/litcentr (800) 548-4725 7 a.m. to 7 p.m. CST (U.S. and Canada) International locations please contact your local sales office.
General Information Hotline	(800) 628-8686 or (916) 356-3104 5 a.m. to 5 p.m. PST

Information in this document is provided in connection with Intel products. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Intel's Terms and Conditions of Sale for such products, Intel assumes no liability whatsoever, and Intel disclaims any express or implied warranty, relating to sale and/or use of Intel products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right. Intel products are not intended for use in medical, life-saving or life-sustaining applications. Intel may make changes to specifications and product descriptions at any time, without notice.

Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined." Intel reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them.

Intel is a trademark or registered trademark of Intel Corporation or its subsidiaries in the United States and other countries.

*Other names and brands may be claimed as the property of others.

For more information, visit the Intel Web site at: developer.intel.com



UNITED STATES AND CANADA
Intel Corporation
Robert Noyce Building
2200 Mission College Blvd.
P.O. Box 58119
Santa Clara, CA 95052-8119
USA

EUROPE
Intel Corporation (UK) Ltd.
Pipers Way
Swindon
Wiltshire SN3 1RJ
UK

ASIA-PACIFIC
Intel Semiconductor Ltd.
32/F Two Pacific Place
88 Queensway, Central
Hong Kong, SAR

JAPAN
Intel Japan (Tsukuba HQ)
5-6
Tokodai Tsukuba-shi
300-2635 Ibaraki-ken
Japan

SOUTH AMERICA
Intel Semicondutores do Brasil LTDA
Av. Dr. Chucuri Zaidan, 940-10° andar
04583-904 São Paulo, SP
Brazil