

## Laser Diode Driver w/ Waveform Generator

The EL6935B is a highly integrated laser diode driver designed to support multi-standard writable optical drives. It accomplishes this by incorporating a waveform generator wherein the diode currents and timing details can be programmed before operation. The generator inspects the NRZ serial data waveform and generates programmed waveforms in recognition of 3, 4, 5, or 6 or more clock periods of space changing to 3, 4, 5, or 6 or more clock periods of mark, and vice versa. The part also has an IV amplifier with concurrent read and write sampling. The gains of the IV amplifier are programmable, eliminating the need for external potentiometers.

The flexible architecture supports different media and speeds for Blue, DVD, and CD standards. The programming is accomplished through a serial interface port. The clock and NRZ inputs can be either standard CMOS or LVDS, selectable through a program bit.

The EL6935B operates on a 5V supply for the analog circuits and a 2.5V supply for the digital circuits.

## Ordering Information

PART NUMBER	PACKAGE	TAPE & REEL	PKG. DWG. #
EL6935BCL	38-Pin QFN	-	MDP0046
EL6935BCL-T7	38-Pin QFN	7"	MDP0046
EL6935BCL-T13	38-Pin QFN	13"	MDP0046
EL6935BCLZ (Note)	38-Pin QFN (Pb-Free)	-	MDP0046
EL6935BCLZ-T7 (Note)	38-Pin QFN (Pb-Free)	7"	MDP0046
EL6935BCLZ-T13 (Note)	38-Pin QFN (Pb-Free)	13"	MDP0046

NOTE: Intersil Pb-free products employ special Pb-free material sets; molding compounds/die attach materials and 100% matte tin plate termination finish, which is compatible with both SnPb and Pb-free soldering operations. Intersil Pb-free products are MSL classified at Pb-free peak reflow temperatures that meet or exceed the Pb-free requirements of IPC/JEDEC J Std-020B.

## Features

- Completely programmable laser diode driver
- 500mA maximum total output
- 10-bit x 10-bit multiplying DAC output provides 10-bit full scale adjustment and 10-bit resolution at any full scale output
- 55psec timer resolution
- Two laser outputs allows read/ write DVD and CD combinations
- Programmable waveform values support CD-R, CD-RW, DVD-RAM, DVD-R, DVD-RW, DVD+R, DVD+RW, and Blue
- Two analog inputs support slope and read APC
- HFM oscillator programmable to 100mA<sub>P-P</sub> from 100MHz to 500MHz
- PLL allows reduced-frequency clock on flex cable
- Separate serial input works up to 100MHz
- Dual sampled IV amplifier with programmable sample and gain selects
- Programmable DC output when HFM is off
- Pb-free available

## Applications

- Combination DVD writable and CD writable drives
- DVD camcorders
- DVD video recorders

**Get FULL DATASHEET**

All Intersil U.S. products are manufactured, assembled and tested utilizing ISO9000 quality systems.  
Intersil Corporation's quality certifications can be viewed at [www.intersil.com/design/quality](http://www.intersil.com/design/quality)

*Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design, software and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.*

For information regarding Intersil Corporation and its products, see [www.intersil.com](http://www.intersil.com)