


100 AMP SCHOTTKY CENTER-TAP IN HERMETIC ISOLATED SIP PACKAGE



100 Amp, 45, 60 and 100 Volt Power Schottky Center-Tap Module

FEATURES

- Two Isolated Schottky Rectifiers In A Hermetic SIP Package
- Very Low Forward Voltage
- Low Recovery Charge
- Rugged Package Design
- High Efficiency For Low Voltage Supplies
- Center-Tap Configuration
- Common Cathode Standard
- Small Size
- Available Screened To MIL-S-19500, TX, TXV And S Levels

DESCRIPTION


This device has two Schottky diodes arranged in a common cathode configuration and is ideally suited for a full wave output rectifier in low voltage switching power supplies where small size and high reliability are required. Common anode configuration also available.

ABSOLUTE MAXIMUM RATINGS ($T_C = 25^\circ\text{C}$) Per Diode


Peak Reverse Voltage	45, 60, 100 V
Maximum Average DC Output Current, Per Leg	50 A
Peak Reverse Transient Current	2 A
Non-Repetitive Peak Surge Current (8.3 ms)	700 A
Storage Temperature Range	- 55°C to + 175° C
Operating Junction Temperature	- 55°C to + 150° C
Package Thermal Resistance Junction to Case	1.25° C

3.2

SCHEMATIC



PIN CONNECTION




ELECTRICAL CHARACTERISTICS (Per Diode)


Part No.	PIV	Maximum Forward Voltage @ $I_F = 50A$ ^{(1) (2)}		Maximum Reverse Current	
		$T_C = 25^{\circ}C$	$T_C = 125^{\circ}C$	$T_C = 25^{\circ}C$	$T_C = 125^{\circ}C$
OM4204XX	45	.750V	.700V	1.0mA	150mA
OM4228XX	60	.87V	.800V	7.0mA	150mA
OM4229XX	100	.97V	.900V	7.0mA	150mA

- (1) **Pulse Test:** Pulse Width 300 μ s. Duty Cycle 2.0%.
(2) **Pin Limitation:** 70 Amp per pair.

TYPICAL FORWARD VOLTAGE



TYPICAL REVERSE CURRENT



MECHANICAL OUTLINE

