



# RL201 THRU RL207

## 2.0 AMPS. SILICON RECTIFIERS


### VOLTAGE RANGE

50 to 1000 Volts

CURRENT

2.0 Amperes

### DO-15



Dimensions in inches and (millimeters)

### FEATURES

- \* Low forward voltage drop
- \* High current capability
- \* High reliability
- \* High surge current capability

### MECHANICAL DATA

- \* Case: Molded plastic
- \* Epoxy: UL 94V-0 rate flame retardant
- \* Lead: Axial leads, solderable per MIL-STD-202, method 208 guaranteed
- \* Polarity: Color band denotes cathode end
- \* Mounting Position: Any
- \* Weight: 0.40 grams

### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%


TYPE NUMBER	SYMBOLS	RL201	RL202	RL203	RL204	RL205	RL206	RL207	UNITS
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	50	100	200	400	600	800	1000	V
Maximum RMS Voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Maximum D.C Blocking Voltage	$V_{DC}$	50	100	200	400	600	800	1000	V
Maximum Average Forward Rectified Current .375"(9.5mm) lead length @ $T_A = 75^\circ\text{C}$	$I_{F(AV)}$	2.0							A
Peak Forward Surge Current, 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	$I_{FSM}$	60							A
Maximum Instantaneous Forward Voltage at 2.0A	$V_F$	1.0							V
Maximum D.C Reverse Current @ $T_A = 25^\circ\text{C}$ at Rated D.C Blocking Voltage @ $T_A = 100^\circ\text{C}$	$I_R$	5.0 50.0							$\mu\text{A}$ $\mu\text{A}$
Typical Junction Capacitance (Note 1)	$C_J$	35							pF
Typical Thermal Resistance (Note 2)	$R_{\theta JA}$	50							$^\circ\text{C}/\text{W}$
Operating Temperature Range	$T_J$	-65 to +125							$^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	-65 to +150							$^\circ\text{C}$

NOTES: 1. Measured at 1 MHz and applied reverse voltage of 4.0V D.C.


2. Thermal Resistance from Junction to Ambient 0.375"(9.5mm) Lead Length.

## RATINGS AND CHARACTERISTIC CURVES (RL201 THRU RL207)


**FIG. 1 – TYPICAL FORWARD CURRENT DERATING CURVE**




**FIG. 2 – MAXIMUM NON - REPETITIVE FORWARD SURGE CURRENT**



**FIG. 3 – TYPICAL FORWARD CHARACTERISTICS**



**FIG. 4 – TYPICAL REVERSE CHARACTERISTICS**



**FIG. 5 – TYPICAL JUNCTION CAPACITANCE**

