


SWITCHING APPLICATION.
INTERFACE CIRCUIT AND DRIVER CIRCUIT APPLICATION.



FEATURES

- With Built-in Bias Resistors.
- Simplify Circuit Design.
- Reduce a Quantity of Parts and Manufacturing Process.
- High Packing Density.

EQUIVALENT CIRCUIT



EQUIVALENT CIRCUIT (TOP VIEW)



MAXIMUM RATING (Ta=25℃)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector-Base Voltage	V _{CBO}	50	V
Collector-Emitter Voltage	V _{CEO}	50	V
Emitter-Base Voltage	V _{EBO}	5	V
Collector Current	I _C	100	mA

CHARACTERISTIC	SYMBOL	RATING	UNIT
Collector Power Dissipation	P _C *	200	mW
Junction Temperature	T _j	150	℃
Storage Temperature Range	T _{stg}	-55 ~ 150	℃

* Total Raing.


ELECTRICAL CHARACTERISTICS (Ta=25℃)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Collector Cut-off Current	I _{CBO}	V _{CB} =50V, I _E =0	-	-	100	nA
Emitter Cut-off Current	I _{EBO}	V _{EB} =5V, I _C =0	-	-	100	nA
DC Current Gain	h _{FE}	V _{CE} =5V, I _C =1mA	120	-	-	
Collector-Emitter Saturation Voltage	V _{CE(sat)}	I _C =10mA, I _B =0.5mA	-	0.1	0.3	V
Transition Frequency	f _T *	V _{CE} =10V, I _C =5mA	-	250	-	MHz
Input Resistor	KRC830E	R ₁	-	4.7	-	k Ω
	KRC831E		-	10	-	
	KRC832E		-	100	-	
	KRC833E		-	22	-	
	KRC834E		-	47	-	

Note : * Characteristic of Transistor Only.

MARK SPEC

TYPE	KRC830E	KRC831E	KRC832E	KRC833E	KRC834E
MARK	YK	YM	YN	YO	YP









KRC830E~KRC834E

ELECTRICAL CHARACTERISTICS (Ta=25 °C)

CHARACTERISTIC			SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Switching Time	Rise Time	KRC830E	t _r	V _O =5V V _{IN} =5V R _L =1k Ω	-	0.025	-	μS
		KRC831E			-	0.03	-	
		KRC832E			-	0.3	-	
		KRC833E			-	0.06	-	
		KRC834E			-	0.11	-	
	Storage Time	KRC830E	t _{stg}		-	3.0	-	
		KRC831E			-	2.0	-	
		KRC832E			-	6.0	-	
		KRC833E			-	4.0	-	
		KRC834E			-	5.0	-	
	Fall Time	KRC830E	t _f		-	0.2	-	
		KRC831E			-	0.12	-	
		KRC832E			-	2.0	-	
		KRC833E			-	0.9	-	
		KRC834E			-	1.4	-	

KRC830E~KRC834E



KRC830E~KRC834E

