



UNCONTROLLED DOCUMENT



NOTES:

1. ANODE
2. CATHODE
3. NO CONNECT
4. EMITTER
5. COLLECTOR
6. BASE

PART NUMBER  
OCP-PCDB116/X

REV.

REV. E.C.N. NUMBER AND REVISION COMMENTS

DATE

CAUTION: STATIC SENSITIVE DEVICE  
FOLLOW PROPER E.S.D. HANDLING PROCEDURES  
WHEN WORKING WITH THIS PART.

PART NUMBER TABLE

PART= /X	CTR (%)
/A	600 TO 2000
/B	1500 TO 4000
/C	3000 TO 6000
/D	5000 TO 9000
/E	600 TO 9000

ABSOLUTE MAXIMUM RATINGS (Ta=25°C)

	PARAMETER	SYMBOL	MAX	UNITS
I	FORWARD CURRENT	I <sub>F</sub>	50	mA
	PEAK FORWARD CURRENT	I <sub>FM</sub>	1	A
	REVERSE VOLTAGE	V <sub>R</sub>	6	V
	POWER DISSIPATION	P <sub>D</sub>	70	mW
O	COLLECTOR-EMITTER VOLTAGE	V <sub>CE0</sub>	300	V
	COLLECTOR-BASE VOLTAGE	V <sub>CB0</sub>	300	V
	EMITTER-BASE VOLTAGE	V <sub>EB0</sub>	6	V
	COLLECTOR CURRENT	I <sub>C</sub>	150	mA
	COLLECTOR POWER DISSIPATION	P <sub>C</sub>	200	mW
	TOTAL POWER DISSIPATION	P <sub>tot</sub>	200	mW
	ISOLATION VOLTAGE 1 MIN.	V <sub>ISO</sub>	5000	V <sub>RMS</sub>
	OPERATING TEMP.	T <sub>opr</sub>	- 30 TO + 100	°C
	STORAGE TEMP.	T <sub>stg</sub>	- 55 TO + 125	°C
	SOLDERING TEMP.	T <sub>sol</sub>	+ 260	°C
	2.0mm FROM BODY		10 SEC. MAX	

I=INPUT, O=OUTPUT.

ELECTRO-OPTICAL CHARACTERISTICS (Ta=25°C)

	PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
I	FORWARD VOLTAGE	V <sub>F</sub>	I <sub>F</sub> =20mA	-	1.2	1.4	V
	PEAK FORWARD VOLTAGE	V <sub>FM</sub>	I <sub>FM</sub> =0.5A	-	-	3.5	V
	REVERSE CURRENT	I <sub>R</sub>	V <sub>R</sub> =4V	-	-	10	μA
	TERMINAL CAPACITANCE	C <sub>t</sub>	V=0, f=1kHz	-	30	-	pF
O	COLLECTOR DARK CURRENT	I <sub>CE0</sub>	V <sub>CE</sub> =200V, I <sub>F</sub> =0	-	-	10 <sup>-6</sup>	A
T	CURRENT TRANSFER RATIO	CRT	I <sub>F</sub> =1mA, V <sub>CE</sub> =2V	600	-	9000	%
	COLLECTOR-EMITTER SATURATION VOLTAGE	V <sub>CE(sat)</sub>	I <sub>F</sub> =20mA, I <sub>C</sub> =5mA	-	-	1.5	V
	ISOLATION RESISTANCE	R <sub>ISO</sub>	DC500V	5x10 <sup>10</sup>	-	-	ohm
	FLOATING CAPACITANCE	C <sub>f</sub>	V=0, f=1MHz	-	0.6	1.0	pF
	CUT-OFF FREQUENCY	f <sub>c</sub>	V <sub>CE</sub> =5V, I <sub>C</sub> =2mA, R <sub>L</sub> =100ohm	-	7	-	kHz
	RESPONSE TIME (RISE)	t <sub>r</sub>	V <sub>CE</sub> =2V, I <sub>C</sub> =20mA, R <sub>L</sub> =100ohm	-	60	300	μS
	RESPONSE TIME (FALL)	t <sub>f</sub>	V <sub>CE</sub> =2V, I <sub>C</sub> =20mA, R <sub>L</sub> =100ohm	-	50	250	μS

I=INPUT, O=OUTPUT, T=TRANSFER CHARACTERISTICS.

UNCONTROLLED DOCUMENT

\*UNLESS OTHERWISE SPECIFIED TOLERANCE IS ±0.25mm (±0.010")

REV.

PART NUMBER

OCP-PCDB116/X

CONFIDENTIAL INFORMATION  
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

**LUMEX**  
INCORPORATED

290 E. HELLEN ROAD  
PALATINE, ILLINOIS 60067  
PHONE: 1-847-359-2790  
WEB: HTTP://WWW.LUMEX.COM

DRAWN BY: CHECKED BY: APPROVED BY: DATE: 9-29-99

PAGE: 1 OF 1

SCALE: N/A

CK/DU

SIX PIN DIP SINGLE CHANNEL PHOTOCOUPLER,

PHOTODARLINGTON OUTPUT WITH EXTERNAL BASE CONNECTION.