


UNCONTROLLED DOCUMENT

Ø3.20 [Ø0.126]    Ø2.90 [Ø0.114]



## NOTES:

1. PART NUMBER SUFFIX /X REPRESENTS AXIAL INTENSITY.

REPLACES PART #: SSL-LX3044SRC(/B-/G)

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030), MIN=+0.00 DECIMAL PRECISION MAX.=+0.00 DECIMAL PRECISION

PART NUMBER  
SSL-LX3044SRC/XREV.  
C

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	UPDATED SPECS.	11.28.94
B	E.C.N. #10584.	1.17.00
C	E.C.N. #10BRDR. & REDRAWN IN 3D.	4.10.01

ELECTRO-OPTICAL CHARACTERISTICS  $T_A=25^\circ\text{C}$   $I_f=20\text{mA}$ 

PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		660		nm	
FORWARD VOLTAGE		1.8	2.3	$V_f$	
REVERSE VOLTAGE	4.0			$V_r$	$I_r=100\mu\text{A}$
AXIAL INTENSITY /B	250	300		med	$I_f=20\text{mA}$
/C	360	430		med	$I_f=20\text{mA}$
/D	500	600		med	$I_f=20\text{mA}$
/E	700	850		med	$I_f=20\text{mA}$
/F	1000	1100		med	$I_f=20\text{mA}$
/G	1200	1300		med	$I_f=20\text{mA}$
/H	1400	1700		med	$I_f=20\text{mA}$
/J	1800	2300		med	$I_f=20\text{mA}$

Ⓜ  
Ⓜ

VIEWING ANGLE 30 2x theta

EMITTED COLOR: RED

EPOXY LENS FINISH: WATER CLEAR

LIMITS OF SAFE OPERATION AT  $25^\circ\text{C}$ 

PARAMETER	MAX	UNITS
Ⓜ PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
Ⓜ POWER DISSIPATION	100	mW
DERATE FROM $25^\circ\text{C}$	-1.6	mW/ $^\circ\text{C}$
OPERATING, STORAGE TEMP.	-40 TO +85	$^\circ\text{C}$
SOLDERING TEMP.	+260	$^\circ\text{C}$
2.0mm FROM BODY		3 SEC. MAX

\*  $t < 10\mu\text{s}$ 

UNCONTROLLED DOCUMENT

REV.

C

PART NUMBER

SSL-LX3044SRC/X

T-3mm (T-1) 660nm SUPER RED LED,  
WATER CLEAR LENS.

## CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

## RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD  
PALATINE, IL 60067-6976  
PHONE: +1.847.359.2790  
US WEB: www.lumex.com  
TW WEB: www.lumex.com.tw

Ⓜ

DRAWN BY:

BC

CHECKED BY:

APPROVED BY:

DATE: 1.17.00

PAGE: 1 OF 1

SCALE: N/A