


DATE	REVISIONS	REV																																																	
			DRAWING NUMBER SSL-LX509F3SGD																																																
ELECTRO-OPTICAL CHARACTERISTICS $T_A=25^{\circ}\text{C}$ $I_f=20\text{mA}$																																																			
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">PARAMETER</th> <th style="text-align: center;">MIN</th> <th style="text-align: center;">TYP</th> <th style="text-align: center;">MAX</th> <th style="text-align: center;">UNITS</th> <th style="text-align: center;">TEST COND</th> </tr> </thead> <tbody> <tr> <td>PEAK WAVELENGTH</td> <td></td> <td style="text-align: center;">565 (GREEN)</td> <td></td> <td style="text-align: center;">nm</td> <td></td> </tr> <tr> <td>FORWARD VOLTAGE</td> <td></td> <td style="text-align: center;">2.1</td> <td style="text-align: center;">2.8</td> <td style="text-align: center;">V_f</td> <td></td> </tr> <tr> <td>REVERSE VOLTAGE</td> <td style="text-align: center;">5.0</td> <td></td> <td></td> <td style="text-align: center;">V_r</td> <td style="text-align: center;">$I_r=100\mu\text{A}$</td> </tr> <tr> <td>AXIAL INTENSITY</td> <td></td> <td style="text-align: center;">40</td> <td></td> <td style="text-align: center;">mcd</td> <td style="text-align: center;">$I_f=20\text{mA}$</td> </tr> <tr> <td>VIEWING ANGLE</td> <td></td> <td style="text-align: center;">60</td> <td></td> <td style="text-align: center;">2x theta</td> <td></td> </tr> <tr> <td>EMITTED COLOR</td> <td style="text-align: center;">GREEN</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>EPOXY LENS FINISH</td> <td style="text-align: center;">GREEN DIFFUSED</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>				PARAMETER	MIN	TYP	MAX	UNITS	TEST COND	PEAK WAVELENGTH		565 (GREEN)		nm		FORWARD VOLTAGE		2.1	2.8	V_f		REVERSE VOLTAGE	5.0			V_r	$I_r=100\mu\text{A}$	AXIAL INTENSITY		40		mcd	$I_f=20\text{mA}$	VIEWING ANGLE		60		2x theta		EMITTED COLOR	GREEN					EPOXY LENS FINISH	GREEN DIFFUSED				
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND																																														
PEAK WAVELENGTH		565 (GREEN)		nm																																															
FORWARD VOLTAGE		2.1	2.8	V_f																																															
REVERSE VOLTAGE	5.0			V_r	$I_r=100\mu\text{A}$																																														
AXIAL INTENSITY		40		mcd	$I_f=20\text{mA}$																																														
VIEWING ANGLE		60		2x theta																																															
EMITTED COLOR	GREEN																																																		
EPOXY LENS FINISH	GREEN DIFFUSED																																																		
LIMITS OF SAFE OPERATION AT 25°C																																																			
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">PARAMETER</th> <th style="text-align: center;">MAX</th> <th style="text-align: center;">UNITS</th> </tr> </thead> <tbody> <tr> <td>PEAK FORWARD CURRENT*</td> <td style="text-align: center;">150</td> <td style="text-align: center;">mA</td> </tr> <tr> <td>STEADY CURRENT</td> <td style="text-align: center;">25</td> <td style="text-align: center;">mA</td> </tr> <tr> <td>POWER DISSIPATION</td> <td style="text-align: center;">105</td> <td style="text-align: center;">mW</td> </tr> <tr> <td>DERATE FROM 25°C</td> <td style="text-align: center;">-1.2</td> <td style="text-align: center;">mW/$^{\circ}\text{C}$</td> </tr> <tr> <td>OPERATING, STORAGE TEMP</td> <td style="text-align: center;">-40 TO +85</td> <td style="text-align: center;">$^{\circ}\text{C}$</td> </tr> <tr> <td>LEAD SOLDERING TEMP 2.0mm FROM BODY</td> <td style="text-align: center;">+260</td> <td style="text-align: center;">$^{\circ}\text{C}$</td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">3 SEC. MAX</td> </tr> </tbody> </table>				PARAMETER	MAX	UNITS	PEAK FORWARD CURRENT*	150	mA	STEADY CURRENT	25	mA	POWER DISSIPATION	105	mW	DERATE FROM 25°C	-1.2	mW/ $^{\circ}\text{C}$	OPERATING, STORAGE TEMP	-40 TO +85	$^{\circ}\text{C}$	LEAD SOLDERING TEMP 2.0mm FROM BODY	+260	$^{\circ}\text{C}$			3 SEC. MAX																								
PARAMETER	MAX	UNITS																																																	
PEAK FORWARD CURRENT*	150	mA																																																	
STEADY CURRENT	25	mA																																																	
POWER DISSIPATION	105	mW																																																	
DERATE FROM 25°C	-1.2	mW/ $^{\circ}\text{C}$																																																	
OPERATING, STORAGE TEMP	-40 TO +85	$^{\circ}\text{C}$																																																	
LEAD SOLDERING TEMP 2.0mm FROM BODY	+260	$^{\circ}\text{C}$																																																	
		3 SEC. MAX																																																	
* $t < 10\mu\text{s}$																																																			
<p>RELIABILITY NOTE OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.</p>																																																			
<div style="display: flex; justify-content: space-between; align-items: center;"> <div style="text-align: center;">  <p>LUMEX OPTO COMPONENTS INC.</p> </div> <div style="text-align: right;"> 292 E. HELLEN ROAD PALATINE, ILLINOIS 60067 (708) 359-2790 </div> </div>																																																			
<small>CONFIDENTIAL INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX OPTO/COMPONENTS, INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX OPTO/COMPONENTS, INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.</small>																																																			
DATE: 6-24-96		DWN:	CHK'D:																																																
SCALE: N/A			APPD:																																																
T-5 (T-1 3/4) FLANGELESS LED SUPER GREEN, DIFFUSED LENS																																																			
PAGE 1 OF 1		DRAWING NUMBER SSL-LX509F3SGD																																																	
		REV																																																	