

DATE	REVISIONS	REV																																																	
			DRAWING NUMBER SSL-LX509F3SYD																																																
ELECTRO-OPTICAL CHARACTERISTICS $T_A = 25^\circ\text{C}$ $I_f = 20\text{mA}$																																																			
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">PARAMETER</th> <th style="text-align: center;">MIN</th> <th style="text-align: center;">TYP</th> <th style="text-align: center;">MAX</th> <th style="text-align: center;">UNITS</th> <th style="text-align: center;">TEST COND</th> </tr> </thead> <tbody> <tr> <td>PEAK WAVELENGTH</td> <td></td> <td style="text-align: center;">585 (YELLOW)</td> <td></td> <td style="text-align: center;">nm</td> <td></td> </tr> <tr> <td>FORWARD VOLTAGE</td> <td></td> <td style="text-align: center;">2.1</td> <td style="text-align: center;">2.8</td> <td style="text-align: center;">V_f</td> <td></td> </tr> <tr> <td>REVERSE VOLTAGE</td> <td style="text-align: center;">5.0</td> <td></td> <td></td> <td style="text-align: center;">V_r</td> <td style="text-align: center;">$I_r = 100\mu\text{A}$</td> </tr> <tr> <td>AXIAL INTENSITY</td> <td></td> <td style="text-align: center;">150</td> <td></td> <td style="text-align: center;">mcd</td> <td style="text-align: center;">$I_f = 20\text{mA}$</td> </tr> <tr> <td>VIEWING ANGLE</td> <td></td> <td style="text-align: center;">60</td> <td></td> <td style="text-align: center;">2x theta</td> <td></td> </tr> <tr> <td>EMITTED COLOR</td> <td style="text-align: center;">YELLOW</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>EPOXY LENS FINISH</td> <td style="text-align: center;">YELLOW DIFFUSED</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>				PARAMETER	MIN	TYP	MAX	UNITS	TEST COND	PEAK WAVELENGTH		585 (YELLOW)		nm		FORWARD VOLTAGE		2.1	2.8	V_f		REVERSE VOLTAGE	5.0			V_r	$I_r = 100\mu\text{A}$	AXIAL INTENSITY		150		mcd	$I_f = 20\text{mA}$	VIEWING ANGLE		60		2x theta		EMITTED COLOR	YELLOW					EPOXY LENS FINISH	YELLOW DIFFUSED				
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND																																														
PEAK WAVELENGTH		585 (YELLOW)		nm																																															
FORWARD VOLTAGE		2.1	2.8	V_f																																															
REVERSE VOLTAGE	5.0			V_r	$I_r = 100\mu\text{A}$																																														
AXIAL INTENSITY		150		mcd	$I_f = 20\text{mA}$																																														
VIEWING ANGLE		60		2x theta																																															
EMITTED COLOR	YELLOW																																																		
EPOXY LENS FINISH	YELLOW DIFFUSED																																																		
LIMITS OF SAFE OPERATION AT 25°C																																																			
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">PARAMETER</th> <th style="text-align: center;">MAX</th> <th style="text-align: center;">UNITS</th> </tr> </thead> <tbody> <tr> <td>PEAK FORWARD CURRENT*</td> <td style="text-align: center;">150</td> <td style="text-align: center;">mA</td> </tr> <tr> <td>STEADY CURRENT</td> <td style="text-align: center;">30</td> <td style="text-align: center;">mA</td> </tr> <tr> <td>POWER DISSIPATION</td> <td style="text-align: center;">125</td> <td style="text-align: center;">mW</td> </tr> <tr> <td>DERATE FROM 25°C</td> <td style="text-align: center;">-1.2</td> <td style="text-align: center;">mW/$^\circ\text{C}$</td> </tr> <tr> <td>OPERATING, STORAGE TEMP</td> <td style="text-align: center;">-40 TO +85</td> <td style="text-align: center;">$^\circ\text{C}$</td> </tr> <tr> <td>LEAD SOLDERING TEMP</td> <td style="text-align: center;">+260</td> <td style="text-align: center;">$^\circ\text{C}$</td> </tr> <tr> <td>2.0mm FROM BODY</td> <td></td> <td style="text-align: center;">3 SEC. MAX</td> </tr> </tbody> </table>				PARAMETER	MAX	UNITS	PEAK FORWARD CURRENT*	150	mA	STEADY CURRENT	30	mA	POWER DISSIPATION	125	mW	DERATE FROM 25°C	-1.2	mW/ $^\circ\text{C}$	OPERATING, STORAGE TEMP	-40 TO +85	$^\circ\text{C}$	LEAD SOLDERING TEMP	+260	$^\circ\text{C}$	2.0mm FROM BODY		3 SEC. MAX																								
PARAMETER	MAX	UNITS																																																	
PEAK FORWARD CURRENT*	150	mA																																																	
STEADY CURRENT	30	mA																																																	
POWER DISSIPATION	125	mW																																																	
DERATE FROM 25°C	-1.2	mW/ $^\circ\text{C}$																																																	
OPERATING, STORAGE TEMP	-40 TO +85	$^\circ\text{C}$																																																	
LEAD SOLDERING TEMP	+260	$^\circ\text{C}$																																																	
2.0mm FROM BODY		3 SEC. MAX																																																	
* $t < 10\mu\text{s}$																																																			
RELIABILITY NOTE OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.																																																			
<div style="display: flex; justify-content: space-between; align-items: center;"> <div style="width: 45%;"> </div> <div style="width: 50%; text-align: right;"> <p>LUMEX OPTO COMPONENTS INC.</p> <p>292 E. HELLEN ROAD PALATINE, ILLINOIS 60067 (708) 359-2790</p> </div> </div>																																																			
CONFIDENTIAL INFORMATION <small>THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX OPTO/COMPONENTS, INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX OPTO/COMPONENTS, INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.</small>																																																			
DATE: 6-24-96		DWN:																																																	
SCALE: N/A		CHK'D:																																																	
		APPD:																																																	
T-5 (T-1 3/4) FLANGELESS LED SUPER YELLOW, DIFFUSED LENS																																																			
PAGE 1 OF 1		DRAWING NUMBER SSL-LX509F3SYD																																																	
CK		REV																																																	