

# 2.3" 8x8 Bi-Color Dot Matrix Display

## FEATURES


- 2.3" 8x8 dot matrix display
- Grey surface/white epoxy color

## OPTO-ELECTRICAL CHARACTERISTICS (Ta = 25°C)

PART NO.		EMITTED COLOR	PEAK WAVE LENGTH (nm)	MAXIMUM RATINGS			OPTO-ELECTRICAL CHARACTERISTICS							PIN OUT
				IF (mA)	VR (V)	PD (mW)	VF(V)			IR(μA)		IV(μcd)		
							typ.	max.	@mA	max.	@VR	typ. per seg.	@mA	
MTAN6323-AHRG	(HR)	Hi-Eff Red	635	30	5	85	2.1	3.0	20	100	5	5900	10	1
	(G)	Green	567	30	5	85	2.1	3.0	20	100	5	5100	10	1
MTAN6423-CHRG	(HR)	Hi-Eff Red	635	30	5	85	2.1	3.0	20	100	5	5900	10	2
	(G)	Green	567	30	5	85	2.1	3.0	20	100	5	5100	10	2

Operating Temperature: -25~+85, Storage Temperature: -25~+100. Other face/epoxy colors are available.

## PACKAGE DIMENSIONS AND PIN FUNCTIONS



1. ALL DIMENSIONS ARE IN mm, TOLERANCE IS  $\pm 0.25$ mm UNLESS OTHERWISE SPECIFIED.  
2. THE SLOPE ANGLE OF ANY PIN MAY BE  $\pm 5.0^\circ$  MAX.



120 Broadway • Menands, New York 12204  
Toll Free: (800) 98-4LEDS • Fax: (518) 432-7454