

DESCRIPTION


MRB31 Series are red LED lamp with 3mm diameter epoxy package.

MRB31C is red chip with red transparent lens.

MRB31D is red chip with red diffused lens.

MRB31T is red chip with clear transparent lens.

MRB31W is red chip with clear diffused lens.



- All Dimension in mm (inch)
- No Scale
- Tol : + / - 0.3mm

ABSOLUTE MAXIMUM RATINGS

Power Dissipation @ Ta=25°C

Forward Current, DC (IF)

Reverse Voltage

Operating & Storage Temperature Range

Lead Soldering Temperature (1/16" from body)

80mW

40mA

5V

-55 to +100°C

260°C for 5 sec.

ELECTRO-OPTICAL CHARACTERISTICS (Ta=25°C)

PARAMETER		SYMBOL	MRB31C	MRB31D	MRB31T	MRB31W	UNIT	CONDITIONS
Forward Voltage	MAX	VF	2.0	2.0	2.0	2.0	V	IF=20mA
Reverse Breakdown Voltage	MIN	BVR	5	5	5	5	V	IR=100μA
Luminous Intensity	MIN	IV	10	1.5	10	1.5	mcd	IF=20mA
	TYP		15	2.0	15	2.0	mcd	
Peak Wavelength	TYP	λp	660	660	660	660	nm	IF=20mA
Spectral Line Half Width	TYP	2θ	20	20	20	20	nm	IF=20mA
Viewing Angle	TYP	2θ 1/2	40	60	40	60	degree	IF=20mA

MICRO ELECTRONICS LTD.

38, Hung To Road, Microtron Building, Kwun Tong, Kowloon, Hong Kong.

Kwun Tong P.O. Box 69477 Hong Kong. Fax No. 2341 0321 Telex:43510 Micro Hx. Tel: 2343 0181-5

Aug-99