

Surface Mount Frequency Mixer

Level 10 (LO Power +10dBm) 2 to 500 MHz


Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power	50mW
IF Current	40mA

Pin Connections

LO	1
RF	4
IF	5
GROUND	2,3,6

Outline Drawing




Outline Dimensions (inch)

A	B	C	D	E	F	G
.400	.31	.200	.10	.010	.100	.050
10.16	7.87	5.08	2.54	0.25	2.54	1.27

H	J	K	L	M	wt
.420	.120	.060	.100	.020	grams
10.67	3.05	1.52	2.54	0.51	0.55

Demo Board MCL P/N: TB-44 Suggested PCB Layout (PL-083)



NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS $0.030" \pm 0.002"$; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Features

- low conversion loss, 5.36 dB typ.
- excellent L-R isolation, 44 dB typ.

Applications

- HF/VHF/UHF
- instrumentation
- cellular



CASE STYLE: QQQ130
PRICE: \$7.95 ea. QTY (1-9)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

Electrical Specifications

FREQUENCY (MHz)	CONVERSION LOSS (dB)	LO-RF ISOLATION (dB)			LO-IF ISOLATION (dB)			IP3 at center band (dBm)
		L	M	U	L	M	U	
LO/RF f_L - f_U	Mid-Band m \bar{X} σ Max.	Typ.	Min.	Typ.	Typ.	Min.	Typ.	Typ.
2-500	DC-500	58	45	44	25	30	20	55


1 dB COMP.: +1 dBm typ.

L = low range [f_L to $10 f_L$]
M = mid range [$10 f_L$ to $f_U/2$]
U = upper range [$f_U/2$ to f_U]

Typical Performance Data

Frequency (MHz)		Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)
RF	LO	LO +10dBm	LO +10dBm	LO +10dBm	LO +10dBm	LO +10dBm
2.00	32.00	6.73	68.96	58.87	1.16	2.42
5.00	35.00	5.87	67.37	56.74	1.08	2.33
10.00	40.00	6.17	65.16	52.79	1.03	2.43
20.00	50.00	6.15	60.74	47.32	1.02	2.47
32.18	62.18	6.06	57.04	43.21	1.03	2.47
50.00	80.00	6.05	48.82	29.76	1.05	2.35
77.45	47.45	6.06	55.97	37.96	1.08	2.35
100.00	70.00	5.90	59.73	36.65	1.10	2.35
122.73	92.73	5.91	63.14	35.55	1.13	2.35
152.91	122.91	5.92	56.38	34.01	1.16	2.30
198.18	168.18	5.94	48.84	32.04	1.20	2.31
228.36	198.36	5.96	45.44	30.49	1.24	2.34
250.00	220.00	6.03	43.77	29.78	1.26	2.32
273.64	243.64	6.06	42.07	28.92	1.30	2.33
303.82	273.82	6.12	39.63	27.42	1.35	2.37
334.00	304.00	6.12	37.56	26.38	1.39	2.34
379.27	349.27	6.09	34.91	25.00	1.43	2.39
409.45	379.45	5.98	33.53	24.14	1.49	2.36
454.73	424.73	6.04	31.70	22.72	1.54	2.39
500.00	470.00	6.19	30.03	21.67	1.58	2.46

Electrical Schematic



Mini-Circuits

INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified



REV. A
M98898
LRMS-1LH
DJ/FL/CP/AM
060807
Page 1 of 2

Performance Charts

