

Ultra-Small Ceramic Power Splitter/Combiner

2 Way-90° 50Ω 425 to 675 MHz

QCN-7+
QCN-7



Maximum Ratings


Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	15W* max.

* Derate linearly to 7W at 100°C ambient.

Pin Connections

SUMPORT	1
PORT 1 (0°)	4
PORT 2 (+90°)	6
GROUND	2,5
50 OHM TERM EXTERNAL	3

Outline Drawing




Outline Dimensions (inch/mm)

A	B	C	D	E	F
.126	.063	.037	.024	.022	.012
3.20	1.60	0.94	0.61	0.56	0.30

G	H	J	K	wt
.039	.042	.024	.123	grams
0.99	1.07	0.61	3.12	.020

Demo Board MCL P/N: TB-255 Suggested PCB Layout (PL-131)



- NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS 0.020" ± 0.0015"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
3. DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
4. DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Features

- low insertion loss, 0.4 dB typ.
- wrap-around terminal for excellent solderability
- ultra small, 0.12"X0.06"X0.035"
- patent pending

Applications

- UHF
- balanced amplifiers
- modulators

CASE STYLE: FV1206-1

Model	Price	Qty.
QCN-7+	\$3.95	(10-49)
QCN-7	\$3.95	(10-49)
QCN-7D+	\$4.45	(10-49)
QCN-7D	\$4.45	(10-49)

+ RoHS compliant in accordance
with EU Directive (2002/95/EC)

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.



Splitter Electrical Specifications¹

FREQ. RANGE (MHz)	ISOLATION (dB)	INSERTION LOSS (dB) Avg. of Coupled Outputs less 3 dB	PHASE UNBALANCE (Degrees)	AMPLITUDE UNBALANCE (dB)	VSWR (:1)
$f_L - f_U$	Typ. Min.	Typ. Max.	Typ. Max.	Typ. Max.	Typ.
425-675					
425-550	17 13	0.4 0.7	2 8	0.5 1.0	1.3
550-675	17 11	0.6 1.1	4 8	0.5 1.0	1.4


1. For applications requiring DC voltage to be applied to the RF ports, add suffix letter "D" to part no.
DC resistance to ground is 100 Mohms min.

Typical Performance Data

Frequency (MHz)	Insertion Loss (dB)	Amplitude Unbalance (dB)	Isolation (dB)	Phase Unbalance (deg.)	VSWR S	VSWR 1	VSWR 2
	S-1	S-2					
425.00	3.08	3.77	0.69	16.15	1.32	1.30	1.26
435.00	3.12	3.73	0.60	16.11	1.32	1.30	1.26
445.00	3.15	3.66	0.51	16.05	1.32	1.29	1.26
470.00	3.25	3.57	0.31	15.95	1.32	1.29	1.26
500.00	3.36	3.51	0.15	15.81	1.32	1.28	1.26
530.00	3.46	3.48	0.02	15.64	1.32	1.28	1.26
555.00	3.50	3.47	0.03	15.46	1.33	1.29	1.27
570.00	3.51	3.49	0.02	15.33	1.34	1.29	1.27
585.00	3.51	3.50	0.00	15.19	1.35	1.29	1.28
600.00	3.50	3.52	0.02	15.03	1.35	1.30	1.29
620.00	3.46	3.57	0.11	14.77	1.37	1.31	1.30
630.00	3.45	3.60	0.15	14.65	1.38	1.32	1.31
645.00	3.43	3.67	0.24	14.44	1.40	1.33	1.33
660.00	3.38	3.76	0.38	14.21	1.42	1.34	1.35
675.00	3.34	3.87	0.53	13.96	1.44	1.36	1.37



electrical schematic



Mini-Circuits®

INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified



REV. F
M102713
QCN-7
ED-10849/1
AD/RS/CP/AM
060906