

Surface Mount Frequency Mixer

Level 13 (LO Power +13 dBm) 2 to 500 MHz

RMS-1MH+
RMS-1MH




Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power	200mW
IF Current	40mA

Pin Connections

LO	1
RF	4
IF	5
GROUND	2,3,6

Outline Drawing




Outline Dimensions (inch mm)

A	B	C	D	E	F
.250	.31	.20	.100	.055	.055
6.35	7.87	5.08	2.54	1.27	1.40

G	H	J	K	wt
.040	.070	.270	.050	grams
1.02	1.78	6.86	1.27	0.50

Demo Board MCL P/N: TB-03 Suggested PCB Layout (PL-052) "w" loc. of pin 1 applies.



- NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .030" ± .002"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
- DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
- DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Features

- excellent L-R isolation, 44 dB typ.
- conversion loss, 5.65 dB typ.
- small size, 0.25"x0.31"x0.2"

Applications

- HF & VHF communications
- intermediate frequency for down converters

CASE STYLE: TT240
PRICE: \$8.95 ea. QTY (1-9)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

Electrical Specifications

FREQUENCY (MHz)		CONVERSION LOSS (dB)				LO-RF ISOLATION (dB)						LO-IF ISOLATION (dB)						IP3 at center band (dBm)	
LO/RF	IF	$f_L - f_U$	\bar{X}	σ	Max.	Total Range Max.	L		M		U		L		M		U		
							Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.		Min.
2-500	DC-500	5.65	.08	7.0	8.0	58	45	44	25	30	20	55	40	36	25	28	17	26	


1 dB COMP.: +9 dBm typ.
For phase detection, DC output positive with in-phase RF & LO.

L = low range [f_L to $10 f_L$]
M = mid range [$10 f_L$ to $f_U/2$]
U = upper range [$f_U/2$ to f_U]

Typical Performance Data

Frequency (MHz)		Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)
RF	LO					
		LO +13dBm	LO +13dBm	LO +13dBm	LO +13dBm	LO +13dBm
2.00	32.00	6.87	74.51	65.71	1.13	2.10
5.00	35.00	5.99	68.76	61.00	1.06	2.01
10.00	40.00	6.21	63.07	55.80	1.02	2.15
20.00	50.00	6.21	57.31	49.78	1.01	2.20
32.18	62.18	6.13	52.98	45.20	1.02	2.17
50.00	80.00	6.10	49.34	40.85	1.04	2.08
77.45	47.45	6.18	47.86	38.28	1.06	2.06
100.00	70.00	6.00	47.68	37.14	1.09	2.04
122.73	92.73	6.08	47.59	36.20	1.11	2.00
168.00	138.00	6.07	45.07	34.10	1.13	1.98
198.18	168.18	6.11	42.15	31.58	1.16	1.99
228.36	198.36	6.11	39.78	30.31	1.18	1.98
250.00	220.00	6.27	37.93	29.36	1.20	1.98
273.64	243.64	6.21	35.54	27.74	1.23	2.01
303.82	273.82	6.26	32.56	25.93	1.25	2.01
349.09	319.09	6.39	29.95	24.88	1.28	2.01
379.27	349.27	6.47	28.87	23.78	1.33	2.01
409.45	379.45	6.45	27.89	22.58	1.36	2.03
454.73	424.73	6.64	25.80	20.47	1.41	2.07
500.00	470.00	7.03	23.97	18.39	1.45	2.09

Electrical Schematic



Mini-Circuits®

INTERNET <http://www.minicircuits.com>

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

Mini-Circuits ISO 9001 & ISO 14001 Certified



REV. A
M98898
RMS-1MH
060515
Page 1 of 2

Performance Charts

