


# NAIS

## HIGH ELECTRICAL & MECHANICAL NOISE IMMUNITY RELAY

# JQ RELAYS



mm inch

## FEATURES

- High electrical noise immunity
- High switching capacity in a compact package
- High sensitivity: 200 mW (1a), 400 mW (1c)
- High surge voltage: 8,000 V between contacts and coil
- UL, CSA, VDE, TÜV, SEMKO approved
- Class B coil insulation type available

## SPECIFICATIONS

### Contact

				Standard type	High capacity type
Arrangement				1 Form A, 1 Form C	
Initial contact resistance, max. (By voltage drop 6 V DC 1 A)				100 mΩ	
Contact material				Silver alloy	
Rating (resistive)	Nominal switching capacity	1a		5 A 125 V AC 2 A 250 V AC 5 A 30 V DC	10 A 125 V AC 5 A 250 V AC 5 A 30 V DC
		1c	N.O.	5 A 125 V AC 2 A 250 V AC 3 A 30 V AC	10 A 125 V AC 5 A 250 V AC 5 A 30 V DC
			N.C.	2 A 125 V AC 1 A 250 V AC 1 A 30 V DC	3 A 125 V AC 2 A 250 V AC 1 A 30 V DC
	Max. switching power	1c	1a	625 VA, 150 W	1,250 VA, 150 W
			N.O.	625 VA, 90 W	1,250 V AC, 150 W
			N.C.	250 VA, 30 W	500 V AC, 30 W
	Max. switching voltage		250 V AC, 110 V DC (0.3A)		
	Max. switching current		N.O.: 5 A N.C.: 2 A N.O.: 10 A N.C.: 3 A		
Expected mechanical life (at 180 cpm)(min. operations)				10 <sup>7</sup>	

### Expected electrical life (min. operations)

Type	Switching capacity		No. of operations
Standard type	1a	5 A 125 V AC	5×10 <sup>4</sup>
		3 A 125 V AC	2×10 <sup>5</sup>
		2 A 250 V AC	2×10 <sup>5</sup>
		5 A 30 V DC	10 <sup>5</sup>
	1c	N.O.	5×10 <sup>4</sup>
		N.C.	2×10 <sup>5</sup>
High capacity type	1a	10 A 125 V AC	5×10 <sup>4</sup>
		5 A 250 V AC	5×10 <sup>4</sup>
		5 A 30 V DC	10 <sup>5</sup>
	1c	N.O.	5×10 <sup>4</sup>
		N.C.	2×10 <sup>5</sup>
	1c	3 A 125 V AC	2×10 <sup>5</sup>
		2 A 250 V AC	2×10 <sup>5</sup>
		1 A 30 V DC	10 <sup>5</sup>

### Coil (at 20°C 68°F)

Nominal operating power	1a: 200 mW	1c: 400 mW
-------------------------	------------	------------

### Characteristics

Max. operating speed		20 cpm
Initial insulation resistance* <sup>1</sup>		Min. 1,000 MΩ at 500 V DC
Initial breakdown voltage* <sup>2</sup>	Between open contacts	1a: 1,000 Vrms for 1 min. 1c: 750 Vrms for 1 min.
	Between contacts and coil	4,000 Vrms for 1 min.
Surge voltage between contact and coil* <sup>3</sup>		8,000 V
Operate time* <sup>4</sup> (at nominal voltage)		Approx. 5 ms
Release time* <sup>4</sup> (at nominal voltage)(without diode)		Approx. 2 ms
Temperature rise* <sup>5</sup>		Max. 45°C
Shock resistance	Functional* <sup>6</sup>	Min. 294 m/s <sup>2</sup> {30 G}
	Destructive* <sup>7</sup>	Min. 980 m/s <sup>2</sup> {100 G}
Vibration resistance	Functional* <sup>8</sup>	98 m/s <sup>2</sup> {10 G}, 10 to 55 Hz at double amplitude of 1.6 mm
	Destructive	117.6 m/s <sup>2</sup> {12 G}, 10 to 55 Hz at double amplitude of 2.0 mm
Conditions for operation, transport and storage* <sup>9</sup> (Not freezing and condensing at low temperature)		Ambient temp.* <sup>10</sup> -40°C to +85°C -40°F to +185°F
		Humidity 5 to 85% R.H.
Unit weight		Approx. 7 g .25 oz

### Remarks

- \* Specifications will vary with foreign standards certification ratings.  
<sup>\*1</sup> Measurement at same location as "Initial breakdown voltage" section  
<sup>\*2</sup> Detection current: 10 mA  
<sup>\*3</sup> Wave is standard shock voltage of ±1.2 × 50μs according to JEC-212-1981  
<sup>\*4</sup> Excluding contact bounce time  
<sup>\*5</sup> Measured conditions

Standard type	Resistive, nominal voltage applied to the coil. Contact carrying current: 5 A, at 70°C 158°F
High capacity type	Resistive, nominal voltage applied to the coil. Contact carrying current: 10 A, at 70°C 158°F

- <sup>\*6</sup> Half-wave pulse of sine wave: 11ms; detection time: 10μs  
<sup>\*7</sup> Half-wave pulse of sine wave: 6ms  
<sup>\*8</sup> Detection time: 10μs  
<sup>\*9</sup> Refer to 5. Conditions for operation, transport and storage mentioned in AMBIENT ENVIRONMENT (Page 24).  
<sup>\*10</sup> When using relays in a high ambient temperature, consider the pick-up voltage rise due to the high temperature (a rise of approx. 0.4% V for each 1°C 33.8°F with 20°C 68°F as a reference) and use a coil impressed voltage that is within the maximum allowable voltage range.

TYPICAL APPLICATIONS

- Air conditioners
- Refrigerators
- Microwave ovens
- Heaters

ORDERING INFORMATION

Ex. JQ

1a

P

—

B

—

12

V


Contact arrangement	Contact capacity	Coil insulation class	Coil voltage (DC)
1a: 1 Form A 1: 1 Form C	Nil: Standard P: High capacity	Nil: Class E coil insulation B: Class B coil insulation	5, 6, 9, 12, 18, 24, 48* V

UL/CSA, VDE, SEMKO approved type is standard.  
\* Available only for 1 Form C type


TYPES AND COIL DATA at 20°C 68°F

	Part No.	Nominal voltage, V DC	Pick-up voltage, V DC (min.)	Drop-out voltage, V DC (min.)	Nominal operating current, mA	Nominal operating power, mW	Coil resistance, Ω (±10%)	Max. allowable voltage, V DC
1 Form A	Standard type	JQ1a-5V	5	3.75	0.25	40	125	180% of nominal voltage (at 20°C 68°F)
		JQ1a-6V	6	4.5	0.3	33.3	180	
		JQ1a-9V	9	6.75	0.45	22.2	405	
		JQ1a-12V	12	9	0.6	16.7	720	
		JQ1a-18V	18	13.5	0.9	11.1	1,620	
		JQ1a-24V	24	18	1.2	8.3	2,880	
	High capacity type	JQ1aP-5V	5	4	0.25	40	125	130% of nominal voltage (at 85°C 185°F)
		JQ1aP-6V	6	4.8	0.3	33.3	180	
		JQ1aP-9V	9	7.2	0.45	22.2	405	
		JQ1aP-12V	12	9.6	0.6	16.7	720	
		JQ1aP-18V	18	14.4	0.9	11.1	1,620	
		JQ1aP-24V	24	19.2	1.2	8.3	2,880	
1 Form C	Standard type	JQ1-5V	5	3.75	0.25	80	62.5	150% of nominal voltage (at 20°C 68°F)
		JQ1-6V	6	4.5	0.3	66.7	90	
		JQ1-9V	9	6.75	0.45	44.4	202.5	
		JQ1-12V	12	9	0.6	33.3	360	
		JQ1-18V	18	13.5	0.9	22.2	810	
		JQ1-24V	24	18	1.2	16.7	1,440	
		JQ1-48V	48	36	2.4	8.3	5,760	
	High capacity type	JQ1P-5V	5	4	0.25	80	62.5	110% of nominal voltage (at 85°C 185°F)
		JQ1P-6V	6	4.8	0.3	66.7	90	
		JQ1P-9V	9	7.2	0.45	44.4	202.5	
		JQ1P-12V	12	9.6	0.6	33.3	360	
		JQ1P-18V	18	14.4	0.9	22.2	810	
		JQ1P-24V	24	19.2	1.2	16.7	1,440	
		JQ1P-48V	48	38.4	2.4	8.3	5,760	


## DIMENSIONS



1 Form A



1 Form C



### Dimension :


Max. 1mm .039 inch  
 1 to 5mm .039 to .118 inch  
 Min. 5mm .118 inch

### General tolerance


$\pm 0.2 \pm 0.008$   
 $\pm 0.3 \pm 0.012$   
 $\pm 0.4 \pm 0.016$

Schematic (Bottom view)

1 Form A




1 Form C




PC board pattern (Copper-side view)

1 Form A




1FormC




Tolerance:  $\pm 0.1 \pm 0.004$

## REFERENCE DATA

Max. switching capacity (1 Form A type)




Max. switching capacity (1 Form C type)



### Standard type


1-(1). Operate &amp; release time (1 Form A type)

Tested sample: JQ1a-12V, 25 pcs.




1-(2). Operate &amp; release time (1 Form C type)

Tested sample: JQ1-24V, 25 pcs.




2. Life curve

Ambient temperature: room temperature




### 3-(1). Coil temperature rise (1 Form A type)

Contact carrying current: 3 A, 5 A  
Measured portion: Inside the coil




### 3-(2). Coil temperature rise (1 Form C type)

Contact carrying current: 3 A, 5 A  
Measured portion: Inside the coil




### 4-(1). Ambient temperature characteristics (1 Form A type)

Tested sample: JQ1a-24V  
Contact carrying current: 3 A, 5 A



### 4-(2). Ambient temperature characteristics (1 Form C type)

Tested sample: JQ1-24V  
Contact carrying current: 3 A, 5 A




- ① Allowable ambient temperature against % coil voltage (max. inside the coil temperature set as 130°C 266°F) (Carrying current: 3 A)
- ② Allowable ambient temperature against % coil voltage (max. inside the coil temperature set as 130°C 266°F) (Carrying current: 5 A)
- ③ Allowable ambient temperature against % coil voltage (max. inside the coil temperature set as 115°C 239°F) (Carrying current: 3 A)
- ④ Allowable ambient temperature against % coil voltage (max. inside the coil temperature set as 115°C 239°F) (Carrying current: 5 A)
- ⑤ Pick-up voltage with a hot-start condition of 100%V on the coil (Carrying current: 3 A)
- ⑥ Pick-up voltage with a hot-start condition of 100%V on the coil (Carrying current: 5 A)
- ⑦ Pick-up voltage

## High capacity type


### 1-(1). Operate & release time (1 Form A type)

Tested sample: JQ1aP-12V, 25 pcs.




### 1-(2). Operate & release time (1 Form C type)

Tested sample: JQ1P-12V, 25 pcs.




### 2. Life curve

Ambient temperature: room temperature




### 3-(1). Coil temperature rise (1 Form A type)

Contact carrying current: 5 A, 10 A  
Measured portion: Inside the coil




### 3-(2). Coil temperature rise (1 Form C type)

Contact carrying current: 5 A, 10 A  
Measured portion: Inside the coil




#### 4-(1). Ambient temperature characteristics (1 Form A type)

Tested sample: JQ1aP-24V  
Contact carrying current: 5 A, 10 A



#### 4-(2). Ambient temperature characteristics (1 Form C type)

Tested sample: JQ1P-24V  
Contact carrying current: 5 A, 10 A



- ① Allowable ambient temperature against % coil voltage (max. inside the coil temperature set as 130°C 266°F) (Carrying current: 5 A)
- ② Allowable ambient temperature against % coil voltage (max. inside the coil temperature set as 130°C 266°F) (Carrying current: 10 A)
- ③ Allowable ambient temperature against % coil voltage (max. inside the coil temperature set as 115°C 239°F) (Carrying current: 5 A)
- ④ Allowable ambient temperature against % coil voltage (max. inside the coil temperature set as 115°C 239°F) (Carrying current: 10 A)
- ⑤ Pick-up voltage with a hot-start condition of 100%V on the coil (Carrying current: 10 A)
- ⑥ Pick-up voltage with a hot-start condition of 100%V on the coil (Carrying current: 5 A)
- ⑦ Pick-up voltage

**For Cautions for Use, see Relay Technical Information (Page 11 to 39).**