

0.5 μ m CMOS Gate Array
CMOS-N5 Family




*High-speed operation with a 5-V power supply voltage
Drastic cost reduction*

**New
Products**

Features

The CMOS-N5 family is a channel-less type gate array that provides high speed operation with a 5-V power supply voltage. Drastic cost reductions have been achieved compared with the conventional CMOS-6 and CMOS-8 families thanks to higher integration by the adoption of 0.5 μm technology (2-layer wiring), and lowering the package assembly cost. Moreover, the 3-V power supply voltage is supported for the CMOS-N5 family.



[Integration]

- 3K to 120K gates (number of integrated gates)
- 2K to 74K gates (number of usable gates)

[Package]

- QFP (FP) 160 to 304 pins
- TQFP 48 to 80 pins
- LQFP 44 to 160 pins

[High-speed operation] (preliminary)

- $t_{PD} = 0.2 \text{ ns}$ (2-input NAND (power gate), fanout = 2, standard wiring length)
- Operating frequency: 60 MHz max.

[Function blocks]

- CPU peripheral block
- RAM block (1 port/2 ports)
- Oscillation block
- CTS block

[Test design]

- Scan path test

Product Overview

Product type list (preliminary)

Product name	μ PD65880	μ PD65881	μ PD65882	μ PD65883	μ PD65884
Number of integrated gates ^{Note 1}	3456	5880	13952	25344	33864
Number of usable gates ^{Note 2}	2073	3528	8371	15206	20318
Number of pads ^{Note 3}	72	88	120	160	184
Internal gate	0.30 ns (fanout = 2, wiring length=2mm)				
Power gate	0.22 ns (fanout = 2, wiring length=2mm)				
Input buffer	0.33 ns (fanout = 2, wiring length=2mm)				
Output buffer	1.30 ns ($C_L = 15$ pF)				
Output drive capability	$I_{OL} = 3, 6, 9, 12, 18, 24$ mA				
Power supply voltage	5 V \pm 10 % (CMOS level)				

Product name	μ PD65885	μ PD65887	μ PD65889	μ PD65890	μ PD65893
Number of integrated gates ^{Note 1}	40768	56496	76000	99528	123384
Number of usable gates ^{Note 2}	24460	33897	45600	59716	74030
Number of pads ^{Note 3}	244	284	324	372	412
Internal gate	0.30 ns (fanout = 2, wiring length=2mm)				
Power gate	0.22 ns (fanout = 2, wiring length=2mm)				
Input buffer	0.33 ns (fanout = 2, wiring length=2mm)				
Output buffer	1.30 ns ($C_L = 15$ pF)				
Output drive capability	$I_{OL} = 3, 6, 9, 12, 18, 24$ mA				
Power supply voltage	5 V \pm 10 % (CMOS level)				

Notes 1. 2-input NAND conversion

2. Cell utilization rate 60 %

3. Including power supply and GND pins. The number of pins that can actually be used differs depending on the type of package.

Package list (1)

Package	Number of pins	Lead pitch (mm)	Body height (mm)	Body size (mm)
QFP (FP)	160	0.5	2.7	24 × 24
	208	0.5	3.2	28 × 28
	240	0.5	3.2	32 × 32
	304	0.5	3.7	40 × 40
TQFP	48	0.5	1.0	7 × 7
	64	0.65	1.0	12 × 12
	80	0.5	1.0	12 × 12
LQFP	44	0.8	1.4	10 × 10
	100	0.5	1.4	14 × 14
	160	0.5	1.4	24 × 24

Package list (2) (preliminary)

Master name	μ PD65880	μ PD65881	μ PD65882	μ PD65883	μ PD65884
160-pin QFP (FP)	—	—	—	—	—
208-pin QFP (FP)	—	—	—	—	—
240-pin QFP (FP)	—	—	—	—	—
304-pin QFP (FP)	—	—	—	—	—
48-pin TQFP	○	○	○	—	—
64-pin TQFP	—	○	○	○	
80-pin TQFP	—	—	○	○	
44-pin LQFP	○	○			
100-pin LQFP (FP)	—	—	○	○	○
160-pin LQFP	—	—	—	—	○

Master name	μ PD65885	μ PD65887	μ PD65889	μ PD65890	μ PD65893
160-pin QFP (FP)	○	○	—	—	—
208-pin QFP (FP)	○	○	○	○	○
240-pin QFP (FP)	—	○	○	○	○
304-pin QFP (FP)	—	—	—	○	○
48-pin TQFP	—	—	—	—	—
64-pin TQFP					
80-pin TQFP					
44-pin LQFP				—	—
100-pin LQFP (FP)	○	○			
160-pin LQFP	—	—	○	○	

Remark ○ : Released — : Not to be supported Blank : Under consideration

Development Tools

Easy interface with your EWSs or PCs

To develop products using the CMOS-N5 family, the following design tools can be used.

- OPENCAD™
- Personal OPENCAD
- Design Compiler™
- PrimeTime™
- VCS™ (PC version only)
- Verilog-XL™
- ModelSim™

OPENCAD is a trademark of NEC Corp.

Design Compiler, PrimeTime and VCS are trademarks of Synopsys, Inc.

Verilog-XL is a trademark of Cadence Design Systems Inc.

ModelSim is a trademark of Model Technology Inc.

The export of this product from Japan is regulated by the Japanese government. To export this product may be prohibited without governmental license, the need for which must be judged by the customer. The export or re-export of this product from a country other than Japan may also be prohibited without a license from that country. Please call an NEC sales representative.

- **The information in this document is based on documents issued in November, 1999 at the latest. The information is subject to change without notice. For actual design-in, refer to the latest publications of data sheet, etc., for the most up-to-date specifications of the device.**
 - No part of this document may be copied or reproduced in any form or by any means without the prior written consent of NEC Corporation. NEC Corporation assumes no responsibility for any errors which may appear in this document.
 - NEC Corporation does not assume any liability for infringement of patents, copyrights or other intellectual property rights of third parties by or arising from use of a device described herein or any other liability arising from use of such device. No license, either express, implied or otherwise, is granted under any patents, copyrights or other intellectual property rights of NEC Corporation or others.
 - Descriptions of circuits, software, and other related information in this document are provided for illustrative purposes in semiconductor product operation and application examples. The incorporation of these circuits, software, and information in the design of the customer's equipment shall be done under the full responsibility of the customer. NEC Corporation assumes no responsibility for any losses incurred by the customer or third parties arising from the use of these circuits, software, and information.
 - While NEC Corporation has been making continuous effort to enhance the reliability of its semiconductor devices, the possibility of defects cannot be eliminated entirely. To minimize risks of damage or injury to persons or property arising from a defect in an NEC semiconductor device, customers must incorporate sufficient safety measures in its design, such as redundancy, fire-containment, and anti-failure features.
 - NEC devices are classified into the following three quality grades:
"Standard", "Special", and "Specific". The Specific quality grade applies only to devices developed based on a customer designated "quality assurance program" for a specific application. The recommended applications of a device depend on its quality grade, as indicated below. Customers must check the quality grade of each device before using it in a particular application.
 - Standard: Computers, office equipment, communications equipment, test and measurement equipment, audio and visual equipment, home electronic appliances, machine tools, personal electronic equipment and industrial robots
 - Special: Transportation equipment (automobiles, trains, ships, etc.), traffic control systems, anti-disaster systems, anti-crime systems, safety equipment and medical equipment (not specifically designed for life support)
 - Specific: Aircraft, aerospace equipment, submersible repeaters, nuclear reactor control systems, life support systems or medical equipment for life support, etc.
- The quality grade of NEC devices is "Standard" unless otherwise specified in NEC's Data Sheets or Data Books. If customers intend to use NEC devices for applications other than those specified for Standard quality grade, they should contact an NEC sales representative in advance.

For further information, please contact:

NEC Corporation

NEC Building
7-1, Shiba 5-chome, Minato-ku
Tokyo 108-8001, Japan
Tel: 03-3454-1111
<http://www.ic.nec.co.jp/>

[North & South America]

NEC Electronics Inc.

2880 Scott Blvd.
Santa Clara, CA 95050-2554, U.S.A.
Tel: 408-588-6000
800-366-9782
Fax: 408-588-6130
800-729-9288
<http://www.necel.com/>

NEC do Brasil S.A.

Electron Devices Division
Rodovia Presidente Dutra, Km 214
07210-902-Guarulhos-SP Brasil
Tel: 55-11-6465-6810
Fax: 55-11-6465-6829

[Europe]

NEC Electronics (Germany) GmbH

Kanzlerstr. 2,
40472 Düsseldorf
Germany
Tel: 0211-650302
Fax: 0211-6503490
<http://www.nec.de/>

Munich Office

Arabellastr. 17
81925 München, Germany
Tel: 089-921003-0
Fax: 089-92100315

Stuttgart Office

Industriestr. 3
70507 Stuttgart, Germany
Tel: 0711-99010-0
Fax: 0711-99010-19

Hannover Office

Podbielskistr. 164
D-30177 Hannover, Germany
Tel: 0511-33402-0
Fax: 0511-33402-34

Benelux Office

Boschdijk 187a
5612 HB Eindhoven,
The Netherlands
Tel: 040-2445845
Fax: 040-2444580

Scandinavia Office

P.O. Box 134
18322 Taeby, Sweden
Tel: 08-6380820
Fax: 08-6380388

NEC Electronics (UK) Limited

Cygnus House, Sunrise Park Way,
Milton Keynes, MK14 6NP, U.K.
Tel: 01908-691-133
Fax: 01908-670-290

NEC Electronics (France) S.A.

9, rue Paul Dautier-BP 187
78142 Velizy-Villacoublay Cédex
France
Tel: 01-30-67-58-00
Fax: 01-30675899

Madrid Office

Juan Esplandiu, 15
28007 Madrid, Spain
Tel: 91-504-2787
Fax: 91-504-2860

NEC Electronics Italiana s.r.l.

Via Fabio Filzi, 25/A,
20124 Milano, Italy
Tel: 02-667541
Fax: 02-66754299

[Asia & Oceania]

NEC Electronics Hong Kong Limited

12/F., Cityplaza 4,
12 Taikoo Wan Road, Hong Kong
Tel: 2886-9318
Fax: 2886-9022/9044

Seoul Branch

10F, ILSONG Bldg., 157-37,
Samsung-Dong, Kangnam-Ku
Seoul, the Republic of Korea
Tel: 02-528-0303
Fax: 02-528-4411

NEC Electronics Taiwan Ltd.

7F, No. 363 Fu Shing North Road
Taipei, Taiwan, R. O. C.
Tel: 02-2719-2377
Fax: 02-2719-5951

NEC Electronics Singapore Pte. Ltd.

101 Thomson Road #04-01/05
United Square, Singapore 307591
Tel: 65-253-8311
Fax: 65-250-3583