


OVERVIEW

The SM5050A is a single-output clock generator IC that generates standard high-frequency clocks derived from a 20 to 40MHz crystal oscillator master clock. The high-frequency output stage uses optimized PLL circuits for low jitter output. The oscillator capacitors C_G and C_D are built-in, realizing a high-frequency output oscillator by just the connection of a crystal. Two program inputs allows selection from 4 frequency multipliers, making the SM5050A able to generate multi-standard frequency clock outputs.

FEATURES

- 2.7 to 3.6V operating supply voltage
- 20 to 40MHz master clock frequency (fundamental)
- Output frequency ranges
 - 100 to 166.6MHz ($V_{DD} = V_{DDQ} = 3.0$ to 3.6V)
 - 100 to 125MHz ($V_{DD} = V_{DDQ} = 2.7$ to 3.6V)
- 8mA output drive capability
- Oscillator capacitors (C_G , C_D) and feedback resistor (R_f) built-in
- 100ps (typ) low jitter output (peak-to-peak)
- 2 program inputs for 4 selectable multiplier ratios
- Standby function
- Packaging
 - Chip form (CF5050A)
 - 8-pin VSOP package (SM5050AV)


PINOUT




ORDERING INFORMATION

Device	Package
CF5050A-1	Chip form
SM5050AV	8-pin VSOP


PAD DIMENSIONS



PACKAGE DIMENSIONS



BLOCK DIAGRAM



PIN DESCRIPTION

SM5050AV		CF5050A			I/O ¹	Description
Number	Name	Name	Pad dimensions [μm]			
			X	Y		
1	P1	P1	620	1330	Ip	Program input 1. Selects the output frequency multiplier ratio.
2	VSS	VSS	290	1132	–	Ground
		VSSQ	290	920	–	Output circuit ground
3	Q	Q	290	569	O	Output (CMOS)
4	VDD	VDDQ	540	240	–	Output circuit supply
		VDD	906	240	–	Supply
5	XTN	XTN	1524	240	O	Crystal oscillator connection pins. Crystal connected between XT and XTN.
6	XT	XT	1870	542	I	
7	INH N	INH N	1870	1015	Ip	Operating state control (inhibit). When INHN is LOW, output is high impedance and PLL circuits stop.
8	P0	P0	1540	1330	Ip	Program input 0. Selects the output frequency multiplier ratio.

1. Ip = input with built-in pull-up resistor.

OUTPUT FREQUENCY SETTINGS

Program inputs		Multiplier ratio	Master clock frequency [MHz]	Output frequency [MHz]	Supply voltage [V]
P0	P1				
LOW	LOW	$\times 4$	25.00	100	2.7 to 3.6
LOW	HIGH	$\times 4.25$	25.00	106.25	
HIGH	LOW	$\times 5$	25.00	125	
			26.66	133.3	3.0 to 3.6
HIGH	HIGH	$\times 6.25$	24.8832	155.52	
			26.66	166.6	

Note: The output frequency range is 100 to 166.6MHz. The master clock frequency can be adjusted to any value within the range 20 to 40MHz, so the master clock frequency and multiplier should be selected such that the output frequency is within the output frequency range.

SPECIFICATIONS

Absolute Maximum Ratings

$V_{SS} = 0V$

Parameter	Symbol	Condition	Rating	Unit
Supply voltage range	V_{DD}		-0.5 to 6.0	V
Input voltage range	V_{IN}		-0.5 to $V_{DD} + 0.5$	V
Output voltage range	V_{OUT}		-0.5 to $V_{DD} + 0.5$	V
Storage temperature range	T_{stg}	CF5050A	-65 to 150	°C
		SM5050AV	-55 to 125	°C
Operating temperature range	T_{opr}		-40 to 85	°C
Output current	I_{OUT}		25	mA
Power dissipation	P_D	SM5050AV	150	mW

Recommended Operating Conditions

$V_{SS} = 0V$, $f_{OUT} = 100$ to 166.6MHz, $C_L = 15pF$

Parameter	Symbol	Condition	Rating			Unit
			min	typ	max	
Operating supply voltage	V_{DD}	$f_{OUT} \leq 125MHz$	2.7	-	3.6	V
		$f_{OUT} \leq 166.6MHz$	3.0	-	3.6	
Input voltage	V_{IN}		V_{SS}	-	V_{DD}	V
Operating temperature	T_{opr}		-20	-	80	°C

DC Characteristics

$V_{DD} = 2.7$ to $3.6V$, $V_{SS} = 0V$, $T_a = -20$ to $80^{\circ}C$ unless otherwise noted

Parameter	Symbol	Condition		Rating			Unit
				min	typ	max	
Q HIGH-level output voltage	V _{OH}	V _{DD} = 2.7V, I _{OH} = 8mA		2.2	–	–	V
Q LOW-level output voltage	V _{OL}	V _{DD} = 2.7V, I _{OL} = 8mA		–	–	0.4	V
Q output leakage current	I _Z	Measurement circuit 4, INHN = V _{SS}	V _{OH} = V _{DD}	–	–	10	μA
			V _{OL} = V _{SS}	–	–	10	
INHN HIGH-level input voltage	V _{IH1}			0.7V _{DD}	–	–	V
P0, P1 HIGH-level input voltage	V _{IH2}			0.9V _{DD}	–	–	V
INHN LOW-level input voltage	V _{IL1}			–	–	0.3V _{DD}	V
P0, P1 LOW-level input voltage	V _{IL2}			–	–	0.1V _{DD}	V
Current consumption	I _{DD}	25MHz crystal, measurement circuit 1, load circuit 1, INHN = open, C _L = 15pF, P0 = HIGH, P1 = LOW, V _{DD} = 3.0V		–	23	–	mA
		25MHz crystal, measurement circuit 1, load circuit 1, INHN = open, C _L = 15pF, P0 = HIGH, P1 = LOW		–	–	42	
Standby current	I _{ST}	INHN = V _{SS} , measurement circuit 1		–	–	40	μA
INHN, P0, P1 input pull-up resistance	R _{UP1}	V _{DD} = 3V, measurement circuit 2		0.3	–	6	MΩ
	R _{UP2}			10	–	200	kΩ
Negative resistance	–R _L	V _{DD} = 3V, Ta = 25°C, f = 30MHz		–	–240	–	Ω
Feedback resistance	R _f	Measurement circuit 3		100	300	900	kΩ
Internal capacitance	C _G	Design values		15.98	18.44	20.90	pF
	C _D			15.98	18.44	20.90	pF


Switching Characteristics

$V_{DD} = 2.7$ to $3.6V$, $V_{SS} = 0V$, $T_a = -20$ to $80^\circ C$ unless otherwise noted

Parameter	Symbol	Condition		Rating			Unit
				min	typ	max	
Output rise time	t _r	0.2V _{DD} → 0.8V _{DD} , measurement circuit 1, load circuit 1, C _L = 15pF		–	1	2.5	ns
Output fall time	t _f	0.8V _{DD} → 0.2V _{DD} , measurement circuit 1, load circuit 1, C _L = 15pF		–	1	2.5	ns
Output duty cycle	Duty	V _{DD} = 3V, Ta = 25°C, measurement circuit 1, load circuit 1, C _L = 15pF, f ≤ 166.6MHz		40	–	60	%
Output disable delay time ¹	t _{PLZ}	V _{DD} = 3V, Ta = 25°C, measurement circuit 1, load circuit 1, C _L = 15pF		–	–	100	ns
Startup time ^{2,3}	t _{SZL}	V _{DD} = 3V, Ta = 25°C, measurement circuit 1, load circuit 1, C _L = 15pF		–	1	–	ms
Oscillator frequency	f	Measurement circuit 1		20	–	40	MHz
Output frequency	f _{OUT}	Measurement circuit 1	V _{DD} = 2.7V	100	–	125	MHz
			V _{DD} = 3.0V	100	–	166.6	
Output clock jitter ³	Jitter	V _{DD} = 3V, Ta = 25°C, 25MHz crystal, P0 = HIGH, P1 = LOW, measurement circuit 1, load circuit 1, C _L = 15pF, peak-to-peak		–	100	–	ps

1. Time from when INHN goes LOW until Q output goes high impedance.
2. Time from when either INHN goes LOW to HIGH or supply voltage $V_{DD} = 3.0V$ until normal signal output.
3. Measured values using NPC characteristics standard evaluation board and standard crystal.


NPC STANDARD CRYSTAL DATA




f (MHz)	R (Ω)	L (mH)	C_a (fF)	C_b (pF)
25	4.368	1.885	21.52	4.793
27	7.421	2.402	14.48	4.097

MEASUREMENT CIRCUITS


Measurement Circuit 1




Measurement Circuit 4




Measurement Circuit 2



Load Circuit 1




Measurement Circuit 3




Switching Time Measurement Waveforms


Output duty level



Output duty cycle time



Output Disable Delay Time/Startup Time



NIPPON PRECISION CIRCUITS INC. reserves the right to make changes to the products described in this data sheet in order to improve the design or performance and to supply the best possible products. Nippon Precision Circuits Inc. assumes no responsibility for the use of any circuits shown in this data sheet, conveys no license under any patent or other rights, and makes no claim that the circuits are free from patent infringement. Applications for any devices shown in this data sheet are for illustration only and Nippon Precision Circuits Inc. makes no claim or warranty that such applications will be suitable for the use specified without further testing or modification. The products described in this data sheet are not intended to use for the apparatus which influence human lives due to the failure or malfunction of the products. Customers are requested to comply with applicable laws and regulations in effect now and hereinafter, including compliance with export controls on the distribution or dissemination of the products. Customers shall not export, directly or indirectly, any products without first obtaining required licenses and approvals from appropriate government agencies.



NIPPON PRECISION CIRCUITS INC.

4-3, Fukuzumi 2-chome
Koto-ku, Tokyo 135-8430, Japan
Telephone: 03-3642-6661
Facsimile: 03-3642-6698

NC9921AE 2000.07