

LM715 High Speed Operational Amplifier

General Description

The LM715 is a high speed, high gain, monolithic operational amplifier intended for use in a wide range of applications where fast signal acquisition or wide bandwidth is required. The LM715 features fast settling time, high slew rate, low offsets, and high output swing for large signal applications. In addition, the device displays excellent temperature stability and will operate over a wide range of supply voltages.

Features


- High slew rate— 100 V/ μ s (Inverting, $A_V = 1$) typically
- Fast settling time— 800 ns typically
- Wide bandwidth— 65 MHz typically
- Wide operating supply range
- Wide input voltage ranges

Applications

- Video amplifiers
- Active filters
- High speed data conversion

Connection Diagrams

10-Lead Metal Package




Top View

TL/H/10059-1

Lead 5 connected to case.

14-Lead DIP



Top View

TL/H/10059-2

Ordering Information

| Device Code | Package Code | Package Description |
|-------------|--------------|---------------------|
| LM715MH | H10C | Metal |
| LM715CH | H10C | Metal |
| LM715MJ | J14A | Ceramic DIP |
| LM715CJ | J14A | Ceramic DIP |

Absolute Maximum Ratings

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

| | |
|-----------------------------|-----------------|
| Storage Temperature Range | −65°C to +175°C |
| Operating Temperature Range | |
| Extended (LM715M) | −55°C to +125°C |
| Commercial (LM715C) | 0°C to +70°C |

Lead Temperature
Metal Can and Ceramic DIP
(Soldering, 60 sec.)

300°C

Internal Power Dissipation (Notes 1, 2)

| | |
|-----------------|-------|
| 10L-Metal Can | 1.07W |
| 14L-Ceramic DIP | 1.36W |

| | |
|----------------------------|------|
| Supply Voltage | ±18V |
| Differential Input Voltage | ±5V |
| Input Voltage (Note 3) | ±15V |

LM715M and LM715C

Electrical Characteristics $T_A = 25^\circ\text{C}$, $V_{CC} = \pm 15\text{V}$, unless otherwise specified

| Symbol | Parameter | Conditions | LM715M | | | LM715C | | | Units |
|----------|---------------------------|--|--------|-----|-----|--------|-----|------|------------------|
| | | | Min | Typ | Max | Min | Typ | Max | |
| V_{IO} | Input Offset Voltage | $R_S \leq 10\text{ k}\Omega$ | | 2.0 | 5.0 | | 2.0 | 7.5 | mV |
| I_{IO} | Input Offset Current | | | 70 | 250 | | 70 | 250 | nA |
| I_{IB} | Input Bias Current | | | 400 | 750 | | 400 | 1500 | nA |
| Z_I | Input Impedance | | | 1.0 | | | 1.0 | | M Ω |
| R_O | Output Resistance | | | 75 | | | 75 | | Ω |
| I_{CC} | Supply Current | | | 5.5 | 7.0 | | 5.5 | 10 | mA |
| P_C | Power Consumption | | | 165 | 210 | | 165 | 300 | mW |
| V_{IR} | Input Voltage Range | | ±10 | ±12 | | ±10 | ±12 | | V |
| A_{VS} | Large Signal Voltage Gain | $R_L \geq 2.0\text{ k}\Omega$, $V_O = \pm 10\text{V}$ | 15 | 30 | | 10 | 30 | | V/mV |
| V | Settling Time | $V_O = \pm 5.0\text{V}$, $A_V = 1.0$ | | 800 | | | 800 | | ns |
| TR | Transient Response | Rise Time | | 30 | 60 | | 30 | 75 | ns |
| | | Overshoot | | 25 | 40 | | 25 | 50 | % |
| SR | Slew Rate | $A_V = 100$ | | 70 | | | 70 | | V/ μs |
| | | $A_V = 10$ | | 38 | | | 38 | | |
| | | $A_V = 1.0$ (Non-Inverting) | 15 | 18 | | 10 | 18 | | |
| | | $A_V = 1.0$ (Inverting) | | 100 | | | 100 | | |

The following specifications apply over the range of $-55^\circ\text{C} \leq T_A \leq +125^\circ\text{C}$ for the LM715M, and $0^\circ\text{C} \leq T_A \leq +70^\circ\text{C}$ for the LM715C

| Symbol | Parameter | Conditions | LM715M | | | LM715C | | | Units |
|----------|------------------------------|---|--------|-----|------|----------------|----------------|-----------------|-----------------|
| | | | Min | Typ | Max | Min | Typ | Max | |
| V_{IO} | Input Offset Voltage | $R_S \leq 10\text{ k}\Omega$ | | | 7.5 | | | 10 | mV |
| I_{IO} | Input Offset Current | $T_A = T_{A\text{ Max}}$ | | | 250 | | | 250 | nA |
| | | $T_A = T_{A\text{ Min}}$ | | | 800 | | | 750 | |
| I_{IB} | Input Bias Current | $T_A = T_{A\text{ Max}}$ | | | 0.75 | | | 1.5 | μA |
| | | $T_A = T_{A\text{ Min}}$ | | | 4.0 | | | 7.5 | |
| CMR | Common Mode Rejection | $R_S \leq 10\text{ k}\Omega$ | 74 | 92 | | 74 (Note 4) | 92 (Note 4) | | dB |
| PSRR | Power Supply Rejection Ratio | $R_S \leq 10\text{ k}\Omega$ | | 45 | 300 | | 45 (Note 4) | 400 (Note 4) | $\mu\text{V/V}$ |
| A_{VS} | Large Signal Voltage Gain | $R_L \geq 2.0\text{ k}\Omega$, $V_O = \pm 10\text{V}$ | 10 | | | 8 | | | V/mV |
| V_{OP} | Output Voltage Swing | $R_L = 2.0\text{ k}\Omega$ | ±10 | ±13 | | ±10 | ±13 | | V |


Note 1: $T_J\text{ Max} = 175^\circ\text{C}$.

Note 2: Ratings apply to ambient temperature at 25°C . Above this temperature, derate the 10L-Metal Can at $7.1\text{ mW}/^\circ\text{C}$, and the 14L-Ceramic DIP at $9.1\text{ mW}/^\circ\text{C}$.

Note 3: For supply voltages less than $\pm 15\text{V}$, the absolute maximum input voltage is equal to the supply voltage.

Note 4: $T_A = 25^\circ\text{C}$ only.

Typical Performance Characteristics for LM715M and LM715C




Note 1: See "Non-Inverting Compensation Components Value Table" for Closed Loop Gain values.


TL/H/10059-4

Typical Performance Characteristics for LM715M and LM715C (Continued)


Output Swing vs Frequency for Closed Loop Gains




Supply Voltage Rejection Ratio vs Frequency




Common Mode Rejection Ratio vs Frequency




Unity Gain Large Signal Pulse Response




Large Signal Pulse Response for Gain 10




Large Signal Pulse Response for Gain 100




Slew Rate vs Closed Loop Voltage Gain




Slew Rate vs Supply Voltage




Voltage Follower Transient Response



Inverting Unity Gain Large Signal Pulse Response




Small Signal Pulse Response Inverting Unity Gain



TL/H/10059-5


Typical Performance Characteristics for LM715M and LM715C (Continued)

Voltage Follower (Note 2)




TL/H/10059-6

Voltage Offset Null Circuit (Note 2)



TL/H/10059-7


High Slew Rate Circuit (Note 2)



TL/H/10059-8

Note 2: Lead numbers apply to metal package.

Equivalent Circuit



TL/H/10059-3


Applications Information

**Non-Inverting Compensation
Components Values**

| Closed Loop Gain | C1 | C2 | C3 |
|------------------|--------|---------|---------|
| 1000 | 10 pF | | |
| 100 | 50 pF | | 250 pF |
| 10 (Note) | 100 pF | 500 pF | 1000 pF |
| 1 | 500 pF | 2000 pF | 1000 pF |


Note: For gain 10, compensation may be simplified by removing C2, C3 and adding a 200 pF capacitor (C4) between Lead 7 and 10.

Frequency Compensation Circuit



TL/H/10059-9

**Suggested Values of Compensation Capacitors vs
Closed Loop Voltage Gain**



TL/H/10059-10

Layout Instructions

Layout—The layout should be such that stray capacitance is minimal.


Supplies—The supplies should be adequately bypassed. Used of 0.1 μ F high quality ceramic capacitors is recommended.

Note: All lead numbers on this page apply to metal package.

Ringing—Excessive ringing (long acquisition time) may occur with large capacitive loads. This may be reduced by isolating the capacitive load with a resistance of 100 Ω . Large source resistances may also give rise to the same problem and this may be decreased by the addition of a capacitance across the feedback resistance. A value of around 50 pF for unity gain configuration and around 3.0 pF for gain 10 should be adequate.


Latch Up—This may occur when the amplifier is used as a voltage follower. The inclusion of a diode between leads 6 and 2 with the cathode toward lead 2 is the recommended preventive measure.

Typical Applications




TL/H/10059-14

High Speed Integrator




TL/H/10059-13

Typical Applications (Continued)




Note: All lead numbers shown refer to metal package.




TL/H/10059-12

Physical Dimensions inches (millimeters)



10-Lead Metal Can Package (H)
Order Number LM715CH or LM715MH
NS Package Number H10C

Physical Dimensions inches (millimeters) (Continued)

14-Lead Ceramic Dual-In-Line Package (J)
Order Number LM715CJ or LM715MJ
NS Package Number J14A

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



National Semiconductor Corporation
 1111 West Bardin Road
 Arlington, TX 76017
 Tel: 1(800) 272-9959
 Fax: 1(800) 737-7018

National Semiconductor Europe
 Fax: (+49) 0-180-530 85 86
 Email: cnjwge@tevm2.nsc.com
 Deutsch Tel: (+49) 0-180-530 85 85
 English Tel: (+49) 0-180-532 78 32
 Français Tel: (+49) 0-180-532 93 58
 Italiano Tel: (+49) 0-180-534 16 80

National Semiconductor Hong Kong Ltd.
 19th Floor, Straight Block,
 Ocean Centre, 5 Canton Rd.
 Tsimshatsui, Kowloon
 Hong Kong
 Tel: (852) 2737-1600
 Fax: (852) 2736-9960

National Semiconductor Japan Ltd.
 Tel: 81-043-299-2309
 Fax: 81-043-299-2408

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.