

LM741 Operational Amplifier


General Description

The LM741 series are general purpose operational amplifiers which feature improved performance over industry standards like the LM709. They are direct, plug-in replacements for the 709C, LM201, MC1439 and 748 in most applications.


The amplifiers offer many features which make their application nearly foolproof: overload protection on the input and output, no latch-up when the common mode range is exceeded, as well as freedom from oscillations.

The LM741C/LM741E are identical to the LM741/LM741A except that the LM741C/LM741E have their performance guaranteed over a 0°C to +70°C temperature range, instead of -55°C to +125°C.

Schematic Diagram



Offset Nulling Circuit



Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

(Note 6)

| | LM741A | LM741E | LM741 | LM741C |
|---|-----------------|-----------------|-----------------|-----------------|
| Supply Voltage | ±22V | ±22V | ±22V | ±18V |
| Power Dissipation (Note 2) | 500 mW | 500 mW | 500 mW | 500 mW |
| Differential Input Voltage | ±30V | ±30V | ±30V | ±30V |
| Input Voltage (Note 3) | ±15V | ±15V | ±15V | ±15V |
| Output Short Circuit Duration | Continuous | Continuous | Continuous | Continuous |
| Operating Temperature Range | –55°C to +125°C | 0°C to +70°C | –55°C to +125°C | 0°C to +70°C |
| Storage Temperature Range | –65°C to +150°C | –65°C to +150°C | –65°C to +150°C | –65°C to +150°C |
| Junction Temperature | 150°C | 100°C | 150°C | 100°C |
| Soldering Information | | | | |
| N-Package (10 seconds) | 260°C | 260°C | 260°C | 260°C |
| J- or H-Package (10 seconds) | 300°C | 300°C | 300°C | 300°C |
| M-Package | | | | |
| Vapor Phase (60 seconds) | 215°C | 215°C | 215°C | 215°C |
| Infrared (15 seconds) | 215°C | 215°C | 215°C | 215°C |
| See AN-450 "Surface Mounting Methods and Their Effect on Product Reliability" for other methods of soldering surface mount devices. | | | | |
| ESD Tolerance (Note 7) | 400V | 400V | 400V | 400V |

Electrical Characteristics (Note 4)

| Parameter | Conditions | LM741A/LM741E | | | LM741 | | | LM741C | | | Units |
|---------------------------------------|---|---------------|-----|-------|-------|-----|-----|--------|-----|-----|------------------------------|
| | | Min | Typ | Max | Min | Typ | Max | Min | Typ | Max | |
| Input Offset Voltage | $T_A = 25^\circ\text{C}$ | | | | | | | | | | mV |
| | $R_S \leq 10\text{ k}\Omega$ | | | | | 1.0 | 5.0 | | 2.0 | 6.0 | mV |
| | $R_S \leq 50\Omega$ | | 0.8 | 3.0 | | | | | | | mV |
| | $T_{AMIN} \leq T_A \leq T_{AMAX}$ | | | 4.0 | | | | | | | mV |
| Average Input Offset Voltage Drift | $R_S \leq 50\Omega$ | | | | | | 6.0 | | | 7.5 | mV |
| | $R_S \leq 10\text{ k}\Omega$ | | | | | | | | | | mV |
| | | | | 15 | | | | | | | $\mu\text{V}/^\circ\text{C}$ |
| | | | | | | | | | | | |
| Input Offset Voltage Adjustment Range | $T_A = 25^\circ\text{C}, V_S = \pm 20\text{V}$ | ±10 | | | | ±15 | | | ±15 | | mV |
| Input Offset Current | $T_A = 25^\circ\text{C}$ | | 3.0 | 30 | | 20 | 200 | | 20 | 200 | nA |
| | $T_{AMIN} \leq T_A \leq T_{AMAX}$ | | | 70 | | 85 | 500 | | | 300 | nA |
| | | | | | | | | | | | nA |
| Average Input Offset Current Drift | | | | 0.5 | | | | | | | $\text{nA}/^\circ\text{C}$ |
| Input Bias Current | $T_A = 25^\circ\text{C}$ | | 30 | 80 | | 80 | 500 | | 80 | 500 | nA |
| | $T_{AMIN} \leq T_A \leq T_{AMAX}$ | | | 0.210 | | | 1.5 | | | 0.8 | μA |
| | | | | | | | | | | | |
| Input Resistance | $T_A = 25^\circ\text{C}, V_S = \pm 20\text{V}$ | 1.0 | 6.0 | | 0.3 | 2.0 | | 0.3 | 2.0 | | $\text{M}\Omega$ |
| | $T_{AMIN} \leq T_A \leq T_{AMAX}, V_S = \pm 20\text{V}$ | 0.5 | | | | | | | | | $\text{M}\Omega$ |
| | | | | | | | | | | | |
| Input Voltage Range | $T_A = 25^\circ\text{C}$ | | | | | | | ±12 | ±13 | | V |
| | $T_{AMIN} \leq T_A \leq T_{AMAX}$ | | | | ±12 | ±13 | | | | | V |

Electrical Characteristics (Note 4) (Continued)

| Parameter | Conditions | LM741A/LM741E | | | LM741 | | | LM741C | | | Units |
|--------------------------------|---|----------------------|-------------|------------|----------------------|----------------------|-----------|----------------------|----------------------|-----|----------------------|
| | | Min | Typ | Max | Min | Typ | Max | Min | Typ | Max | |
| Large Signal Voltage Gain | $T_A = 25^\circ\text{C}$, $R_L \geq 2\text{ k}\Omega$ $V_S = \pm 20\text{V}$, $V_O = \pm 15\text{V}$ $V_S = \pm 15\text{V}$, $V_O = \pm 10\text{V}$ | 50 | | | 50 | 200 | | 20 | 200 | | V/mV V/mV |
| | $T_{AMIN} \leq T_A \leq T_{AMAX}$, $R_L \geq 2\text{ k}\Omega$, $V_S = \pm 20\text{V}$, $V_O = \pm 15\text{V}$ $V_S = \pm 15\text{V}$, $V_O = \pm 10\text{V}$ $V_S = \pm 5\text{V}$, $V_O = \pm 2\text{V}$ | 32 | | | 25 | | | 15 | | | V/mV V/mV V/mV |
| | | 10 | | | | | | | | | |
| | | | | | | | | | | | |
| Output Voltage Swing | $V_S = \pm 20\text{V}$ $R_L \geq 10\text{ k}\Omega$ $R_L \geq 2\text{ k}\Omega$ | ± 16 ± 15 | | | | | | | | | V V |
| | $V_S = \pm 15\text{V}$ $R_L \geq 10\text{ k}\Omega$ $R_L \geq 2\text{ k}\Omega$ | | | | ± 12 ± 10 | ± 14 ± 13 | | ± 12 ± 10 | ± 14 ± 13 | | V V |
| | | | | | | | | | | | |
| | | | | | | | | | | | |
| Output Short Circuit Current | $T_A = 25^\circ\text{C}$ | 10 | 25 | 35 | | 25 | | | 25 | | mA |
| | $T_{AMIN} \leq T_A \leq T_{AMAX}$ | 10 | | 40 | | | | | | | mA |
| Common-Mode Rejection Ratio | $T_{AMIN} \leq T_A \leq T_{AMAX}$ $R_S \leq 10\text{ k}\Omega$, $V_{CM} = \pm 12\text{V}$ $R_S \leq 50\Omega$, $V_{CM} = \pm 12\text{V}$ | | | | 70 | 90 | | 70 | 90 | | dB dB |
| | | 80 | 95 | | | | | | | | |
| Supply Voltage Rejection Ratio | $T_{AMIN} \leq T_A \leq T_{AMAX}$, $V_S = \pm 20\text{V}$ to $V_S = \pm 5\text{V}$ $R_S \leq 50\Omega$ $R_S \leq 10\text{ k}\Omega$ | 86 | 96 | | 77 | 96 | | 77 | 96 | | dB dB |
| | | | | | | | | | | | |
| Transient Response | $T_A = 25^\circ\text{C}$, Unity Gain | | | | | | | | | | |
| | | | 0.25 6.0 | 0.8 20 | | 0.3 5 | | | 0.3 5 | | μs % |
| Bandwidth (Note 5) | $T_A = 25^\circ\text{C}$ | 0.437 | 1.5 | | | | | | | | MHz |
| Slew Rate | $T_A = 25^\circ\text{C}$, Unity Gain | 0.3 | 0.7 | | | 0.5 | | | 0.5 | | V/ μs |
| Supply Current | $T_A = 25^\circ\text{C}$ | | | | | 1.7 | 2.8 | | 1.7 | 2.8 | mA |
| Power Consumption | $T_A = 25^\circ\text{C}$ $V_S = \pm 20\text{V}$ $V_S = \pm 15\text{V}$ | | 80 | 150 | | | | | | | mW mW |
| | LM741A | | | | | | | | | | |
| | | | | | | | | | | | |
| | LM741E | | | 165 135 | | | | | | | mW mW |
| | | | | | | | | | | | |
| | LM741 | | | 150 150 | | | | | | | mW mW |
| | | | | | | | | | | | |
| | | | | | | 60 45 | 100 75 | | | | mW mW |

Note 1: "Absolute Maximum Ratings" indicate limits beyond which damage to the device may occur. Operating Ratings indicate conditions for which the device is functional, but do not guarantee specific performance limits.

Electrical Characteristics (Note 4) (Continued)

Note 2: For operation at elevated temperatures, these devices must be derated based on thermal resistance, and T_J max. (listed under "Absolute Maximum Ratings"). $T_J = T_A + (\theta_{JA} P_D)$.

| Thermal Resistance | Cerdip (J) | DIP (N) | HO8 (H) | SO-8 (M) |
|-------------------------------------|------------|---------|---------|----------|
| θ_{JA} (Junction to Ambient) | 100°C/W | 100°C/W | 170°C/W | 195°C/W |
| θ_{JC} (Junction to Case) | N/A | N/A | 25°C/W | N/A |

Note 3: For supply voltages less than $\pm 15V$, the absolute maximum input voltage is equal to the supply voltage.

Note 4: Unless otherwise specified, these specifications apply for $V_S = \pm 15V$, $-55^\circ C \leq T_A \leq +125^\circ C$ (LM741/LM741A). For the LM741C/LM741E, these specifications are limited to $0^\circ C \leq T_A \leq +70^\circ C$.


Note 5: Calculated value from: BW (MHz) = $0.35/\text{Rise Time}(\mu s)$.

Note 6: For military specifications see RETS741X for LM741 and RETS741AX for LM741A.

Note 7: Human body model, 1.5 k Ω in series with 100 pF.

Connection Diagram


Metal Can Package



Note 8: LM741H is available per JM38510/10101


**Order Number LM741H, LM741H/883 (Note 8),
LM741AH/883 or LM741CH
See NS Package Number H08C**

Dual-In-Line or S.O. Package



**Order Number LM741J, LM741J/883,
LM741CM, LM741CN or LM741EN
See NS Package Number J08A, M08A or N08E**

Ceramic Dual-In-Line Package




Note 9: also available per JM38510/10101


Note 10: also available per JM38510/10102

**Order Number LM741J-14/883 (Note 9),
LM741AJ-14/883 (Note 10)
See NS Package Number J14A**


Ceramic Flatpak



**Order Number LM741W/883
See NS Package Number W10A**


Physical Dimensions inches (millimeters) unless otherwise noted

Metal Can Package (H)
Order Number LM741H, LM741H/883, LM741AH/883, LM741CH or LM741EH
NS Package Number H08C





Ceramic Dual-In-Line Package (J)
Order Number LM741CJ or LM741J/883
NS Package Number J08A

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)




Ceramic Dual-In-Line Package (J)
Order Number LM741J-14/883 or LM741AJ-14/883
NS Package Number J14A




Small Outline Package (M)
Order Number LM741CM
NS Package Number M08A

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)



Dual-In-Line Package (N)
Order Number LM741CN or LM741EN
NS Package Number N08E

Physical Dimensions inches (millimeters) unless otherwise noted (Continued)

10-Lead Ceramic Flatpak (W)
Order Number LM741W/883
NS Package Number W10A

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



National Semiconductor Corporation
Americas
Tel: 1-800-272-9959
Fax: 1-800-737-7018
Email: support@nsc.com

www.national.com

National Semiconductor Europe

Fax: +49 (0) 1 80-530 85 86
Email: europe.support@nsc.com
Deutsch Tel: +49 (0) 1 80-530 85 85
English Tel: +49 (0) 1 80-532 78 32
Français Tel: +49 (0) 1 80-532 93 58
Italiano Tel: +49 (0) 1 80-534 16 80

National Semiconductor Asia Pacific Customer Response Group

Tel: 65-2544466
Fax: 65-2504466
Email: sea.support@nsc.com

National Semiconductor Japan Ltd.

Tel: 81-3-5639-7560
Fax: 81-3-5639-7507